



APC Smart-UPS uninterruptible power supply (UPS) Line-Interactive 9 AC outlet(s)

Brand : APC


Product code: SMT3000RMI2U

Product name : Smart-UPS



Smart-UPS, 3000VA, RM 2U, LCD, 230V
APC Smart-UPS. UPS topology: Line-Interactive, Waveform: Sine, Input operation voltage (min): 151 V.
AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s).
Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 547 VAh, Typical backup time at full load: 3.2 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm

Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Waveform *	Sine	Rack capacity	2U
Input operation voltage (min) *	151 V	Cable length	2 m
Input operation voltage (max) *	302 V	Product colour *	Black
Input frequency *	50/60 Hz	LED indicators	Status
Output operation voltage (min)	220 V	Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Output operation voltage (max)	240 V		
Automatic Voltage Regulation (AVR)	✔	Operational conditions	
Surge energy rating	320 J	Operating temperature (T-T)	0 - 40 °C
Hold time (min)	4 ms	Storage temperature (T-T)	-15 - 45 °C
Hold time (max)	8 ms	Operating relative humidity (H-H)	0 - 95%
Efficiency	99%	Storage relative humidity (H-H)	0 - 95%
Noise level	55 dB	Operating altitude	0 - 3000 m
Audible alarm(s)	✔	Non-operating altitude	0 - 15000 m
Auto-restart	✔	Technical details	
Ports & interfaces		Sustainability certificates	ENERGY STAR
AC outlet types	C13 coupler, C19 coupler	Compliance certificates	RoHS
Power plug	C20 coupler	Weight & dimensions	
AC outlets quantity	9 AC outlet(s)	Width	480 mm
Number of output IEC jumpers	3	Depth	683 mm
USB port	✔	Height	86 mm
Battery		Weight	44.3 kg
Battery technology	Sealed Lead Acid (VRLA)	Package width	600 mm
Battery capacity	547 VAh	Package depth	980 mm
Typical backup time at full load	3.2 min	Package height	254 mm
Typical backup time at half load	11.5 min	Package weight	51.7 kg
Battery life (max)	5 year(s)	Packaging data	
Battery recharge time	3 h	Rack mount kit	✔
Hot-swap battery	✔	Cables included	RS-232, USB cable
Automatic battery test	✔	Quick installation guide	✔
Cold start	✔	Software CD	✔
Logistics data			
		Products per pallet	8 pc(s)
Other features			
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304284642



731304284642

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date