Rackmount KVM Console - Single Port VGA KVM with 19" LCD Monitor for Server Rack - Fully Featured Universal 1U LCD KVM Drawer w/Cables & Hardware - USB Support - 50,000 MTBF

**Product ID:** RKCONS1901



This rack-mount KVM console provides complete keyboard, monitor and mouse control for a single server or multiple servers, connected through a separate KVM switch (sold separately). The 19 in. console installs into 1U of rack space, offering a space-efficient solution for complete console control.

This KVM console provides all the essential controls you'll need to manage your server room at a low cost. The console features a built-in keyboard and a touchpad for intuitive control, as well as an LCD display that supports resolutions up to 1280x1024.

This versatile LCD console has a 19 in. screen. The increased screen space allows you to run multiple applications on the same screen, increasing your productivity.

The rack-mount LCD console slides out from 1U of rack space, enabling you to easily monitor and control a single server or multiple servers when connected through a KVM switch. The rack-mount VGA console features a handle that makes it easy to slide the console in and out of the server rack, keeping your area organized and clutter-free.

The rack console features a single-port KVM module, which enables you to connect it directly to a server. The module offers the flexibility you need to easily integrate it into your existing server infrastructure.

The RKCONS1901 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

## Applications

• Control a single system, or dozens of KVM-connected computers

• Improve the internal space efficiency of your server cabinet

• Manage cabinet-mounted servers and KVM switches

## Features

• FLEXIBLE DESIGN: This rackmount KVM console drawer works with all KVM switch brands and models that supports VGA and USB interfaces and conveniently slides into the server rack when not in use

• VERSATILE INTERFACES: Rack mount monitor w/ 19" Active Matrix TFT  1280 x 1024 LCD 1U height  99 key full keyboard with numeric keypad + Trackpad  Supports VGA and USB  Integrated Power Supply

• MAX DURABILITY: Features durable steel housing design and rails that withstand frequent use, rated to work in environments from 0 to 40 deg. C and a 50,000 hour MTBF

• TESTED AND PROVEN: Our KVM consoles are backed by a 2 year warranty with 24/5 by multi-lingual tech support based in North America with free technical support for the life of the product

• KVM Collection: Can be purchased with integrated 8-port (RKCONS1908K) or 16-port (RKCONS1916K) KVM or use with StarTech.com enterprise KVM switches: SV831DUSB, SV831DUSBUK, SV1631DUSBU, SV1631DUSBUK

**Hardware**

| | | |
|---|---|---|
| Warranty | 2 Years | |
| U Height | 1U | |
| Front Door Key Lock | No | |
| Audio | No | |
| Display Size | 19in | |
| Panel Type | Active Matrix TFT LCD | |
| KVM Ports | 1 | |
| PC Interface | USB | |
| PC Video Type | VGA | |
| Number of Monitors Supported | 1 | |
| Rack-Mountable | Yes | |
| Cables Included | Yes | |
| Daisy-Chain | No | |

**Performance**

| | |
|---|---|
| IP Control | No |
| Maximum Analog Resolutions | 1280 x 1024 |
| Supported Resolutions | 1024x768 |
| | 1280x720 (High-definition 720p) |
| | 1280 x 1024 |
| | |
| | <i>Lower resolutions are also supported</i> |
| Contrast Ratio | 1000:1 |
| Brightness | 250 cd/m |
| Color Depth | 8-bit, 16.7M colors |
| Pixel Pitch Support | 0.264 x 0.264 mm |
| Maximum Number of Users | 1 |
| MTBF | 50, 000 Hrs |

**Connector(s)**

| | |
|---|---|
| Console Interface(s) | VGA (15 pin, High Density D-Sub) |

**Indicators**

| | |
|---|---|
| LED Indicators | power / status LED |

**Power**

| | |
|---|---|
| Power Source | International Power Cords |
| Power Consumption (In Watts) | 17W |

**Environmental**

| | |
|---|---|
| Operating Temperature | 0C to 40C (32F to 104F) |
| Storage Temperature | -20C to 60C (-4F to 140F) |
| Humidity | 10 ~ 80% RH |

**Physical Characteristics**

| | |
|---|---|
| Material | Steel |

| | | |
|---|---|---|
| Product Length | 21.0 in [53.3 cm] | |
| Product Width | 19.0 in [48.3 cm] | |
| Product Height | 1.7 in [43 mm] | |
| Weight of Product | 27.0 lb [12.2 kg] | |
| Maximum Mounting Depth | 30.7 in [78 cm] | |
| Minimum Mounting Depth | 19.7 in [50 cm] | |

**Packaging Information**

| | | |
|---|---|---|
| Package Length | 30.1 in [76.5 cm] | |
| Package Width | 24.2 in [61.5 cm] | |
| Package Height | 7.5 in [19 cm] | |
| Shipping (Package) Weight | 35.4 lb [16 kg] | |

**What's in the Box**

| | |
|---|---|
| Included in Package | KVM console |
| | 6 ft [1.8 m] KVM cable |
| | M5 cage nuts |
| | M5 screws |
| | regional power cords (NA, JP, UK, EU, ANZ) |
| | quick-start guide |
| | mounting rails (variable length) |

*\*Product appearance and specifications are subject to change without notice.*