



APC Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD

Brand : APC

Product code: SMT2200RMI2UNC

Product name : Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD



Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD  
APC Smart-UPS, Line Interactive, 2200VA, Rackmount 2U, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C20 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 509 Ah, Battery recharge time: 5 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm

| Features                        |                         | Design                            |  |
|---------------------------------|-------------------------|-----------------------------------|--|
| UPS topology *                  | Line-Interactive        | Form factor *                     | Rackmount  |
| Output power capacity *         | 2.2 kVA                 | Rack capacity                     | 2U   |
| Output power *                  | 1980 W                  | Product colour *                  | Black  |
| Waveform *                      | Sine                    | Display type                      | LCD  |
| Input operation voltage (min) * | 151 V                   | LED indicators                    | ✓  |
| Input operation voltage (max) * | 302 V                   | Certification                     | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE |
| Input frequency *               | 50/60 Hz                |                                   |  |
| Output operation voltage (min)  | 220 V                   |                                   |  |
| Output operation voltage (max)  | 240 V                   |                                   |  |
| Output frequency                | 50/60 Hz                |                                   |  |
| Surge energy rating             | 375 J                   | Operational conditions            |  |
| Response time                   | 4 ms                    | Operating temperature (T-T)       | 0 - 40 °C  |
| Emergency Power Off (EPO)       | 0                       | Storage temperature (T-T)         | -15 - 45 °C  |
| Noise level                     | 55 dB                   | Operating relative humidity (H-H) | 0 - 95%  |
| Surge protection                | ✓                       | Storage relative humidity (H-H)   | 0 - 95%  |
| Audible alarm(s)                | ✓                       | Operating altitude                | 0 - 3000 m   |
| Web-based management            | ✓                       | Non-operating altitude            | 0 - 15000 m  |
| Audible alarm modes             | Battery replacement     | Technical details                 |  |
| Auto-restart                    | ✓                       | Sustainability certificates       | Green Premium  |
| Ports & interfaces              |                         | Compliance certificates           | RoHS   |
| AC outlet types                 | C20 coupler             | Weight & dimensions               |  |
| Power plug                      | C20 coupler             | Width                             | 480 mm   |
| AC outlets quantity             | 9 AC outlet(s)          | Depth                             | 683 mm   |
| USB 2.0 ports quantity          | 1                       | Height                            | 86 mm  |
| Ethernet LAN (RJ-45) ports      | 1                       | Weight                            | 42.2 kg  |
| Battery                         |                         | Package width                     | 600 mm   |
| Battery technology              | Sealed Lead Acid (VRLA) | Package depth                     | 980 mm   |
| Battery capacity                | 509 Ah                  | Package height                    | 254 mm   |
| Battery recharge time           | 5 h                     | Package weight                    | 49.6 kg  |
| Hot-swap battery                | ✓                       | Packaging data                    |  |
| Automatic battery test          | ✓                       | Rack mount kit                    | ✓  |
| Cold start                      | ✓                       | Cables included                   | Input power cable, USB cable   |
|                                 |                         | Quick installation guide          | ✓  |
|                                 |                         | Resource CD                       | ✓  |
|                                 |                         | Logistics data                    |  |
|                                 |                         | Products per pallet               | 8 pc(s)  |
|                                 |                         | Harmonized System (HS) code       | 85078000   |
|                                 |                         | Other features                    |  |
|                                 |                         | Output voltage                    | 230 V  |



0731304327691



731304327691

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.