KOF555-1/2/3-EUK



All Weather Rated

- Designed to support 55" Peerless-AV® XHB554 Outdoor Displays to offer maximum flexibility at the best value
- Elegant, minimalistic design protects displays and internal equipment, while enhancing the drive-thru aesthetics
- Designed for common 8" baseplate mounting pattern, with 30° of rotational positioning to select the best viewing angle for your customers
- Designed and tested to IP54
- Create a fully integrated drivethru solution with a variety of options:
 - Speaker/Microphone Kit (KOF-OPT-SPK) Contact sales for further info
 - Media Storage Fan (KOF-OPT-FAN-EUK)
 - Internal Media Player Shelf (KOF-OPT-SHELF)

Outdoor Digital Menu Boards

SUPPORT 55" PEERLESS-AV® XTREME XHB554 OUTDOOR DISPLAY(S)

Increase drive-thru sales and promote order efficiency with Peerless-AV's Outdoor Digital Menu Boards, designed to support High Bright 55" Peerless-AV® XHB554 Outdoor Displays. These all-weather rated, outdoor units offer a low operating cost, modular design, and an easy, two-man installation process. By making the switch to digital, with Peerless-AV's Outdoor Digital Menu Boards, you will no longer need to manually update static menu content throughout the day. Instead, the digital content can be updated remotely and in real-time, creating a seamless drive-thru experience for customers and a more efficient restaurant.



Peerless-AV[®] Outdoor Digital Menu Boards also support one or two displays.

Driving Technology Through Innovation

⋈ info@peerless-av.com

Kiosk: RoHS



Kiosk Enclosure Warranty: 5 Years

Model Numbers

KOF555-1-EUKOutdoor Digital Menu Board Supports (1) 55" Peerless-AV® XHB554 Outdoor DisplayKOF555-2-EUKOutdoor Digital Menu Board Supports (2) 55" Peerless-AV® XHB554 Outdoor DisplaysKOF555-3-EUKOutdoor Digital Menu Board Supports (3) 55" Peerless-AV® XHB554 Outdoor Displays

Product Specifications

MODEL NUMBERS	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	FINISH	AVAILABLE COLORS	
KOF555-1-EUK	28.38" x 75.67" x 12.62" (721 x 1922 x 321mm)	132lb (60kg)			
KOF555-2-EUK	57.17" x 75.67" x 12.62" (1452 x 1922 x 321mm)	163lb (74kg)	Textured Powder Coat	Black	
KOF555-3-EUK	85.97" x 75.67" x 12.62" (2184 x 1922 x 321mm)	194lb (88kg)			

Package Specifications

MODEL NUMBERS PA	ACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
KOF555-1-EUK (1) KOF555-2-EUK (1) KOF555-3-EUK 99	88.00" x 84.00" x 27.00" (966 x 2134 x 686mm) 50.00" x 84.00" x 40.00" (524 x 2134 x 1016mm) 96.00" x 84.00" x 48.00" 2438 x 2134 x 1219mm)	185lb (84kg) 224lb (102kg) 290lb (132kg)	735029341703 735029341727 735029341734	Digital Menu Board Enclosure, Mounting Hardware and Instructions	1

Options

KOF-OPT-SPK: Speaker/Microphone Kit KOF-OPT-FAN-EUK: Media Storage Fan

KOF-OPT-SHELF: Internal Media Player Shelf

All dimensions = inch (mm)



MODEL NO.	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	DIMENSION "E"	DIMENSION "F"
KOF555-1-EUK	12.65" (321mm)	75.67" (1922mm)	12.54" (319mm)	12.70" (322mm)	49.36"(1254mm)	28.38" (721mm)
KOF555-2-EUK	12.65" (321mm)	75.67" (1922mm)	12.54" (319mm)	12.70" (322mm)	49.36"(1254mm)	57.17" (1452mm)
KOF555-3-EUK	12.65" (321mm)	75.67" (1922mm)	12.54" (319mm)	12.70" (322mm)	49.36"(1254mm)	85.97" (2184mm)

Architect Specifications

The Outdoor Digital Menu Board shall be a Peerless- AV^{\oplus} model KOF555-1, -2, -3 -EUK and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit **peerless-av.com** to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, display mounts, projector mounts, carts/stands, and a full assortment of accessories. Peerless-AV 2300 White Oak Circle Aurora, IL 60502 USA (800) 865-2112 (630) 375-5100 Fax: (800) 359-6500 Peerless-AV EMEA Unit 2 Curo Park, St Albans, Herts AL2 2DD United Kingdom +44 (0) 1923 200100 Fax: +44 (0) 1923 200101 Peerless-AV Latin America Av. de las Industrias 413 Parque Industrial Escobedo General Escobedo, N.L., México, 66062 +52 (81) 8384-8300 Fax: +52 (81) 8384-8360

