logitech

Logitech RoomMate

Brand : Logitech

Product name : RoomMate

Product code: 991-000412

RoomMate
Logitech RoomMate. HD type: 4K Ultra HD, Supported video modes: 720p, 1080p, 2160p. Digital zoom: 8x. Ethernet LAN, Wi-Fi. Bluetooth. Display: IPS, Display diagonal: 25.6 cm (10.1"), Display resolution: 1280 x 800 pixels. Operating system installed: CollabOS. Product colour: Graphite, White

Performance

Bluetooth	✔
Bluetooth version	5.0
Product colour *	Graphite, White
Wall mountable	✔
Pan range	-25 - 25°
Tilt angle range	-15 - 15°
PTZ control	✔

Video

HD type *	4K Ultra HD
Maximum video resolution *	3840 x 2160 pixels
Supported video modes	720p, 1080p, 2160p

Audio

Built-in speaker(s)	✔
Output level	86.5/95 dB
Output voltage Total Harmonic Distortion (THD)	3%
Audio beamforming	✔
Microphone pick-up range	4 m
Sample rates	0 - 32 kHz

Ports & interfaces

HDMI ports quantity	3
HDMI output ports quantity	2
HDMI input ports quantity	1
USB connector type	USB Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ethernet LAN (RJ-45) ports	1

Interface module

Interface module RJ-45 ports quantity	1

Features

Motion sensor	✔
Cable lock slot	✔
Cable lock slot type	Kensington

Logistics data

Master (outer) case gross weight	8.82 kg
Master (outer) case length	529 mm
Master (outer) case width	463 mm
Master (outer) case height	203 mm
Harmonized System (HS) code	85176990

Battery

Battery capacity	0.675 Wh

Computer system

VESA mounting	✔
Operating system installed	CollabOS
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 95%
Storage temperature (T-T)	-40 - 70 °C

Power

Power source type	AC
AC input voltage	100 - 240 V
Current	4.74 A

Network

Ethernet LAN *	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Security algorithms	128-bit AES

Camera

Zoom capability	✔
Digital zoom	8x
Horizontal field of view	113°
Vertical field of view	80.7°
Diagonal field of view	120°
Number of camera presets	3
Remote control interface	RF Wireless

Display

Display	IPS
Display diagonal	25.6 cm (10.1")
Display resolution	1280 x 800 pixels
Contrast ratio (typical)	1000:1
Touchscreen	✔
Touchscreen type	Capacitive
Viewing angle, horizontal	85°
Viewing angle, vertical	85°
Display brightness	400 cd/m²
Oleophobic coating	✔

Microphone

Microphone sensitivity	-27 dB
Microphone frequency	90 - 16000 Hz

Power

DC input voltage	19 V
Battery technology	Lithium
Battery capacity	220 mAh
Number of batteries supported	2
Power plug type	Type G

Weight & dimensions

Interface module dimensions (W x D x H)	246.2 x 171.3 x 56.1 mm
Interface module weight	1 kg
Remote control dimensions (W x H x D)	83 x 83 x 10 mm
Camera dimensions (WxDxH)	400 x 85 x 104 mm
Camera weight	1.04 kg
Width	161 mm
Depth	211 mm
Height	34.5 mm
Weight	1.04 kg
Package width	456 mm
Package depth	522 mm
Package height	189 mm
Package weight	8.82 kg

Packaging content

Cables included	AC, DC, USB
Power cable length	2.5 m
AC adapter included	✔
Mounting kit	✔
Camera included	✔
Quick start guide	✔

5099206102187