



APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19

Brand : APC

Product code: AP8653

Product name : Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19
APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 32A, 230V, (21) C13 & (3) C19. PDU types: Metered, Metered-by-outlet, Switched, Rack capacity: 0U, Type: Single-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC309. Cable length: 3 m, Certification: EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, VDE. Monitoring: Current, Power, Voltage, Outlet control: Lock-out, Recycle, Turn off, Turn on. Nominal input voltage: 230 V, Maximum current: 32 A, AC input frequency: 50 - 60 Hz



Design		Power	
PDU types *	Metered, Metered-by-outlet, Switched	Maximum input current per phase	32 A
Type	Single-phase	Maximum total current draw per phase	32 A
Rack capacity *	0U	Power protection features	Overload
Mounting	Vertical	Maximum power	7680 W
Product colour	Black	Weight & dimensions	
Ports & interfaces		Dimensions (WxDxH)	56.00 x 51.00 x 1829.00 mm
AC outlets quantity *	24 AC outlet(s)	Weight	8.23 kg
Power plug	IEC309	Packaging data	
AC outlet types *	C13 coupler, C19 coupler	Package dimensions (WxDxH)	162.00 x 118.00 x 2038.00 mm
Features		Package weight	10.5 kg
Cable length	3 m	Operational conditions	
Certification	EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, VDE	Operating temperature (T-T)	-5 - 45 °C
Management features		Storage temperature (T-T)	-25 - 65 °C
Monitoring	Current, Power, Voltage	Operating relative humidity (H-H)	5 - 95%
Outlet control	Lock-out, Recycle, Turn off, Turn on	Storage relative humidity (H-H)	5 - 95%
Power		Operating altitude	0 - 3000 m
Nominal input voltage *	230 V	Non-operating altitude	0 - 15000 m
AC input frequency	50 - 60 Hz	Technical details	
Maximum current *	32 A	Compliance certificates	RoHS
Nominal output voltage	230 V		
Load capacity	7680 VA		



0731304276982



731304276982

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date