



APC Smart-UPS RT 2200VA 230V - Marine

Brand : APC
Product code: SURTD2200XLIM
Product name : Smart-UPS RT 2200VA 230V - Marine

Smart-UPS RT 2200VA 230V - Marine

APC Smart-UPS RT 2200VA 230V - Marine:

High availability, ruggedized power protection for shipboard and other transportation applications.
APC Smart-UPS RT 2200VA 230V - Marine. Output power capacity: 2.2 kVA, Output power: 1540 W, Input operation voltage (min): 100 V. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 2.5 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 3U. Width: 130 mm, Depth: 660 mm, Height: 432 mm



Features		Design	
Output power capacity *	2.2 kVA	Rack capacity	3U
Output power *	1540 W	Cable length	2.5 m
Input operation voltage (min) *	100 V	Product colour *	Black
Input operation voltage (max) *	280 V	Certification	CE, DNV, EN 50091-1, EN 50091-2, EN 55022 Cl. A, EN 60950, EN 61000-3-2.
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V	Operational conditions	
Surge energy rating	480 J	Operating temperature (T-T)	0 - 55 °C
Efficiency	92%	Storage temperature (T-T)	-15 - 45 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	3%	Operating altitude	0 - 3000 m
Noise level	55 dB	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Technical details	
Ports & interfaces		Compliance certificates	RoHS
AC outlet types		Weight & dimensions	
AC outlets quantity	C13 coupler, C19 coupler	Width	130 mm
Number of output IEC jumpers	10 AC outlet(s)	Depth	660 mm
Ethernet LAN (RJ-45) ports	2	Height	432 mm
	1	Weight	54.5 kg
Battery		Package weight	63.6 kg
Battery technology	Sealed Lead Acid (VRLA)	Logistics data	
Battery recharge time	2.5 h	Harmonized System (HS) code	85078000
Design		Other features	
Form factor *	Rackmount	Dimensions (WxDxH)	130 x 660 x 432 mm
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Package dimensions (WxDxH)	603 x 980 x 347 mm



0731304286929



731304286929

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date