

4-Port DisplayPort KVM Switch, Single 4K 60Hz Monitor, 6x USB Ports, Push-Button & Hotkey Switching, DisplayPort 1.2, OS Independent, TAA Compliant

Product ID: P4AD122-KVM-SWITCH



This DisplayPort KVM Switch enables users to switch between four desktops equipped with USB-A and DisplayPort. It facilitates sharing a 4K 60Hz DisplayPort monitor, a keyboard, mouse, two USB 5Gbps devices, a stereo audio output device, and four USB 2.0 devices.

This KVM supports resolutions up to 4K 60Hz, making it ideal for applications such as CAD/CAM, video editing, and content creation. In addition, its support for High Dynamic Range (HDR) enhances contrast, brightness, color, and overall vibrancy.

This universal KVM switch offers hotkey and push-button switching. Hotkeys allow independent switching of audio and video, enabling audio playback from one computer while controlling another. An audible buzzer confirms hotkey inputs, and LEDs provide visual status feedback for the selected host.

The TAA-compliant KVM Switch offers universal compatibility and works with all operating systems, including Windows, macOS, ChromeOS, and Linux. The KVM provides BIOS/UEFI control and is compatible with all hardware platforms, including Intel, AMD, and Apple Silicon (M1/M2/M3).

The rugged metal case helps prevent electromagnetic interference (EMI). 8kV Air/6kV Contact ESD protection enhances the reliability and longevity of the KVM. The included set of rubber feet protect the work surface from scratches and keep KVM in place during operation.

Certifications, Reports and Compatibility









Applications

- Share a monitor, mouse, keyboard, and stereo audio peripheral between four desktop computers
- Great for applications like CAD/CAM, video editing, and content creation

Features

• FAST SWITCHING 4K 60HZ KVM: Control up to four DisplayPort-enabled desktops/workstations/servers from one mouse, keyboard, USB 5Gbps hub, and 4K 60Hz DisplayPort monitor; Ideal for CAD/CAM, video editing, and content creation applications

• MULTIPLE SWITCHING OPTIONS: Fast Switching via push-buttons or hotkeys with an audible buzzer providing confirmation; LEDs provide quick visual port selection status; Listen to audio from one computer while controlling another

• UNIVERSAL COMPATIBILITY: TAA-Compliant KVM Switch provides BIOS/UEFI control and works with any operating system including Windows, macOS, ChromeOS, and Linux; No software required; Compatible with all hardware platforms such as Intel, AMD, and Apple

• DURABLE DESIGN: Metal housing helps prevent Electro-magnetic Interference (EMI); 8kV Air/6kV Contact ESD protection enhances the reliability and longevity of the KVM; Included rubber feet protect the work surface and keep KVM in place during operation

• TECHNICAL SPECIFICATIONS: KVM Switch is DisplayPort 1.2 compliant, supporting resolutions up to 4K 60Hz, HDR10, and HDCP 1.4; Supports DisplayPort Audio and 3.5mm analog audio; 4x USB HID Ports; 2x USB 5Gbps Hub Ports; OS Independent

Hardware		
	Warranty	2 Years
	Audio	Yes
	KVM Ports	4
	PC Interface	USB 3.2 Gen 1 (5Gbps)
	PC Video Type	DisplayPort
	Number of Monitors Supported	1
	Cables Included	No



	Chipset ID	GL3523
Performance		
	On-Screen Display	No
	Video Revision	DisplayPort 1.2
	IP Control	No
	Hot-Key Selection	Yes
	Maximum Data Transfer Rate	USB 5Gbps
	Maximum Digital Resolutions	4096 x 2160 60Hz
	Supported Resolutions	10-bit RGB
		3840x2160 @ 60hz
		3840x2160 @ 30hz
		2560x1600 @ 60hz
		2560x1600 @ 30hz
		2560x1440 @ 60hz
		2048x1536 @ 60hz
		2048x1536 @ 30hz
		1920x1440 @ 60hz
		1920x1200 @ 60hz
		1920x1080 @ 60hz
		1680x1050 @ 60hz
		1600x1200 @ 60hz
		1600x1024 @ 60hz
		1600x900 @ 60hz
		1440x1080 @ 60hz
		1366x768 @ 60hz
		1360x768 @ 60hz
		1280x1024 @ 60hz
		1280x960 @ 60hz
		1280x800 @ 60hz



		1280x768 @ 60hz
		1280x720 @ 60hz
		1176x664 @ 60hz
		1152x864 @ 60hz
		1024x768 @ 60hz
		800x600 @ 60hz
		<i>Other resolutions may be supported</i>
	Wide Screen Supported	Yes
	Audio Specifications	DisplayPort - 2 Channel Audio
		Analog Stereo - 2 Channel Audio
	Auto Scan	3, 8, 15 & 30 seconds
	Port Selection Support	Push Button and Hotkeys
	MTBF	130,000 Hours
Connector(s)		
	Console Interface(s)	4 - USB 2.0 Type-A (4 pin, 480Mbps)
		2 - USB 3.2 Type-A (9 pin, Gen 1, 5Gbps)
		1 - 3.5mm Stereo Female 3 pos
		1 - DisplayPort
		1 - Barrel Power Connector (Size M, OD:5.50, ID: 2.10)
	Host Connectors	4 - DisplayPort
		4 - USB 3.2 Type-B (9 pin, Gen 1, 5Gbps)
		4 - 3.5mm Stereo Female 3 pos
Software		
	OS Compatibility	No Drivers or Software Required
Indicators	LED Indicators	4 - Port Selection:



Solid Green - PC 1 ~ 4 connected (powered on) Solid Red - Selected PC Port

1 - Power LED:

Solid Green - KVM Switch is powered on

Power		
	Power Source	AC Adapter Included
	Input Voltage	100 - 240 AC
	Input Current	1.0A
	Output Voltage	12V DC
	Output Current	3A
	Center Tip Polarity	Positive
	Plug Type	Μ
	Power Consumption (In Watts)	36W
Environmental		
	Operating Temperature	0C to 40C (32F to 104F)
	Storage Temperature	-10C to 60C (14F to 140F)
	Humidity	0% ~ 80% RH
Physical Characteristics		
	Color	Black
	Material	Metal
	Product Length	8.7 in [22.0 cm]
	Product Width	5.1 in [13.0 cm]
	Product Height	1.7 in [4.4 cm]
	Weight of Product	2.3 lb [1.0 kg]
Packaging Information		
	Package Length	16.1 in [41.0 cm]

STARTECH.COM



	Package Width	8.3 in [21.2 cm]
	Package Height	3.4 in [8.7 cm]
	Shipping (Package) Weight	2.6 lb [1.2 kg]
What's in the Box		
	Included in Package	1 - KVM Switch
		1 - Universal Power Adapter (NA/EU/UK/ANZ)
		1 - Set of Rubber Feet
		1 - Quick-Start Guide

*Product appearance and specifications are subject to change without notice.

