StarTech.com SV231DPUCA KVM switch Black

Brand : StarTech.com

Product code: SV231DPUCA

Product name : SV231DPUCA

StarTech.com 2-Port USB-C KVM Switch, Single 4K 60Hz DisplayPort Monitor, 3.5mm Audio, 6x USB Hub Ports, Hot Key Switching, Thunderbolt 3/4 Compatible - TAA
StarTech.com SV231DPUCA. Keyboard port type: USB, Mouse port type: USB, Video port type: DisplayPort. HD type: 4K Ultra HD, Maximum resolution: 5120 x 1440 pixels, Video bandwidth: 60 Hz. Product colour: Black, Mean time between failures (MTBF): 158000 h. Power source: AC, Input voltage: 100 - 240 V, Input current: 1.2 A. Width: 140 mm, Depth: 160 mm, Height: 40 mm

Ports & interfaces

Number of computers controlled *	2
Keyboard port type *	USB
Mouse port type *	USB
Video port type *	DisplayPort
DisplayPort version	1.2
Console ports *	3.5mm headphone, 3.5mm mic, DisplayPort
Console USB ports quantity	6
Console DisplayPorts ports quantity	1
USB hub	✔
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
Headphone outputs	1
Number of microphone inputs	1

Performance

HD type *	4K Ultra HD
Maximum resolution *	5120 x 1440 pixels
Video bandwidth	60 Hz
Data transfer rate (max)	5 Gbit/s
Scan interval	3,8,15,30 s
HDCP	✔
Chipset	Parade - PS8461, Etron - EJ899I
Audio channels	2.0
Number of displays supported	1

Design

Rack mounting *	✘
Product colour *	Black
LED indicators	✔

Display

Built-in display *	✘

Power

Power source	AC
Input voltage	100 - 240 V
Input current	1.2 A
Output voltage	12 V
Output current	3 A
Power plug type	Type M

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 60 °C
Operating relative humidity (H-H)	0 - 80%

Weight & dimensions

Width	140 mm
Depth	160 mm
Height	40 mm
Weight	600 g

Packaging data

Package width	184 mm
Package depth	238 mm
Package height	89 mm
Package weight	1 kg

Packaging content

Quick installation guide	✔
AC adapter included	✔
Rubber feet	✔

Design			Other features	
Push button	✔		IP control	✘
Hot keys	✔			
Mean time between failures (MTBF)	158000 h			

Logistics data

Master (outer) case width	300 mm
Master (outer) case length	397 mm
Master (outer) case height	257 mm
Products per master (outer) case	6 pc(s)

0065030872201

065030872201