



TP-Link EAP725-Wall 5012 Mbit/s Power over Ethernet (PoE)

Brand : TP-Link

Product code: EAP725-WALL

Product name : EAP725-Wall

- BE5000 Wi-Fi 7 (4324 Mbps on 5 GHz + 688 Mbps on 2.4 GHz).†
 - 1× 2.5G PoE input port + 1× 2.5G pass-through port + 2× Gigabit RJ45 downlink ports
 - 240 MHz bandwidth enables many more simultaneous transmissions.‡
 - Multi-RUs ensure the high performance of your network.‡
 - Advanced Functions: Centralized management, Mesh, and Seamless Roaming
- EAP725-Wall - BE5000 Wall Plate Wi-Fi 7 Access Point

TP-Link EAP725-Wall 5012 Mbit/s Power over Ethernet (PoE):


Dedicated and Complete, Private WiFi Networks for Every Room

Optimized Wired Performance with 2.5G PoE Ports

With 2.5G PoE input and pass-through ports, along with two Gigabit RJ45 ports, enjoy high-speed data transfers and connect multiple devices to your gigabit network. Wired devices, such as IP Phones, can be powered without the need for additional electrical cables.

Seamless Integration into the Omada SDN

Remotely manage your access points, switches, and routers across multiple sites — all from a single interface.



Features		Antenna	
2.4 GHz *	✓	Antenna type *	Internal
5 GHz *	✓	Antennas quantity	4
6 GHz *	✗	Antenna gain level (max)	5 dBi
Maximum data transfer rate *	5012 Mbit/s	Performance	
Maximum data transfer rate (2.4 GHz)	688 Mbit/s	Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows 11, Linux
Maximum data transfer rate (5 GHz)	4324 Mbit/s	Certificates	
VLAN support	✓	Certification	FCC, RoHS
Security		Weight & dimensions	
MAC address filtering	✓	Width	86 mm
Number of SSID supported	16	Depth	40 mm
Remote Authentication Dial-In User Service (RADIUS)	✓	Height	143 mm
Access Control List (ACL)	✓	Packaging data	
Ports & interfaces		Package type	Box
Ethernet LAN (RJ-45) ports *	3	Packaging content	
Power		Quantity per pack	1 pc(s)
Power over Ethernet (PoE) *	✓	Mounting kit	✓
Design		Operational conditions	
Reset button	✓	Operating relative humidity (H-H)	10 - 90%
LED indicators	✓	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%



8885020626353

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-FEB-2025. Prints or copies of Information are only valid on the printed Publication date