



**APC 230V Smart UPS RT 6000 VA + PowerChute uninterruptible power supply (UPS) 6 kVA 4200 W**

**Brand :** APC

**Product code:** SURT6000XLI

**Product name :** 230V Smart UPS RT 6000 VA + PowerChute

230V Smart UPS RT 6000 VA

APC 230V Smart UPS RT 6000 VA + PowerChute uninterruptible power supply (UPS) 6 kVA 4200 W:

APC Smart-UPS RT, 6000VA/4200W, Input 230V/Output 230V, Interface Port DB-9 RS-232, RJ-45 10/100 Base-T, Smart-Slot, Extended runtime model, Rack Height 3 U

**Includes:** CD with software, Rack Mounting support rails, Smart UPS signalling RS-232 cable, User Manual, Web/SNMP Management Card

**Standard Lead Time:** Usually in Stock  
APC 230V Smart UPS RT 6000 VA + PowerChute. Output power capacity: 6 kVA, Output power: 4200 W, Surge energy rating: 480 J. Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 5.3 min, Typical backup time at half load: 15.8 min. Product colour: Black, Certification: C-tick,CE,EN 50091-1,EN 50091-2,EN 55022 Class A,EN 60950,EN 61000-3-2,GOST,VDE. Width: 130 mm, Depth: 660 mm, Height: 432 mm. Interface: DB-9 RS-232, Dimensions (WxDxH): 432 x 660 x 130 mm, Nominal output voltage: 230 V



Features		Operational conditions	
Output power capacity *	6 kVA	Storage temperature (T-T)	-15 - 45 °C
Output power *	4200 W	Operating relative humidity (H-H)	0 - 85%
Surge energy rating	480 J	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Weight & dimensions	
Noise level	55 dB	Width	130 mm
Audible alarm(s)	✓	Depth	660 mm
Battery		Height	432 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	54.4 kg
Typical backup time at full load	5.3 min	Package weight	63.6 kg
Typical backup time at half load	15.8 min	Logistics data	
Battery recharge time	2.5 h	Harmonized System (HS) code	85078000
Design		Other features	
Product colour *	Black	I/O ports	8 x IEC 320 C13; 2 x IEC 320 C19
Certification	C-tick,CE,EN 50091-1,EN 50091-2,EN 55022 Class A,EN 60950,EN 61000-3-2,GOST,VDE	Interface	DB-9 RS-232
Operational conditions		Dimensions (WxDxH)	432 x 660 x 130 mm
Operating temperature (T-T)	0 - 40 °C	Nominal output voltage	230 V
		Nominal input voltage	230 V
		Package dimensions (WxDxH)	603 x 980 x 347 mm



4053162303010



0731304240174



731304240174

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-AUG-2024. Prints or copies of Information are only valid on the printed Publication date