FUJITSU PRIMERGY

Fujitsu PRIMERGY TX1310 M5 server 2 TB Tower Intel Xeon E E-2324G 3.1 GHz 16 GB DDR4-SDRAM 450 W

Brand : Fujitsu

Product family: PRIMERGY

Product code: VFY:T1315SC110IN

Product name : TX1310 M5

Intel Xeon E-2324G (8MB Cache, 3.1GHz), 16GB DDR4-SDRAM (3200MHz), 2 x 1TB HDD, DVD-RW, Intel UHD Graphics P750, No OS
Fujitsu PRIMERGY TX1310 M5. Processor family: Intel Xeon E, Processor frequency: 3.1 GHz, Processor model: E-2324G. Internal memory: 16 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size): 1 x 16 GB. Total storage capacity: 2 TB, HDD size: 3.5", HDD interface: SATA III, Optical drive type: DVD-RW. Power supply: 450 W. Chassis type: Tower

intel XEON

Processor

Processor manufacturer *	Intel
Processor family *	Intel Xeon E
Processor model *	E-2324G
Processor frequency *	3.1 GHz
Processor boost frequency	4.6 GHz
Processor cache	8 MB
Motherboard chipset	Intel C256
Number of processors installed	1

Memory

Internal memory *	16 GB
Internal memory type *	DDR4-SDRAM
Memory slots	4x DIMM
ECC	✓
Memory clock speed	3200 MHz
Memory layout (slots x size)	1 x 16 GB
Maximum internal memory *	128 GB

Storage

Total storage capacity *	2 TB
Number of HDDs installed	2
HDD capacity	1 TB
HDD interface	SATA III
HDD speed	7200 RPM
HDD size	3.5"

Ports & interfaces

USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	1
DisplayPorts quantity	1
Total number of SATA connectors	7

Expansion slots

PCI Express x4 (Gen 3.x) slots	2
PCI Express x16 (Gen 4.x) slots	1

Design

Chassis type *	Tower
Product colour	Black

Performance

Trusted Platform Module (TPM)	✓
Trusted Platform Module (TPM) version	2.0

Software

Operating system installed *	✗

Storage

Number of HDDs supported	4
Supported HDD sizes	3.5"
RAID support *	✔
RAID levels	0, 1, 10
Number of 5.25" bays	2
Optical drive type *	DVD-RW

Graphics

On-board graphics card	✔
On-board graphics card model	Intel UHD Graphics P750

Network

LAN controller	Intel I210

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2
USB 2.0 ports quantity	4

Software

Compatible operating systems *	Windows Server 2022 Datacenter Windows Server 2022 Standard Windows Server 2022 Essentials Windows Server 2019 Datacenter Windows Server 2019 Standard Windows Server 2019 Essentials SUSE® Linux Enterprise Server 15 Red Hat® Enterprise Linux 8

Power

Redundant power supply (RPS) support *	✘
Power supply *	450 W

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Operating relative humidity (H-H)	10 - 85%

Weight & dimensions

Width	180 mm
Depth	313 mm
Height	379 mm

4065221938040