



APC Smart-UPS SMT1000RM12UC - 4x C13, USB, Rackmount 2U, SmartConnect, 1000VA



Brand : APC

Product code: SMT1000RM12UC

Product name : APC Smart-UPS SMT1000RM12UC - 4x C13, USB, Rackmount 2U, SmartConnect, 1000VA

APC Smart-UPS SMT750RM12UC - 4x C13, USB, Rackmount 2U, SmartConnect, 750VA
APC Smart-UPS SMT1000RM12UC - 4x C13, USB, Rackmount 2U, SmartConnect, 1000VA. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 700 W. AC outlet types: C13 coupler, AC outlets quantity: 4 AC outlet(s), USB port type: USB Type-A. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 477 mm, Height: 86 mm

Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	1 kVA	Cold start	✓
Output power *	700 W	Replacement battery cartridge	APCRBC132
Waveform *	Sine	Design	
Input operation voltage (min) *	151 V	Form factor *	Rackmount
Input operation voltage (max) *	302 V	Rack capacity	2U
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	Certification	EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH
Automatic Voltage Regulation (AVR)	✓	Operational conditions	
Surge energy rating	459 J	Operating temperature (T-T)	0 - 40 °C
Response time	10 ms	Storage temperature (T-T)	-15 - 45 °C
Output voltage Total Harmonic Distortion (THD)	5%	Operating relative humidity (H-H)	0 - 95%
Noise level	45 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Web-based management	✓	Non-operating altitude	0 - 15000 m
Auto-restart	✓	Technical details	
Temperature voltage compensation	✓	Sustainability certificates	Green Premium
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	C13 coupler	Weight & dimensions	
AC outlets quantity	4 AC outlet(s)	Width	432 mm
USB port	✓	Depth	477 mm
USB port type	USB Type-A	Height	86 mm
Serial interface	✓	Weight	22.5 kg
Serial interface type	RJ-45	Package width	594 mm
Ethernet LAN (RJ-45) ports	1	Package depth	603 mm
SmartSlot	✓	Package height	251 mm
Battery		Package weight	31.4 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Number of batteries supported	1	Rack mount kit	✓
Battery life (max)	6 year(s)	Cables included	RS-232, USB cable
Battery recharge time	3 h	Quick installation guide	✓
Hot-swap battery	✓	Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	8 pc(s)

Logistics data

Harmonized System (HS) code 85078000



0731304332985



731304332985

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.