## GIGABYTE H610M H V3 DDR4 Motherboard - Supports Intel Core 14th CPUs, 4+1+1 Hybrid Phases Digital VRM, up to 3200MHz DDR4, 1xPCle 3.0 M.2, GbE LAN, USB 3.2 Gen 1

Brand: GIGABYTE Product code: H610M H V3 DDR4

**Product name:** H610M H V3 DDR4 Motherboard - Supports Intel Core 14th CPUs, 4+1+1 Hybrid Phases Digital VRM, up to 3200MHz DDR4, 1xPCle 3.0 M.2, GbE LAN, USB 3.2 Gen 1

GIGABYTE

HIGHM H V3 DDV4 (1)

- Supports Intel® Core™ 14th/ 13th /12th processors
- Dual Channel Non-ECC Unbuffered DDR4, 2 DIMMs
- 4+1+1 Hybrid Digital VRM Design
- GbE LAN with Bandwidth Management
- NVMe PCIe 3.0 x4 M.2
- High Quality Audio Capacitors and Audio Noise Guard
- Smart Fan 6 Features Multiple Temperature Sensors , Hybrid Fan Headers with FAN STOP
- GIGABYTE APP Center, Simple and Easy Use
- Anti-Sulfur Resistors Design

Intel H610 Motherboard with 4+1+1 Hybrid Phases Digital VRM Design, PCle 4.0\* Design, Gen3 x4 M.2, Anti-Sulfur Resistor, Smart Fan 6







| Processor   |   | Rear panel I/O ports   |  |
|---|---|--|--|
| Processor manufacturer * Processor socket *   | Intel<br>LGA 1700<br>Intel® Celeron®, Intel® Core™ i3,                | Headphone outputs<br>Microphone in<br>USB connector type   | 3<br>✓<br>USB Type-A   |
| Compatible processor series *   | Intel® Core™ i5, Intel® Core™ i7,<br>Intel® Core™ i9, Intel® Pentium® | Network  |  |
| Supported processor sockets  Memory   | Gold<br>LGA 1700  | Ethernet LAN Ethernet interface type Wi-Fi *   | ✓<br>Gigabit Ethernet<br>★   |
| Supported memory types *  | DDR4-SDRAM  | Features   |  |
| Number of memory slots *  Memory slots type  Memory channels  ECC  Non-ECC  Supported memory clock speeds  Supported memory clock speed (max)  Maximum internal memory *  Supported memory module capacities  Unbuffered memory | 2 DIMM Dual-channel   | Motherboard chipset * Audio chip Audio output channels * Product colour PC health monitoring Component for * Motherboard form factor * Motherboard chipset family * Cooling type Power source type Windows operating systems supported | Intel H610 Express Realtek ALC897 7.1 channels Black Fan, Temperature, Voltage, Water cooling PC micro ATX Intel Active ATX Windows 10 x64, Windows 11 x64 |
| Storage controllers   |   | Expansion slots  |  |
| Supported storage drive types Supported storage drive interfaces * Number of HDDs supported Number of storage drives supported  | 1   | PCI Express x1 slots PCI Express x16 slots Number of M.2 (M) slots   | 1<br>1<br>1  |
| Graphics  |   | BIOS   |  |
| Parallel processing technology support * Graphics card family   | Not supported<br>Intel  | BIOS type * BIOS memory size ACPI version  | UEFI AMI<br>128 Mbit<br>5.0  |

| Graphics                               |                    | BIOS  |  |
|--|--------------------|---|--|
| Graphics card                          | HD Graphics        | Clear CMOS jumper                             | ✓  |
| Maximum resolution                     | 4096 x 2304 pixels | Clear CMOS button                             | ✓  |
| HDCP                                   | 1                  | Desktop Management Interface<br>(DMI) version | 2.7  |
| Internal I/O                           |                    | System Management BIOS                        | 2.7  |
| USB 2.0 connectors *                   | 2                  | (SMBIOS) version                              | 2.1  |
| USB 3.2 Gen 1 (3.1 Gen 1) connectors * | 1                  | Logistics data                                |  |
| Number of SATA III connectors *        | 4                  | Country of origin                             | China  |
| Front panel audio connector            | ✓                  | Products per shipping (inner) case            | 1 pc(s)  |
| Front panel connector                  | ✓                  | Battery                                       |  |
| ATX Power connector (24-pin)           | ✓                  | Battery weight                                | 3 g  |
| CPU fan connector                      | ✓                  | Lithium weight per battery                    | 0.07 g   |
| EPS power connector (8-pin)            | ✓                  | Number of battery cells                       | 1  |
| TPM connector                          | ✓                  | Battery technology                            | Lithium-Manganese Dioxide  |
| Serial port headers                    | 1                  | ,   | (LiMnO2)   |
| 12V power connector                    | ✓                  | Battery type                                  | CR2032   |
| RGB LED pin header                     | <b>✓</b>           | Packaging data                                |  |
| Rear panel I/O ports                   |                    | Package width                                 | 265 mm   |
| USB 2.0 ports quantity *               | 4                  | Package depth                                 | 235 mm   |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A       | 2                  | Package height                                | 52 mm  |
| ports quantity *                       | _                  | Package weight                                | 684 g  |
| Ethernet LAN (RJ-45) ports *           | 1                  | Weight & dimensions                           |  |
| PS/2 ports quantity                    | 1                  | Width   | 230 mm   |
| VGA (D-Sub) ports quantity *           | 1                  | Depth   | 215 mm   |
| HDMI ports quantity *                  | 1                  | Height  | 35 mm  |
| DVI-D ports quantity *                 | 1 2                |   | 55   |
| DisplayPorts quantity                  | 2                  | Packaging content                             |  |
|  |                    | Cables included                               | SATA   |
|  |                    | Batteries included                            | <b>√</b>   |
|  |                    | Bundled software                              | Norton Internet Security (OEM version) LAN bandwidth management software |
|  |                    | Technical details                             |  |
|  |                    | Warranty period                               | 3 year(s)  |



4719331859718

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.