

## Epson EB-PU2010W data projector Large venue projector 10000 ANSI lumens 3LCD WUXGA (1920x1200) White

**Brand :** Epson

**Product code:** V11HA52940

**Product name :** EB-PU2010W



3LCD, 1.03" with C2 Fine, WUXGA, 1920 x 1200, 16:10, 10000 Lumen

Epson EB-PU2010W. Projector brightness: 10000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focal length range: varies by lens, Zoom type: Auto, Throw ratio: 0.35 - 7.41:1. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709. Serial interface type: RS-232C



| Projector                                    |   | Design                            |  |
|--|---|-----------------------------------|--|
| Projector brightness *                       | 10000 ANSI lumens   | Market positioning *              | Business   |
| Projection technology *                      | 3LCD  | Product type *                    | Large venue projector  |
| Projector native resolution *                | WUXGA (1920x1200)   | Product colour *                  | White  |
| Contrast ratio (typical) *                   | 2000:1  | Placement                         | Ceiling, Desktop, Flying frame   |
| Native aspect ratio *                        | 16:10   | Cable lock slot                   | ✓  |
| Number of colours                            | 1.07 billion colours  | Cable lock slot type              | Kensington   |
| Projector brightness (economic mode)         | 7000 ANSI lumens  | <b>Display</b>                    |  |
| Projector brightness (portrait mode)         | 10000 ANSI lumens   | Built-in display *                | ✗  |
| Keystone correction, horizontal              | -30 - 30°   | <b>Power</b>                      |  |
| Keystone correction, vertical                | -45 - 45°   | Power source *                    | AC   |
| Matrix size                                  | 2.62 cm (1.03")   | Power consumption (typical) *     | 535 W  |
| Heat dissipation                             | 1819 BTU/h  | Power consumption (standby) *     | 0.5 W  |
| <b>Light source</b>                          |   | Power consumption (economy mode)  | 452 W  |
| Light source type *                          | Laser   | AC input voltage                  | 100-240 V  |
| Service life of light source *               | 20000 h   | AC input frequency                | 50 - 60 Hz   |
| Service life of light source (economic mode) | 30000 h   | <b>Software</b>                   |  |
| <b>Lens system</b>                           |   | Software support                  | via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery |
| Focal length range                           | varies by lens  | <b>Operational conditions</b>     |  |
| Zoom type                                    | Auto  | Storage temperature (T-T)         | -10 - 60 °C  |
| Throw ratio                                  | 0.35 - 7.41:1   | Operating relative humidity (H-H) | 20 - 80%   |
| Interchangeable lens                         | ✓   | Storage relative humidity (H-H)   | 10 - 90%   |
| <b>Video</b>                                 |   | <b>Weight &amp; dimensions</b>    |  |
| Analog signal format system *                | Not supported   | Width                             | 545 mm   |
| Full HD *                                    | ✓   | Depth                             | 436 mm   |
| 3D *   | ✗   | Height                            | 189 mm   |
| Video processing                             | 10 bit  | Weight *                          | 16.8 kg  |
| Video colour modes                           | Cinema, Dynamic, Natural, Presentation, DICOM simulation mode, Multi-projection, BT.709 | Package width                     | 570 mm   |
| <b>Ports &amp; interfaces</b>                |   | Package depth                     | 765 mm   |
| USB 2.0 Type-B ports quantity                | 1   | Package height                    | 270 mm   |
| Audio (L/R) in *                             | 1   | Package weight                    | 22.1 kg  |
| Serial interface type *                      | RS-232C   |                                   |  |

| Ports & interfaces           |                               | Packaging content           |  |
|------------------------------|-------------------------------|-----------------------------|--|
| VGA (D-Sub) ports quantity * | 1                             | Remote control included *   | ✓  |
| HDMI ports quantity *        | 1                             | Batteries included          | ✓  |
| DVI port *                   | ✓                             | Cables included             | AC   |
| Network                      |                               | Manual                      | ✓  |
| Ethernet LAN *               | ✓                             | Warranty card               | ✓  |
| Ethernet LAN (RJ-45) ports   | 1                             | WLAN adapter included       | ✓  |
| Storage                      |                               | Bundled software            | Inhalt DIY-App, EasyMP Multi PC Projection, Epson Projektor Content Manager, Epson Projektor Management, Epson Projektor Professional Tool |
| Card reader integrated *     | ✗                             |                             |  |
| Features                     |                               | Logistics data              |  |
| Noise level (economic mode)  | 30 dB                         | Quantity per pack           | 1 pc(s)  |
| Preset modes                 | Cinema, Dynamic, Presentation | Products per pallet         | 14 pc(s)   |
| Noise level *                | 37 dB                         | Pallet gross weight         | 0 g  |
| Country of origin            | Philippines                   | Products per pallet (UK)    | 14 pc(s)   |
| Password protection          | ✓                             | Pallet weight (UK)          | 0 g  |
|                              |                               | Harmonized System (HS) code | 85286200   |
|                              |                               | Other features              |  |
|                              |                               | Supported network protocols | HTTPS, IPv6, SNMP, ESC/VP.net, PJLink  |



8715946697451

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-DEC-2024. Prints or copies of Information are only valid on the printed Publication date