Samsung QB13R-M Digital signage flat panel 33 cm (13") LCD Wi-Fi 500 cd/m^2 Full HD Black Built-in processor Tizen 4.0 16/7

Brand : Samsung Product family: QBR-M Product code: LH13QBRMBGCXEN

Product name: QB13R-M

Samsung QB13R-M. Product design: Digital signage flat panel. Display diagonal: 33 cm (13"), Display technology: LCD, Display resolution: 1920×1080 pixels, Display brightness: 500 cd/m^2 , HD type: Full HD. Wi-Fi. Operating hours (hours/days): 16/7. Operating system installed: Tizen 4.0. Product colour: Black





Display		Design	
Panel type Display diagonal * Display technology *	ADS 33 cm (13") LCD	Bezel width (top) Bezel colour Mounting type	1.22 cm Charcoal Black Wall
Display resolution *	1920 x 1080 pixels	Performance	
Display brightness * HD type * Touchscreen * Native aspect ratio	ic) 10000:1 ntal 178°	Purpose * Operating hours (hours/days) HDCP HDCP version	Universal 16/7 ✓ 2.2
Response time Contrast ratio (typical)		Power	
Contrast ratio (typical) Contrast ratio (dynamic) Viewing angle, horizontal Viewing angle, vertical Pixel pitch		Power consumption (typical) * Power consumption (sleep) AC input voltage AC input frequency	27.5 W 0.5 W 100 - 240 V 50/60 Hz
Horizontal scan range	30 - 81 kHz	Computer system	
Vertical scan range Haze rate Pixel frequency (max) Colour gamut	48 - 75 Hz 25% 594 MHz 45%	Computer system * Computer system type Built-in processor * Operating system installed	✓ System on Chip (SoC) ✓ Tizen 4.0
Ports & interfaces		Weight & dimensions	
HDMI ports quantity * HDMI version HDMI input ports quantity DVI port *	MI version 1.4 MI input ports quantity 1 port * X	Display width Display depth Display height Display weight	322 mm 28.2 mm 193.5 mm 900 g
USB port * USB ports quantity	√ 1	Packaging data	
Ethernet LAN * Ethernet LAN (RJ-45) ports Wi-Fi * RS-232 interface	√ 1 √ √	Package width Package depth Package height Package weight	376 mm 248 mm 132 mm 1.7 kg
DC-in jack	✓	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Product design * Product colour * Screen shape	Digital signage flat panel Black Flat	Operating relative humidity (H-H) Certificates	10 - 80%
VESA mounting *	1 lat √	Certification	Class B 60950-1, 62368-1
Panel mounting interface	100 x 100 mm	Technical details	
Bezel width (bottom) Bezel width (side)	1.22 cm 1.22 cm	Audio out (mini jack)	1

Other features		
Flash memory	8000 MB	
RS-232 input ports	1	
RJ-45 input ports	1	



8806094965469

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.