## StarTech.com 3-Port PCI Express USB 3.0 Card + Gigabit Ethernet

Brand : StarTech.com Product code: PEXUSB3S3GE

Product name : 3-Port PCI Express USB 3.0 Card +

Gigabit Ethernet

StarTech.com 3 Port PCI Express USB 3.0 Card + Gigabit Ethernet - Fits Standard & Low-Profile PCs - UASP Supported - Optional SATA Power

StarTech.com 3-Port PCI Express USB 3.0 Card + Gigabit Ethernet. Internal. Connectivity technology: Wired, Host interface: PCI Express, Interface: Ethernet. Maximum data transfer rate: 5000 Mbit/s. Product colour: Metallic, Red





Connectivity technology* Wired  Host interface * PCI Express Ethernet  LAN (RJ-45) ports  Ethernet LAN (RJ-45) ports  USB 9.2. Gen 1 (3.1 Gen 1) Type-A hub ports quantity  Network  Network  Maximum data transfer rate * D5000 Mbit/s Ethernet LAN Ethernet LAN Ethernet LAN Ethernet LAN Ethernet LAN  Ethernet  Sound Mbit/s  Ethernet  Sound Mbit/s  IEEE 802.10, IEEE 802.10, IEEE 802.30, IEEB 802.3
Host interface * PCI Express Ethernet Ethernet Ethernet Ethernet LAN (RJ-45) ports 1  Steffernet LAN (RJ-45) ports 1  LUSB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity 3.2 Gen 1 (3.1 Gen 1)  CUSB wersion 3.2 Gen 1 (3.1 Gen 1)  PCI version 2.0  Network  Maximum data transfer rate * 5000 Mbit/s IEEE 802.10, IEEE 802.31, IEEE 802.32, IEEE 802.32, IEEE 802.32, IEEE 802.33, IEEE 802.33, IEEE 802.33, IEEE 802.33, IEEE 802.33, IEEE 802.34, IEEE 80
laternal *
Server operating systems supported Windows Server 2008 R2, Windows Server 2012

Design		Operational conditions	
Chipset  LED indicators  Mean time between failures (MTBF)  Certification	Renesas / NEC - µPD720201, Realtek - RTL8153 Activity, Link 1920042 h CE, FCC	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	5 - 50 °C -25 - 70 °C 20 - 80%
		Weight & dimensions	
		Width Depth Height Weight	18 mm 77 mm 120 mm 60 g
		Packaging data	
		Quantity Drivers included Package width Package depth Package height Package weight Packaging content	1 ✓ 144 mm 176 mm 33 mm 150 g
		Mounting brackets included  Manual	<i>'</i>
		Technical details	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	85176990
		Other features	
		Flow control support USB data transfer rates	✓ 5000 Mbit/s

UASP support





065030860796

0065030860796

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.