TP-Link Tapo C660 KIT Bullet IP security camera Outdoor 3840 x 2160 pixels Ceiling/wall

Brand : TP-Link   **Product family:** Tapo   **Product code:** TAPO C660 KIT

Product name : C660 KIT

- 4K Ultimate Clarity: The camera features 4K 8MP resolution and 18× digital zoom for superior clarity
- Free Person/Pet/Vehicle Detection: The camera identifies people, pets, and vehicles, reducing false alerts and unnecessary notifications
- 360° AI Tracking: The camera provides 360° coverage and accurately identifies and tracks people, pets, and vehicles
- Solar Charging, Maintenance-Free: Effortlessly monitor your space wirelessly from any location, liberating yourself from outlet limitations
- Starlight Color Night Vision: Capture vibrant images in low light. Enhance security with an F1.6 lens, starlight sensor, and spotlights
- 2.4/5 GHz Connection: Connect the camera to 5 GHz for faster speed or 2.4 GHz for longer distance
1/2.7" Progressive Scan CMOS Starlight Sensor, 850 nm IR LED (40 ft / 12 m), 4K 8MP (3840 x 2160 px), 15/20 fps

Performance	
Type *	IP security camera
Placement supported *	Outdoor
Connectivity technology *	Wired & Wireless
Virtual assistant	Amazon Alexa & Google Assistant
Infrared (IR) cut-off filter	✔
Remote viewing	✔
Certification	CB, CE, FCC, DOE, CEC, RCM, KC, JFR,VCCI,NCC, BSMI, NTRA, IP65

Design	
Form factor *	Bullet
Mounting type *	Ceiling/wall
Product colour *	White
LED indicators	System
International Protection (IP) code	IP65

Camera	
Lens viewing angle, horizontal	88°
Lens viewing angle, vertical	45°
Lens viewing angle, diagonal	105°

Image sensor	
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Sensor type *	CMOS

Lens system	
Digital zoom	18x
Number of lenses *	1
Maximum aperture number	1.6
Fixed focal length	4 mm

Audio	
Built-in microphone	✔

Network	
Ethernet LAN *	✔
Wi-Fi *	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Live view	✔

Storage	
Built-in HDD *	✘
Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)

Security	
Built-in siren	✔
Video motion detection	✔
Security algorithms	128-bit AES, SSL/TLS, WPA, WPA2-PSK
Alert notification type	Text alert message

Management features	
Reset button	✔

Power	
Power source type *	AC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz

Operational conditions	
Operating temperature (T-T)	-20 - 45 °C
Storage temperature (T-T)	-20 - 60 °C

Night vision

Night vision *	✔
Night vision distance	12 m
LED type	IR
Infra-red wavelength	850 nm

Video

Maximum resolution *	3840 x 2160 pixels
Total megapixels *	8 MP
Video compression formats	H.264
Frame rate	20 fps
Video streaming	✔

Audio

Built-in speaker(s)	✔

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	0 - 90%

System requirements

Mobile operating systems supported	Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.1, Android 7.1.2, Android 8.0, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 14.5, iOS 15, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3

Weight & dimensions

Width	185 mm
Depth	147 mm
Height	75 mm

Packaging data

Package type	Box

Sustainability

Compliance certificates	BSMI, CB, CE, Federal Communications Commission (FCC), KC, NCC, RCM, VCCI

Packaging content

Number of cameras *	1

8885020624199

1210002608138