



APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit, 6-year warranty

Brand : APC

Product code: SRT6KRMXLI-6W

Product name : Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit, 6-year warranty

Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit, 6-year warranty

APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card, Extended runtime, W/ rail kit, 6-year warranty:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 6kVA on-line 4U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with hard wire 3-wire (1P+N+E) input, 6x IEC 320 C13 and 4x IEC 320 C19 outlets, and 2x IEC jumper cables. The UPS has an embedded Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 6-year warranty and comes with a built-in lead-acid battery.



| Features | | Design | |
|----------------------------------|----------------------------|------------------------------------|---|
| UPS topology * | Double-conversion (Online) | Form factor * | Rackmount |
| Output power capacity * | 6 kVA | Rack capacity | 4U |
| Output power * | 6000 W | Product colour * | Black |
| Waveform * | Sine | Display type | LCD |
| Input operation voltage (min) * | 100 V | LED indicators | Status |
| Input operation voltage (max) * | 275 V | International Protection (IP) code | IP20 |
| Input frequency * | 40 - 70 Hz | Certification | REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE |
| Output operation voltage (min) | 220 V | Operational conditions | |
| Output operation voltage (max) | 240 V | Operating temperature (T-T) | 0 - 40 °C |
| Output frequency regulation | 50/60 Hz | Storage temperature (T-T) | -15 - 45 °C |
| Surge energy rating | 480 J | Operating relative humidity (H-H) | 0 - 95% |
| Number of output phases | 1 | Storage relative humidity (H-H) | 0 - 95% |
| Efficiency | 94.4% | Operating altitude | 0 - 3000 m |
| Crest factor | 3:1 | Non-operating altitude | 0 - 15000 m |
| Emergency Power Off (EPO) | ✓ | Technical details | |
| Noise level | 55 dB | Sustainability certificates | ENERGY STAR |
| Surge protection | ✓ | Compliance certificates | RoHS |
| Audible alarm(s) | ✓ | Weight & dimensions | |
| Auto-restart | ✓ | Width | 432 mm |
| Ports & interfaces | | Depth | 719 mm |
| AC outlet types | C13 coupler, C19 coupler | Height | 174 mm |
| Power plug | Terminal | Weight | 60 kg |
| AC outlets quantity | 10 AC outlet(s) | Package width | 610 mm |
| Number of output IEC jumpers | 2 | Package depth | 960 mm |
| USB port | ✓ | Package height | 370 mm |
| Serial interface | ✓ | Package weight | 67 kg |
| SmartSlot | ✓ | Packaging data | |
| Battery | | Rack mount kit | ✓ |
| Battery technology | Sealed Lead Acid (VRLA) | Bracket | ✓ |
| Battery capacity | 902 VAh | Cables included | USB cable |
| Typical backup time at full load | 2.5 min | Temperature sensor | ✓ |
| Typical backup time at half load | 8.7 min | | |
| Battery life (max) | 5 year(s) | | |

| Battery | | Packaging data | |
|------------------------|-------|-----------------------------|--------------------------|
| Battery recharge time | 1.5 h | Quick installation guide | ✓ |
| Hot-swap battery | ✓ | Warranty card | ✓ |
| Automatic battery test | ✓ | Software CD | ✓ |
| Cold start | ✓ | Logistics data | |
| | | Products per pallet | 6 pc(s) |
| | | Harmonized System (HS) code | 85078000 |
| | | Other features | |
| | | Packaging content | Web/SNMP Management Card |



8592978053499



3606481339003

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date