

TP-Link Omada DR3220v-4G wireless router Gigabit Ethernet Dualband (2.4 GHz / 5 GHz) Black

Brand : TP-Link Product family: Omada Product code: DR3220V-4G

Product name: DR3220v-4G

- AX3000 WiFi 6 with 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz*1*4
- VDSL2 35b: Supports 350Mbps DSL Access*2
- VDSL2/ADSL2+/ADSL2/ADSL Compatibility
- Centralized Cloud Management
- IPSec/PPTP/L2TP/OpenVPN/WireGuard/GRE/SSL VPN
- Load Balancing Between DSL and Ethernet WAN
- Omada Mesh Technology*3
- 3 \times RJ11 Ports (2 \times FXS, 1 \times DSL) & 5 \times RJ45 Gigabit Ports & 2 \times USB 3.0 Ports
- Desktop/Wall Mounting
- $-8.9 \times 5.2 \times 1.4$ in (226 × 131.2 × 35 mm)

2.4 GHz: 574 Mbps, 5 GHz: 2402 Mbps (HE160), 256 MB NAND, 512 MB DDR4, 393.5Mbps, 129.3Mbps, 126.7Mbps, 802.1Q VLAN, 50 Tunnels, CE, RoHS





WAN connection		Security	
Ethernet WAN *	✓	Security algorithms	WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal,
DSL WAN *	✓	Security digoritims	WPA3-Enterprise, WPA3-Personal
SIM card slot *	×	Guest access	✓
3G/4G USB modem compatibility *	✓	Access Control List (ACL)	✓
WAN connection type	RJ-45	URL filtering	✓
Wireless LAN features		System event log	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	DMZ support	✓
WLAN data transfer rate (max) *	2402 Mbit/s	Network address translation (NAT)	✓
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi	Protocols	
MILAN data to a Second of Section 1	6 (802.11ax)	DHCP client	✓
WLAN data transfer rate (first band) WLAN data transfer rate (second	574 MDIT/S	DHCP server	✓
band)	2402 Mbit/s	Universal Plug and Play (UPnP)	✓
Network		Voice codecs	G.711a, G.711ulaw, G.722, G.726, G.729ab
Ethernet LAN *	✓	Design	
Ethernet LAN interface type *	Gigabit Ethernet	Product colour	Black
Ethernet LAN data rates	10,100,1000 Mbit/s	Wall mountable	✓
Cabling technology	10/100/1000Base-T(X) IEEE 802.11a, IEEE 802.11ac, IEEE	Indication light	1
	802.11ax, IEEE 802.11b, IEEE	LED indicators	
Networking standards		LED IIIUICALOIS	DSL, LAN, USB, WLAN
	802.11g, IEEE 802.11n, IEEE	Product type *	DSL, LAN, USB, WLAN Tabletop router
	802.11g, IEEE 802.11n, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x		
Port triggering	802.1Q, IEEE 802.3, IEEE 802.3ab,	Product type *	
-	802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Product type * Packaging content	Tabletop router
Port triggering	802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x ✓	Product type * Packaging content Cables included	Tabletop router LAN (RJ-45), Phone
Port triggering Load balancing system	802.10, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Product type * Packaging content Cables included AC adapter included Antenna included	Tabletop router LAN (RJ-45), Phone
Port triggering Load balancing system Dynamic DNS (DDNS)	802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Product type * Packaging content Cables included AC adapter included Antenna included Antenna	Tabletop router LAN (RJ-45), Phone ✓
Port triggering Load balancing system Dynamic DNS (DDNS) Policy-based routing	802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Product type * Packaging content Cables included AC adapter included Antenna included Antenna Antenna Antenna design *	Tabletop router LAN (RJ-45), Phone
Port triggering Load balancing system Dynamic DNS (DDNS) Policy-based routing Static route	802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Product type * Packaging content Cables included AC adapter included Antenna included Antenna	Tabletop router LAN (RJ-45), Phone External

DSL features		Power	
ADSL	✓	Power source type *	AC
ADSL2	✓	Output voltage	12 V
ADSL2+	✓	Output current	3.3 A
VDSL2	✓	Operational conditions	
Ports & interfaces		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Ethernet LAN (RJ-45) ports *	4	Operating relative humidity (H-H)	10 - 90%
USB port *	✓	Storage relative humidity (H-H)	5 - 90%
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Weight & dimensions	
RJ-11 ports quantity	3	Width	226 mm
DC-in jack	✓	Depth	131 mm
Management features		Height	35 mm
Web-based management	✓	Packaging data	
Quality of Service (QoS) support	✓	Package type	Box
Reset button	✓	Number of products included	1 pc(s)
MU-MIMO technology	✓		



1210002608411

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.