



## APC Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 208V-230V, 8x C13+1x C19 IEC, Network card, Extended runtime



**Brand :** APC

**Product code:** SMX2200R2HVNC

**Product name :** Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 208V-230V, 8x C13+1x C19 IEC, Network card, Extended runtime



Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 208V-230V, 8x C13+1x C19 IEC, Network card, Extended runtime  
APC Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 208V-230V, 8x C13+1x C19 IEC, Network card, Extended runtime. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, C20 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 702 Ah, Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 667 mm, Height: 85 mm

Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount/Tower
Output power capacity *	2.2 kVA	Rack capacity	2U
Output power *	1980 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	208 V	LED indicators	✔
Input operation voltage (max) *	230 V	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Input frequency *	50/60 Hz		
Output operation voltage (min)	208 V	Operational conditions	
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	+/- 3 Hz	Storage temperature (T-T)	-15 - 45 °C
Output voltage regulation	5%	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	645 J	Storage relative humidity (H-H)	0 - 95%
Response time	10 ms	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✔	Non-operating altitude	0 - 15000 m
Noise level	55 dB	Technical details	
Surge protection	✔		
Audible alarm(s)	✔	Compliance certificates	RoHS
Web-based management	✔	Weight & dimensions	
Audible alarm modes	Battery replacement		
Auto-restart	✔	Width	432 mm
Ports & interfaces		Depth	667 mm
		Height	85 mm
AC outlet types	C13 coupler, C19 coupler, C20 coupler	Weight	37.4 kg
Power plug	C20 coupler	Package width	596 mm
AC outlets quantity	9 AC outlet(s)	Package depth	869 mm
USB 2.0 ports quantity	1	Package height	243 mm
Ethernet LAN (RJ-45) ports	1	Package weight	45.3 kg
Battery		Packaging data	
		Rack mount kit	✔
Battery technology	Sealed Lead Acid (VRLA)	Cables included	Input power cable, USB cable
Battery capacity	702 Ah	Quick installation guide	✔
Battery recharge time	3 h	Resource CD	✔
Hot-swap battery	✔	Logistics data	
Automatic battery test	✔		
		Products per pallet	8 pc(s)

Battery		Logistics data	
Cold start	✓	Harmonized System (HS) code	85078000
		Other features	
		Output voltage	230 V



0731304327738



731304327738

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date