NEC MultiSync M651 Digital signage flat panel 165.1 cm (65") LCD 500 cd/m² 4K Ultra HD Black Touchscreen

Brand: NEC Product family: MultiSync Product code: 60006094

Product name: M651

65", IPS, 500 cd/m, 60Hz

NEC MultiSync M651. Product design: Digital signage flat panel. Display diagonal: 165.1 cm (65"), Display technology: LCD, Display resolution: $3840 \times 2160 \text{ pixels}$, Display brightness: 500 cd/m^2 , HD type: 4K Ultra HD, Touchscreen. Product colour: Black





Display		Power	
Panel type LED backlighting type Display diagonal * Display technology * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio Response time	IPS Edge-LED 165.1 cm (65") LCD 3840 x 2160 pixels 500 cd/m² 4K Ultra HD ✓ 16:9 8 ms	Power consumption (typical) * Power consumption (standby) * Energy efficiency class (SDR) Energy efficiency class (HDR) Energy consumption (SDR) per 1000 hours Energy consumption (HDR) per 1000 hours AC input voltage AC input frequency	105 kWh 100-240 V 50-60 Hz
Contrast ratio (typical)	8000:1	Energy efficiency scale	A to G
Viewing angle, horizontal Viewing angle, vertical Display number of colours Display diagonal (metric) Horizontal scan range Vertical scan range Native refresh rate	178° 178° 1.076 billion colours 164 cm 15 - 135 kHz 23 - 86 Hz	Computer system	
		Video formats supported	H.263, H.264, HEVC/H.265, MP4, MPG, TS
		Audio formats supported Image formats supported Windows operating systems supported Linux operating systems supported	MP3 JPG ✓
Haze rate	28%	Weight & dimensions	
Ports & interfaces HDMI ports quantity * DisplayPorts quantity * USB port *	2 1 •• 1	Display width Display depth Display height Display weight	1458 mm 62.6 mm 836.2 mm 37.1 kg
USB ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-C		Packaging data	
ports quantity Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates	1 1 100 Mbit/s	Package width Package depth Package height Package weight	1736 mm 1033 mm 280 mm 49.3 kg
Design		Operational conditions	
Product design * Orientation Product colour * VESA mounting * Panel mounting interface	Digital signage flat panel Horizontal/Vertical Black 300 x 300 mm	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 20 - 80% -20 - 60 °C 10 - 90%

PerformanceLogistics dataPurpose *UniversalHarmonized System (HS) code85285210HDCP✓



5028695127531

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.