

Brother TD-4750TNWB label printer Direct thermal / Thermal transfer 300 x 300 DPI 152 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth

Brand: Brother Product code: TD4750TNWBZU1

Product name: TD-4750TNWB

- Ease of use with 2.3" colour LCD display
- Thermal transfer and direct thermal printing technology
- Range of connectivity options including USB, Network, WiFi and Bluetooth
- High capacity with 300m ribbon, minimising downtime
- 300dpi high resolution printing for crisp text and barcodes
- Fast print speeds up to 6 inches per second

TT/ DT, 300 \times 300, 2.3" LCD, 128 MB / 128 MB, Wi-Fi, Bluetooth, LAN 10/100 Mbps, USB, 3 kg Brother TD-4750TNWB. Print technology: Direct thermal / Thermal transfer, Maximum resolution: 300 \times 300 DPI, Print speed: 152 mm/sec. Connectivity technology: Wired & Wireless. Product colour: Black





Printing		System requirements	
Print technology * Colour *	Direct thermal / Thermal transfer	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Maximum resolution * Print speed * Maximum printing width * Maximum print length	300 x 300 DPI 152 mm/sec 10.5 cm 11.43 m	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.7 Lion, Mac
Paper handling			OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Maximum label width Maximum roll diameter Ports & interfaces	11.2 cm 12.7 cm	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Connectivity technology *	Wired & Wireless	Linux operating systems supported	✓
Ethernet LAN *	 ✓ 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n) ✓ 4.2 	Operational conditions	
Wi-Fi * Wi-Fi standards Bluetooth Bluetooth version		Operating relative humidity (H-H) Storage relative humidity (H-H) Operating temperature (T-T) Storage temperature (T-T)	5 - 40% 25 - 85% -40 - 60 °C 10 - 90 °C
USB port *	4.2	Weight & dimensions	
USB 2.0 ports quantity RS-232 ports Performance	1	Width Depth Height	219 mm 285 mm 191 mm
	128 MB	Weight	3 kg
Internal memory Flash memory	128 MB	Packaging content	
		Cables included Bundled software Quick start guide	AC, USB Bartender Ultra Lite Edition ✓

Performance		Packaging content	
Built-in barcodes	AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Code-128 Codabar Library, EAN128, EAN13, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, MaxiCode, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E	Software development kit (SDK)	✓
		Logistics data	
		Harmonized System (HS) code	84433210
		Technical details	
		Sustainability certificates	ENERGY STAR
Design		Other features	
Product colour *	Black	Languages support	Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Norwegian, Portuguese, Slovenian
Built-in display	✓		
Display *	LCD		
Display diagonal	5.84 cm (2.3")		
Colour display	✓		

