

4Cabling Pty Ltd ABN 74 123 035 889 4cabling.com.au SALES SUPPORT: 1300 855 235 sales@4cabling.com.au STORE LOCATIONS: Sydney | Melbourne | Brisbane | Perth



3m LC-SC/APC OS1 / OS2 Singlemode Fibre Optic Duplex Patch Lead - 2mm Oversleeving | Yellow

Product Images





Description

3m LC-SC/APC OS1 / OS2 Singlemode Fibre Optic Duplex Patch Lead - 2mm Oversleeving | Yellow

Optical fibre cables are the thin, flexible fibres of glass that carry telephone conversations and emails all over the world in a matter of seconds with much less interference than copper cables. Fibre-Optic cables need less amplification to boost signals so they travel better over longer distances.

4Cabling's LC-SC/APC OS1 / OS2 Singlemode Fibre Optic Patch Leads provide connection for high speed and legacy networks like Gigabit Ethernet, Fast Ethernet and Ethernet and are immune to EMI/RFI. They are mainly used on patch panels for the connection between outlets and terminal equipment. The multimode optical fibre cables are manufactured using LSZH cables which conform to IEC, EIA TIA and Telecordia standards.

The big difference between APC and UPC connectors is the fibre connector endface. APC connectors feature a fibre connector endface that is polished at an 8-degree angle, while UPC connectors are polished with no angle.

Applications include:

- Termination enclosure to equipment patching
- Equipment to equipment patching
- Cross-connect patching

FEATURES

- OM1 fibre patch leads conform to TIA/EIA-568, 492AAAA
- OS2 fibre patch leads conform to ITU-T G.652.D, TIA/EIA 492CAAB
- Individually labelled for lead tracing
- Low smoke zero halogen (LSZH) cable
- Manufactured with stringent quality control
- All leads are supplied with a factory test report
- Duplex configurable assemblies for LC, SC, ST as well as MTRJ Patch leads
- All ends are polished and individually inspected for correct polishing
- Supports high speed multi-channel data, voice & video applications
- Duplex yellow jacket zip cord multi-mode 9μ / 125μ
- UL approved fibre optic cables
- Conforms to ISO/ IEC 11801

FIBRE SPECIFICATIONS

Mode: OS1 / OS2 SinglemodeFibre Terminations: LC-SC/APC

Length: 3mColour: YellowOversleeving: 2mm

Multimode	Core/Cladding Diameter (µm)	Fast Ethernet 100BASEFX	1 Glgabit 1000BASE-SX	1 Gigabit 1000BASE-LX	10 Gigabit 10GBASE	40 Gigabit 40GBASE	100 Glgabit 100GBASE
OM1	62.5/125	2000 14-1	275 Meters	550 Meters	33 Meters	N/A	
OM2					82 Meters		
OM3*	50/125	2000 Meters	550 Meters	550 Meters	300 Meters	100 Meters	100 Meters
OM4*					400 Meters	150 Meters	150 Meters
Singlemode							
OS1	9/125	2000 Meters	5 km at 1310nm	5 km at 1310nm	10 km at 1310nm		
* Laser Optimised							

WARRANTY

3-year limited warranty.

WHY 4CABLING?

- Australia's leading importer & wholesaler of 19" server racks, copper, ethernet cable, fibre & structured networking products
- ISO 9001, NSW Govt. & GITC (QLD Govt.) approved supplier
- Secure online shopping 24/7
- A loyal customer base of 100k+ who trust us for their data & electrical needs
- Over 3000 quality products in stock ready to go
- All products are approved as per local Australian standards
- Warranty & peace of mind return policy
- Lightning fast delivery nationwide
- Expert advice
- Proudly 100% Australian owned & operated

expert advisers.

Additional Information

SKU	FL.OS2LCSCAPC3M
Manufacturer Part#	FL.OS2LCSCAPC3M
Length	3m
Terminations	SC/APC - LC
Colour	Yellow
Transmission Mode	OS1/OS2
Package	Single pack
Jacket Material	LSZH
Warranty	3 Years

