## Poly Studio X72 All-In-One Video Bar with TC10 Controller Kit No Power Cord TAA





\*Product image may differ from actual product

## Made for big rooms and even bigger ideas

Don't let the size of the room slow your team down during hybrid meetings. Easily set up the Poly Studio X72 all-in-one video bar with Al-enhanced video and audio technology, seamless scalability and flexibility to join nearly any cloud video call.

#### No one gets left behind

Ensure everyone feels included and make communication effortless with the built-in AV AI technology in this all-in-one video bar.

#### Big room? We've got you covered

Outfit larger rooms to ensure everyone's captured with this all-in-one video bar. Simply add Poly peripherals1 to enhance every meeting experience.

#### Ready. Set. Join the call

Enjoy hassle-free connections and easy setup with the Poly Studio X72 video bar, featuring an all-in-one design and native cloud video experience.

## **Featuring**

#### Participants in. Distractions out

Make your presence felt with Poly DirectorAl. Framing and tracking modes enhance meetings. Remove distractions and confusion over who says what.

#### All eyes on the action

Enjoy rich and sharp images with the dual 4K 20MP cameras with 70° and 120° fields of view, ideal for large-sized meeting rooms.

#### Never miss a beat

Let voices take center stage with the innovative acoustic chamber design and beamforming microphone array of the Poly Studio X72 video bar.

#### Zero in on the conversation

Fuel productivity with Poly audio innovations. Al and machine learning technology provides a focused call that brings people closer together.

#### Adapts to your needs

Expand your video conferencing setup seamlessly by connecting additional peripherals over Ethernet for a simple, cost-effective, and scalable setup.

#### Choose your app. Join the call. Done

Join calls without missing a beat—the Poly Studio X72 is our most flexible all-in-one video bar to date, working with the apps you already know.

### Sustainability in action

#### Built for a better tomorrow

Containing recycled plastics<sup>2</sup> and shipped in paper-based packaging<sup>3</sup> derived from at least 60% recycled materials, this all-in-one video bar enables more impactful meetings in large rooms with less impact on the environment.

# Poly Studio X72 All-In-One Video Bar with TC10 Controller Kit No Power Cord TAA





\*Product image may differ from actual product

### **Specifications**

#### Camera

Camera resolution: 2160p, 4K UHD (3840 x 2160) Diagonal field of view (dFoV): 140° (wide); 78° (narrow) Horizontal field of view (hFoV): 120° (wide); 70° (narrow)

Total Camera Megapixels: 2 x 20 MP

Zoom capability: 7.3x digital Camera type: Dual-lens

Lens privacy capabilities: Integrated

Smart camera technology: Poly DirectorAl with speaker

framing, people framing, group framing

#### Video

People video resolution: 4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 30 fps from 512 Kbps

Content video resolution (input): UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); UXGA (1600 x 1200); SXGA (1280 x 1024); WXGA (1280 x 768); HD (1280 x 720); XGA (1024 x 768); SVGA (800 x 600)

Content video resolution (output): UHD (3840 x 2160); WUXGA (1920 x 1200); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA+ (1400 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768)

**Video frame rate:** 5-30 fps (up to 4K resolution at 15 fps in call) **Video standards:** H.264 AVC; H.264 High Profile; H.265

Content sharing: Apple AirPlay; Miracast; Digital

Whiteboarding; HDMI input

Digital signage: Appspace; Raydiant

#### Connectivity and communications

External I/O ports:

1 USB Type-C<sup>®</sup> 5Gbps signaling rate 2 USB Type-A 5Gbps signaling rate

1 line in

1 line out

1 line in (optional microphone)

2 HDMI-out 2.0 (video, 4K @ 30 Hz)

1 HDMI-in 1.4 (video and audio, 4K @ 30 Hz)

Interoperability:

Zoom

Microsoft Teams

All cloud service providers through Poly Video App mode USB Device mode

Wireless Technology:

Bluetooth® 5.0; Wi-Fi 802.11a/b/g/n/ac/ax (MIMO) Multi-channel Concurrency<sup>1</sup>

#### **Audio**

**Audio features:** 

Poly NoiseBlockAl technology Poly Acoustic Fence technology

Microphone type: Two MEMS microphones; Two second-order microphones

Microphone Pickup Range: Up to 7.62 m Up to 25 ft

Speaker output power: 2 x 20 W (RMS for mid speakers); 2 x 30 W (maximum for mid speakers); 2 x 15 W (RMS for tweeter speakers); 2 x 20 W (maximum for tweeter speakers)

Audio standards: 22 kHz with Polycom Siren 22 technology; 20 kHz with G.719 (M-Mode) and Polycom Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1; 3.4 kHz with G.711, G.728, G.729A

Sensitivity (speaker): 83 dB (mid speakers); 89 dB (tweeter speakers)

Speaker type: Two-way dual speakers

#### Power supply

Power supply type: External; Auto sensing Operating voltage: 37 VA @ 120 V @ 60 Hz; 37 VA @ 230 V @ 50/60 Hz

Heat dissipation cooling: 65 BTU/h

#### Certifications

Certified collaboration software: Microsoft Teams; Zoom

#### **Environmental**

Operatina altitude: 4.877 m

Operating humidity range: 15 to 80% Non-operating humidity range: 5 to 95% Operating temperature range: 0 to 40°C

Non-operating temperature: -40 to 70 °C -40 to 158 °F Sustainable impact specifications: Contains recycled plastics; Paper-based packaging derived from at least 60% recycled materials<sup>2,3</sup>



# Poly Studio X72 All-In-One Video Bar with TC10 Controller Kit No Power Cord TAA







\*Product image may differ from actual product

### **Specifications**

#### Management

Management software:

Poly Lens

#### Security

Standard Kensington lock slot

**Security management:** 

AES 128 bits encryption

AES 256 bits encryption

Media encryption (H.323, SIP)

H.235.6 support

Authenticated access to admin menus, web interface, and

APIs

**BFCP** 

Local account password policy configuration

Security profiles

Secure defaults

Remote logging with support for TLS

Active directory external authentication

#### **Network**

Network capabilities: IPv4; IPv6; 1x 10/100/1G Ethernet; Auto-MDIX; H.323 and/or SIP up to 6 Mbps in Poly App video mode; Polycom Lost Packet Recovery (LPR) technology; Dynamic bandwidth allocation; Reconfigurable MTU size; Web proxy support: basic, digest, and NTLM; Simple Certificate Enrollment Protocol (SCEP)

#### Weight and dimensions

**Product Primary Color: Black** 

Weight: 3300 g (Poly Studio X72); 1270 g (Poly TC10

controller)

Product dimensions: 840.18 x 135.4 x 117.93 mm (Poly Studio

X72); 260 x 184 x 64 mm (Poly TC10 controller)

Package weight: 9 kg

Package dimensions: 34 x 27 x 94 cm

Cartons per layer: 4
Pallet (layers): 6
Cartons per pallet: 24
Products per layer: 4
Products per pallet: 24
Pallet weight: 180 kg

Pallet dimensions: 217 x 100 x 120 cm

UPC number: 198415349507 Product number: A4MB1AA

Product name: Poly Studio X72 All-In-One Video Bar with

TC10 Controller Kit No Power Cord TAA

#### Warranty

Poly standard one-year limited warranty

#### Country of origin

Country of origin: Made in Laos

#### Regulatory

RMN number: PATX-STX-72R

#### What is in the box

Ethernet cable
Wall mount kit
2 HDMI cable
AC power adapter
Poly TC10 touch controller
Poly Studio X72



# Poly Studio X72 All-In-One Video Bar with TC10 Controller Kit No Power Cord TAA

## Accessories and services (not included)

Poly Studio G/X/V Bluetooth Remote Control



Product number: 874R8AA

Poly TC10 White Touch Controller



The Poly TC10 touch control panel makes meetings more productive and allows users to easily schedule workspaces and conference rooms.

Product number: 875J5AA

Poly Studio X70 VESA Mount	Product number: 875L2AA
Poly Studio X70 Table Stand	Product number: 875L3AA
Poly Studio X50/X52/X70/USB Expansion Microphone Cable Extender Pack	Product number: 875M4AA

### **Footnotes**

#### **Messaging Footnotes**

<sup>1</sup> Supported Poly peripherals include the following Poly cameras: Poly Studio E360, Poly Studio E60 and Poly Studio E70. Poly audio includes Poly Studio Table Microphone, pending regional availability and sold separately. <sup>2</sup> Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard. <sup>3</sup> Percent of paper-based packaging made from sustainably sourced, certified, and recycled fibers. <sup>4</sup> Supported Poly peripherals over Ethernet include the Poly Studio E360 and Poly Studio Table Microphone, pending regional availability and sold separately. <sup>5</sup> With the Poly Studio X72, you can extend people and content across three displays while in Zoom mode using a pluggable USB adapter, sold separately.

#### **Technical Specifications Footnotes**

<sup>1</sup>TAA, JITC and no radio versions available. <sup>2</sup> Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard. <sup>3</sup> Percent of paper-based packaging made from sustainably sourced, certified, and recycled fibers.

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by HP is under license. Other trademarks and trade names are those of their respective owners. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum.



