# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

## USB-A to RJ45 Serial Rollover Cable (M/M) -Cisco Compatible, 250 Kbps, 6 ft. (1.83 m), Gray

## MODEL NUMBER: U209-006-RJ45-X









Connects your computer or laptop's USB port to your Cisco modem, router, firewall, switch or other serialbased Cisco device with a console port.

### Features

**Connects Computer's USB Port to Cisco Device**Connect computer or laptop to Cisco modem, router, firewall, switch or other serial-based Cisco device with a console portWorks with older and new Cisco models6 ft. long

Top-of-the-Line PerformanceSupports data transfer rates up to 250 KbpsSupports remote wake-up and power managementUtilizes FTDI chipset.

Easy to UseNo other cables or adapters neededNo external power requiredDriver CD included (drivers also available online for download if your computer has no CD drive)

# **Specifications**

OVERVIEW	
UPC Code	037332190017
PHYSICAL	
Color	Gray
Material of Construction	PVC
Cable Jacket Color	Gray
Cable Jacket Material	PVC
Cable Outer Diameter (OD)	2.5 mm
Wire Gauge (AWG)	26

### Highlights

- Supports data transfer rates up to 250 Kbps
- Supports remote wake-up and power management
- Compatible with Windows, Mac and Linux
- No cables, adapters or external power required

#### **System Requirements**

- Computer with available USB port
- Cisco device with available RJ45 console port
- Windows, Mac or Linux operating system

#### Package Includes

- U209-006-RJ45-X USB to RJ45 Cisco Serial Rollover Cable
- Driver CD
- Owner's manual

# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

[	
Cable Length (ft.)	6
Cable Length (m)	1.83
Cable Length (in.)	72
Shipping Dimensions (hwd / in.)	1.20 x 4.70 x 4.10
Shipping Dimensions (hwd / cm)	3.05 x 11.94 x 10.41
Shipping Weight (lbs.)	0.24
Shipping Weight (kg)	0.11
Unit Packaging Type	Box
Unit Weight (Ibs.)	0.2425
Unit Weight (kg)	0.11
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Storage Temperature Range	-4° to 140°F (-20° to 60°C)
Relative Humidity	0% to 90% RH (Non-Condensing)
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	RJ45 (MALE)
Connector Plating	Gold
FEATURES & SPECIFICATIONS	
IP68 Rated	No
IP20 Rated	No
Driver Required	Yes
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.