



APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine

Brand : APC

Product code: SRT6KRMXLIM

Product name : Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine



Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine
APC Smart-UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/ rail kit, Marine. UPS topology: Double-conversion (Online), Output power capacity: 6 kVA, Output power: 6000 W. AC outlet types: C13 coupler, C19 coupler, IEC Jumpers, Power plug: Terminal, AC outlets quantity: 13 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 1 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 4U. Width: 432 mm, Depth: 719 mm, Height: 174 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Number of batteries supported	1
Output power capacity *	6 kVA	Battery life (max)	5 year(s)
Output power *	6000 W	Battery recharge time	1 h
Waveform *	Sine	Hot-swap battery	✓
Input operation voltage (min) *	160 V	Automatic battery test	✓
Input operation voltage (max) *	275 V	Design	
Input frequency *	40 - 70 Hz	Form factor *	Rackmount
Output operation voltage (min)	220 V	Rack capacity	4U
Output operation voltage (max)	240 V	Product colour *	Black
Output frequency	50/60 Hz	Display type	LCD
Surge energy rating	480 J	LED indicators	✓
Crest factor	3:1	International Protection (IP) code	IP20
Emergency Power Off (EPO)	✓	Certification	CE, EAC, RCM, VDE, REACH
Output voltage Total Harmonic Distortion (THD)	3%	Operational conditions	
Noise level	55 dB	Operating temperature (T-T)	0 - 40 °C
Surge protection	✓	Storage temperature (T-T)	-15 - 45 °C
Audible alarm(s)	✓	Operating relative humidity (H-H)	0 - 95%
Auto-restart	✓	Storage relative humidity (H-H)	0 - 95%
Temperature voltage compensation	✓	Operating altitude	0 - 3000 m
Ports & interfaces		Non-operating altitude	0 - 15000 m
AC outlet types	C13 coupler, C19 coupler, IEC Jumpers	Technical details	
Power plug	Terminal	Compliance certificates	RoHS
AC outlets quantity	13 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	432 mm
USB 2.0 ports quantity	1	Depth	719 mm
Serial interface	✓	Height	174 mm
Ethernet LAN (RJ-45) ports	1	Weight	60 kg
Cabling technology	10/100Base-T	Package width	610 mm
SmartSlot	✓	Package depth	960 mm
Battery		Package height	370 mm
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
		Package volume	67000 cm ³
		Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000



0731304320838



731304320838

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date