

## TP-Link INSIGHT S455 Turret CCTV security camera Outdoor 2880 x 1620 pixels Ceiling

**Brand :** TP-Link **Product code:** INSIGHT S455(2.8MM)

**Product name:** INSIGHT S455

- 5MP Super-High Definition and 24h Full-Color
- People & Vehicle Analytics§
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Active Defense and Two-Way Audio
- IP67 Waterproof
- H.265+ Compression Technology

VIGI 5MP Full-Color Turret Network Camera, 1/2.7", 1/3 to 1/10000 s, F1.6, 2880 x 1620, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC  $\pm$  5%, Max. 11 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 12 W, IP67, 111 x 111 x 83.7 mm, 0.48 kg, White

TP-Link INSIGHT S455. Type: CCTV security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Turret. Lens viewing angle, horizontal: 111.4°, Lens viewing angle, vertical: 58.8°, Lens viewing angle, diagonal: 134°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Sensor type (panoramic camera): CMOS, Signal-to-Noise Ratio (SNR) (panoramic camera): 52 dB





Performance		Video	
Type * Placement supported *	·	Digital Wide Dynamic Range (DWDR)	1
Connectivity technology *	Wired	Audio	
Maximum operating distance	64 m	Built-in speaker(s)	✓
Wide Dynamic Range (WDR)	✓	Audio system	2-way
Day/night mode	✓	Audio input channels	1 channels
Infrared (IR) cut-off filter	✓	Audio output channels	1 channels
Remote viewing	✓	Audio formats supported	G.711 A-law
Dynamic range	120 dB	Sample rate	8 kHz
Plug and Play	✓	Built-in microphone	✓
Design		Number of microphones	1
Form factor *	Turret	Bit rate range	0 - 64 Kbit/s
Mounting type *	Ceiling	Network	
Product colour *	White	Ethernet LAN *	✓
Housing material Protection features International Protection (IP) code	Metal Waterproof IP67	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Weatherproof	✓	Wi-Fi *	×
Camera		Bluetooth *	×
Lens viewing angle, horizontal Lens viewing angle, vertical	111.4° 58.8°	Live view	✓
		Storage	
Lens viewing angle, diagonal Tilt angle range Camera shutter speed	134° 0 - 90° 1/3 to 1/10000	Compatible memory cards Maximum memory card size	MicroSD (TransFlash) 512 GB
·	1/3 to 1/10000	Security	
Image sensor	25 4 / 2.7 mm /1 / 2.7"\	Built-in siren	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Video motion detection	✓
Progressive scan	CMOS	Alert notification type	Push notification
Sensor type *	CIMOS	Motion sensor	✓

Panoramic camera		Security	
Sensor type (panoramic camera)	CMOS	Mirror	✓
Signal-to-Noise Ratio (SNR) (panoramic camera)	52 dB	Management features	
Digital Wide Dynamic Range (DWDR) (panoramic camera)	<b>✓</b>	Web browser	✓
, , , ,		Cloud-managed *	<b>✓</b>
Lens system		Reset button	✓
Recognize distance	13 m	Power	
Focal length range Fixed focus	2.8 mm	Power source type *	DC, PoE
	•	Power consumption (max)	11 W
Night vision  Night vision *	<b>/</b>	Power consumption (Power over Ethernet (PoE))	12 W
LED type	IR/White	DC output voltage	12
Video	TY TITLE	Operational conditions	
Maximum resolution * Total megapixels * Video compression formats	solution * 2880 x 1620 pixels  5 MP  ression formats H.264, H.264, H.265, H.265+  ling ✓ Constant Bit Rate (CBR)/Variable Bit Rate (VBR)  Main Stream: 256 Kbps to 6 Mbps, Sub-Stream: 64 Kbps to 512 Kbps  compensation (BLC) ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-30 - 60 °C -40 - 60 °C 0 - 95% 0 - 95%
Video recording		Weight & dimensions	
Bit rate control  Bit rate  Back Light Compensation (BLC)		Width Height Length Weight	111 mm 83.7 mm 111 mm 480 g
Highlight Compensation (HLC)	<b>*</b>	Packaging data	
		Package type	Box
		Packaging content	
		Number of cameras *	1
		Mounting kit	1
		Screws included	✓
		Drilling template included	✓
		Manual	✓



1210002604468

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.