



LG 55XE3C Signage Display Digital signage flat panel 139.7 cm (55") Full HD Black 24/7



Brand : LG

Product code: 55XE3C

Product name : 55XE3C

55" IPS Full HD 1920 x 1080, 1000:1, 50000H, HDMI/ DP/ DVI-D/ Audio, 100 - 240 V/ 50 - 60 Hz

[LG 55XE3C Signage Display Digital signage flat panel 139.7 cm \(55"\) Full HD Black 24/7:](#)

SMART BRIGHTNESS CONTROL

The auto-brightness sensor and preset time scheduler save power whenever possible.

DUST & HUMIDITY PROTECTION

The conformal coating enhances circuit board reliability by protecting it from dust, iron shavings, humidity and other harsh conditions.

LOW POWER CONSUMPTION USING THE M+ PANEL

The M+ panel offers excellent energy efficiency and cost savings and decreases power consumption by approx. 31% compared to conventional RGB panels*.

WEB MONITORING

The embedded web monitoring allows a variety of parameters to be diagnosed in real time using temperature, pixel, door, ambient light and gyro sensors. It can be easily controlled at all times.

LG 55XE3C. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 1920 x 1080 pixels, HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black

Display		Performance	
Display diagonal *	139.7 cm (55")	International Protection (IP) code	IP56
Display resolution *	1920 x 1080 pixels	Power	
HD type *	Full HD	Power consumption (typical) *	350 W
Touchscreen *	✗	AC input voltage	100 - 240 V
Native aspect ratio	16:9	AC input frequency	50 - 60 Hz
Contrast ratio (typical)	1000:1	Weight & dimensions	
Viewing angle, horizontal	178°	Width	745.3 mm
Viewing angle, vertical	178°	Depth	160 mm
Panel life	50000 h	Height	1345.4 mm
Ports & interfaces		Weight	70 kg
HDMI ports quantity *	1	Packaging data	
DVI port *	✓	Package width	1027 mm
DVI-D ports quantity	1	Package depth	309 mm
DisplayPorts quantity *	2	Package height	1491 mm
USB ports quantity	1	Package weight	100.5 kg
USB version	3.2 Gen 1 (3.1 Gen 1)	Packaging content	
Ethernet LAN *	✓	Remote control included	✓
Ethernet LAN (RJ-45) ports	1	Cables included	HDMI, USB
RS-232C	✓	Operational conditions	
Design		Operating temperature (T-T)	-30 - 50 °C
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	10 - 100%
Orientation	Horizontal/Vertical	Other features	
Product colour *	Black	Manual	✓
Performance		Portrait mode	✓
Operating hours (hours/days)	24/7		



8806087857337

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-AUG-2024. Prints or copies of Information are only valid on the printed Publication date