ASUS ProArt PA24ACRV computer monitor 60.5 cm (23.8") 2560 x 1440 pixels Quad HD LCD Black

Brand : ASUS Product family: ProArt Product code: 90LM08Y0-

B01M70

Product name : ProArt

PA24ACRV

- 23.8-inch QHD (2560 x 1440) LED backlight display with IPS 178° wide viewing angle panel
- International color standard 95% DCI-P3 and 100% sRGB wide color gamut
- Calman Verified with factory calibrated for excellent Delta E < 2 color accuracy
- Extensive connectivity including DP over USB-C™ with 96W Power Delivery, DisplayPort (MST), HDMI and USB hub
- Built-in Ambient Light Sensor synchronizes display brightness and color temperature with environment light changes
- Ergonomic design with tilt, swivel, pivot and height adjustments for a comfortable viewing experience
- Green Sustainability: paper packaging and energy-efficient environmental standards ProArt Display PA24ACRV Professional Monitor 24-inch (23.8-inch viewable), IPS, QHD (2560 x 1440), 95% DCI-P3, Color Accuracy Δ E < 2, Calman Verified, USB-C PD 96W, VESA DisplayHDR 400, VESA MediaSync, Ergonomic Stand, Green Sustainability





| Display | | Ports & interfaces | |
|--|---|--|---|
| Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (peak) | 60.5 cm (23.8") 2560 x 1440 pixels Quad HD 16:9 LCD IPS LED X 400 cd/m² | HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Headphone out * Headphone outputs HDCP HDCP version | 1 2.0 2 1.4 1 1 |
| Display brightness (typical) Response time * | 350 cd/m² 5 ms | Ergonomics | |
| Anti-glare screen Screen shape * Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Pixel density Viewable size, horizontal Viewable size, vertical Digital horizontal frequency | 0.2058 x 0.2058 mm 123 ppi 52.7 cm 29.6 cm | VESA mounting * Panel mounting interface Wall mountable Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment | 100 x 100 mm Kensington 13 cm -90 - 90° -30 - 30° -5 - 23° |
| Digital vertical frequency Display diagonal (metric) | | Tilt angle range Power | J 23 |
| High Dynamic Range (HDR) supported | √ | Energy efficiency class (SDR) * Energy efficiency class (HDR) * | E G |

| Dienlay | | Power | |
|--|--|--|--|
| Display | | | |
| High Dynamic Range (HDR) technology | DisplayHDR 400, High Dynamic Range 10 (HDR10) | Energy consumption (SDR) per 100 hours * | ⁰ 18 kWh |
| Colour gamut standard Colour gamut | DCI-P3 95% | Energy consumption (HDR) per 1000 hours * | 39 kWh |
| sRGB coverage (typical) | 100% | Power consumption (typical) * | 15 W |
| 3 (), | 10070 | Power consumption (off) | 0 W |
| Performance | | Power consumption (PowerSave) | 0.5 W |
| Flicker-free technology | ✓ | AC input voltage | 100 - 240 V |
| Low Blue Light technology | ✓ | AC input frequency | 50/60 Hz |
| Multimedia | | Energy efficiency scale | A to G |
| Number of speakers | 2 | European Product Registry for Energy Labelling (EPREL) code | 1829124 |
| RMS rated power | 4 W | Weight & dimensions | |
| Built-in speaker(s) * | • | Width (with stand) | 539.6 mm |
| Built-in camera * | × | Depth (with stand) | 197.2 mm |
| Design | | Height (with stand) | 515.1 mm |
| Market positioning * | Photo editing | Weight (with stand) | 5.6 kg |
| Product colour * | Black | Width (without stand) | 539.6 mm |
| Feet colour | Silver | Depth (without stand) | 44.6 mm |
| Ports & interfaces | | Height (without stand) | 322.2 mm |
| Built-in USB hub * | 1 | Weight (without stand) | 3.9 kg |
| USB hub version | 3.2 Gen 1 (3.1 Gen 1) | Packaging data | |
| Number of USB Type-C upstream | | Package width | 620 mm |
| ports quantity | 1 | Package depth | 127 mm |
| USB Type-A downstream ports | 3 | Package height | 390 mm |
| quantity | | Package weight | 8.1 kg |
| USB Type-C downstream ports quantity | 1 | Package type | Box |
| USB Type-C DisplayPort Alternate Mode | ✓ | Sustainability | |
| | | Sustainability compliance | ✓ |
| USB Power Delivery (USB PD) USB Power Delivery up to | 96 W | Sustainability certificates | EPEAT Gold, Forest Stewardship Council (FSC) Mix, TCO |
| | | | |





4711387308127

0197105308138



197105308138

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.