



D-Link DXS-1210-10TS network switch Managed L2/L3 10G Ethernet (100/1000/10000) 1U Black, Silver

Brand : D-Link

Product code: DXS-1210-10TS

Product name : DXS-1210-10TS

Smart Switch, 10 Gigabit, 8 x RJ-45, 2 x SFP+

D-Link DXS-1210-10TS. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 16000 entries. Networking standards: IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Rack mounting, Form factor: 1U



Management features		Technical details	
Switch type *	Managed	Shipping (inner) case height	38.3 cm
Switch layer	L2/L3	Shipping (inner) case width	31.4 cm
Quality of Service (QoS) support	✓	Shipping (inner) case length	56.2 cm
Web-based management	✓	Shipping (inner) case net weight	13.1 kg
MIB support	Bridge, MIB-II	Products per shipping (inner) case	3 pc(s)
Ports & interfaces		Pallet gross weight (air)	272.5 kg
Basic switching RJ-45 Ethernet ports quantity *	8	Master (outer) cases per pallet (air)	18 pc(s)
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Products per pallet (air)	54 pc(s)
SFP+ module slots quantity	4	Pallet gross length	110 cm
Network		Pallet gross width	120 cm
Networking standards *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Pallet height (air)	128.4 cm
		Pallet gross weight (sea)	441.7 kg
		Master (outer) cases per pallet (sea)	30 pc(s)
		Products per pallet (sea)	90 pc(s)
		Pallet height (sea)	2.05 m
10G support *	✓	Shipping (inner) case gross weight	14.1 kg
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10BASE-T, 10GBASE-T	Power	
Port mirroring	✓	AC input voltage	100 - 240 V
Flow control support	✓	AC input frequency	50 - 60 Hz
Link aggregation	✓	Power consumption (max)	68.67 W
Broadcast storm control	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✗
Spanning tree protocol	✓	Operational conditions	
Head-of-line (HOL) blocking	✓	Operating temperature (T-T)	-5 - 50 °C
VLAN support	✓	Storage temperature (T-T)	-40 - 70 °C
Number of VLANs	4000	Operating relative humidity (H-H)	0 - 95%
Data transmission		Storage relative humidity (H-H)	0 - 95%
MAC address table *	16000 entries	Weight & dimensions	
Store-and-forward	✓	Width	440 mm
Number of queues	8	Depth	210 mm
Jumbo frames support	✓	Height	44 mm
Security		Weight	3.1 kg
DHCP features	DHCP server, DHCP client	Packaging data	
Access Control List (ACL)	✓	Package width	349 mm
IGMP snooping	✓	Package depth	546 mm
Security algorithms	802.1x RADIUS, SSH, SSL/TLS	Package height	96 mm
Multicast features		Package weight	4.38 kg
Multicast support	✓	Logistics data	
		Harmonized System (HS) code	85176990

Protocols	
Management protocols	SNMPv1/2/3, Telnet, SSH, TFTP, RMON v1/v21
Design	
Rack mounting *	✓
Form factor	1U
Product colour	Black, Silver
LED indicators	✓
Safety	cUL, CB, CE, CCC, BSMI
Certification	CE FCC C-Ticket VCCI BSMI CCC



0790069409325



790069409325

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-AUG-2024. Prints or copies of Information are only valid on the printed Publication date