

Philips V Line 275V8LA/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black

Brand : Philips

Product family: V Line

Product code: 275V8LA/00

Product name : 275V8LA/00

Monitor 275V8LA LCD monitor

Philips V Line 275V8LA/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black:

Philips V line wide-view monitor gives viewing beyond boundaries, great value with essential features. Adaptive-Sync delivers smooth video display. Features like anti-glare, LowBlue mode and flicker-free for easy-on-the-eyes.

Philips V Line 275V8LA/00. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Tilt angle range	-5 - 20°
Display resolution *	2560 x 1440 pixels	On Screen Display (OSD)	✓
HD type *	Quad HD	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Native aspect ratio *	16:9		
Display technology *	LED		
Panel type *	VA	Plug and Play	✓
Backlight type	W-LED	LED indicators	Operation, Stand-by
Touchscreen *	✗	Power	
Display brightness (typical)	250 cd/m²	Energy efficiency class (SDR) *	F
Response time *	4 ms	Energy efficiency class (HDR) *	Not available
Anti-glare screen	✓	Energy consumption (SDR) per 1000 hours *	26 kWh
Screen shape *	Flat	Power consumption (typical) *	25.2 W
Contrast ratio (typical) *	4000:1	Power consumption (standby) *	0.5 W
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (off)	0.3 W
Maximum refresh rate *	75 Hz	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Power supply type	Internal
Display number of colours *	16.7 million colours	Energy efficiency scale	A to G
Pixel pitch	0.2331 x 0.2331 mm	European Product Registry for Energy Labelling (EPREL) code	1258715
Pixel density	108.79 ppi	Operational conditions	
Horizontal scan range	30 - 114 kHz	Operating temperature (T-T)	0 - 40 °C
Vertical scan range	48 - 75 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal	59.7 cm	Operating relative humidity (H-H)	20 - 80%
Viewable size, vertical	33.6 cm	Operating altitude	0 - 3658 m
Display diagonal (metric)	68.6 cm	Non-operating altitude	3658 - 12192 m
DDC/CI	✓		
Haze rate	25%		
Surface hardness	3H		

Display		Weight & dimensions	
Colour gamut standard	sRGB	Width (with stand)	614 mm
Display sRGB	✓	Depth (with stand)	231 mm
Performance		Height (with stand)	458 mm
NVIDIA G-SYNC *	✗	Weight (with stand)	4.06 kg
AMD FreeSync *	✗	Width (without stand)	614 mm
VESA Adaptive Sync support	✓	Depth (without stand)	53 mm
Component video sync	Separate sync	Height (without stand)	367 mm
Flicker-free technology	✓	Weight (without stand)	3.61 kg
Low Blue Light technology	✓	Packaging data	
Multimedia		Package width	730 mm
Number of speakers	2	Package depth	141 mm
RMS rated power	4 W	Package height	453 mm
Built-in speaker(s) *	✓	Package weight	6.45 kg
Built-in camera *	✗	Packaging content	
Design		Stand included	✓
Market positioning *	Home	Cables included	HDMI, AC
Product colour *	Black	Manual	✓
Ports & interfaces		Sustainability	
Built-in USB hub *	✗	Sustainability compliance	✓
HDMI *	✓	Doesn't contain	Mercury, PVC/BFR
HDMI ports quantity	2	Other features	
HDMI version	1.4	Compatible operating systems	Mac OS X Windows 11 / 10 / 8.1 / 8 / 7
DisplayPorts quantity	1	Exterior finish type	Textured
DisplayPort version	1.2	Picture enhancement	SmartImage
Audio output	✓	Recyclable packaging material	100%
HDCP	✓	Regulatory Approvals	CB; FCC Class B; ICES-003; CE Mark; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
HDCP version	1.4	EasyRead mode	✓
Ergonomics		LowBlue mode	✓
VESA mounting *	✓	Compliance certificates	RoHS
Panel mounting interface	100 x 100 mm	Mean time between failures (MTBF)	50000 h
Cable lock slot *	✓		
Cable lock slot type	Kensington		
Height adjustment *	✗		



8712581795108

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date