## GIGABYTE B650M GAMING PLUS WIFI Motherboard - AMD Ryzen 9000 CPUs, 5+2+2 Phases VRM, up to 8000MHz DDR5, 2xPCle 4.0 M.2, 2.5GbE LAN, WIFI 6E, USB 3.2 Gen 1

Brand: GIGABYTE Product code: B650M GAMING PLUS

**Product name :** B650M GAMING PLUS WIFI Motherboard - AMD Ryzen 9000 CPUs, 5+2+2 Phases VRM, up to 8000MHz DDR5, 2xPCIe 4.0 M.2, 2.5GbE LAN, WIFI 6E, USB 3.2 Gen 1

B650M GAMING PLUS WIFI Motherboard - AMD Ryzen 9000 CPUs, 5+2+2 Phases VRM, up to 8000MHz DDR5, 2xPCIe 4.0 M.2, 2.5GbE LAN, WIFI 6E, USB 3.2 Gen 1

GIGABYTE B650M GAMING PLUS WIFI Motherboard - AMD Ryzen 9000 CPUs, 5+2+2 Phases VRM, up to 8000MHz DDR5, 2xPCIe 4.0 M.2, 2.5GbE LAN, WIFI 6E, USB 3.2 Gen 1:

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge





| Processor   |   | Network   |   |
|---|---|---|---|
| Processor manufacturer * Processor socket *   | AMD Socket AM5 AMD Ryzen 7000 Series, AMD Ryzen     | Ethernet LAN Ethernet interface type LAN controller   | ✓ 2.5 Gigabit Ethernet Realtek RTL8125  |
| Compatible processor series *   | 8000 Series, AMD Ryzen 9000<br>Series               | Wi-Fi *   | <b>✓</b>  |
| Supported processor sockets   | Socket AM5  | Top Wi-Fi standard  | Wi-Fi 6E (802.11ax)   |
| Memory Supported memory types * DDR5-SDRAM Number of memory slots * 4   |   | Wi-Fi standards   | 802.11a, 802.11b, 802.11g, Wi-Fi 4<br>(802.11n), Wi-Fi 5 (802.11ac), Wi-Fi<br>6 (802.11ax), Wi-Fi 6E (802.11ax) |
| Memory slots type DIMM Memory channels Dual-channel   |   | WLAN controller model   | Realtek RTL8852CE   |
| ECC compatibility Non-ECC 8000 7800 760   | 0,7200,7000,6800,6600,6400,6200,6000,5600,5200,4800 | Bluetooth   | <b>✓</b>  |
| Supported memory clock speeds  Supported memory clock speed  Supported memory clock speed   | ,,,,  | Bluetooth version   | 5.3   |
| (max) 8000 MH2  |   | Features  |   |
| Maximum internal memory * 256 GB Unbuffered memory ✓  |   | Motherboard chipset *   | AMD B650  |
| Maximum internal memory per slot 64 GB  |   | Audio chip  | Realtek ALC897  |
| Storage controllers   |   | Audio output channels *   | 7.1 channels  |
| Supported storage drive types<br>Supported storage drive interfaces<br>Number of HDDs supported<br>Number of storage drives supporte<br>RAID support<br>RAID levels | 4   | Product colour PC health monitoring Component for * Motherboard form factor * Motherboard chipset family * Cooling type Power source type | Dark brown Fan, Temperature, Voltage PC micro ATX AMD Passive ATX   |
| Graphics  |   | Windows operating systems   | Windows 10 x64, Windows 11 x64  |
| Parallel processing technology support *  | Not supported                                       | supported  Expansion slots  | WINDOWS 10 X04, WINDOWS 11 X04  |
| Maximum resolution HDCP DirectX version   | 4096 x 2160 pixels  ✓ 12.0                          | PCI Express x1 (Gen 3.x) slots PCI Express x16 (Gen 4.x) slots Number of M.2 (M) slots  | 1<br>1<br>2   |

| Internal I/O  |          | Expansion slots   |   |
|---|----------|---|---|
| •   | 2        | •   | 2500  |
| USB 2.0 connectors * USB 3.2 Gen 1 (3.1 Gen 1) connectors * | 2        | 1st M.2 largest key size 1st M.2 highest PCI Express generation | 2580<br>4.0   |
| Number of SATA III connectors *                             | 4        | 2nd M.2 largest key size  | 22110   |
| Front panel audio connector                                 | ·<br>•   | 2nd M.2 highest PCI Express                                     |   |
| Front panel connector                                       | <b>✓</b> | generation  | 4.0   |
| ATX Power connector (24-pin)                                | <b>✓</b> | BIOS  |   |
| CPU fan connector   | <b>/</b> | BIOS type *   | UEFI AMI  |
| Number of CPU fan connectors                                | 1        | BIOS memory size  | 256 Mbit  |
| Number of chassis fan connectors                            | 2        | ACPI version  | 5.0   |
| EPS power connector (8-pin)                                 | <b>✓</b> | Clear CMOS jumper   | <b>✓</b>  |
| Number of EPS power connectors (8-pin)                      | 1        | Desktop Management Interface (DMI) version                      | 2.7   |
| TPM connector   | <b>✓</b> | System Management BIOS (SMBIOS) version                         | 2.7   |
| RGB LED pin header  | <b>✓</b> | Logistics data  |   |
| Number of RGB LED pin headers                               | 3        | Products per shipping (inner) case                              | 1 pc(s)   |
| Rear panel I/O ports  |          | Battery   |   |
| USB 2.0 ports quantity *                                    | 2        | Battery weight  | 3 g   |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *           | 3        | Lithium weight per battery                                      | 0.07 g  |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C                            | 1        | Number of battery cells   | 1   |
| ports quantity * Ethernet LAN (RJ-45) ports *               | 1        | Battery technology  | Lithium-Manganese Dioxide<br>(LiMnO2)                                     |
| PS/2 ports quantity   | 1        | Battery type  | CR2032  |
| HDMI ports quantity *                                       | 1        | Packaging data  |   |
| HDMI version  | 2.1      | Package width   | 270 mm  |
| DisplayPorts quantity                                       | 2        | Package depth   | 268 mm  |
| DisplayPort version   | 1.4      | Package height  | 68 mm   |
| Headphone outputs   | 1        | Package weight  | 1.53 kg   |
| Line-in   | <b>V</b> | Weight & dimensions   |   |
| Microphone in   | <b>✓</b> | Width   | 244 mm  |
| WiFi-AP antenna jack  | 2        | Depth   | 244 mm  |
|   |          | Height  | 35 mm   |
|   |          | Packaging content   |   |
|   |          | Batteries included  | ✓   |
|   |          | Antenna included  | ✓   |
|   |          | Screws included   | <b>✓</b>  |
|   |          | Bundled software  | Norton® Internet Security (OEM version) LAN bandwidth management software |
|   |          | Other features  |   |
|   |          | Weight  | 1.44 kg   |
|   |          | Technical details   |   |
|   |          | Warranty period   | 3 year(s)   |



4719331862213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.