

Epson DS-410 Sheet-fed scanner 600 x 600 DPI A4 Black, White

Brand : Epson

Product code: B11B249401BY

Product name : DS-410



215.9 x 3048mm, 600x600DPI, CIS, 50 - 209 g/m², 297x152x154mm, 2.5kg  
Epson DS-410. Maximum scan size: 215.9 x 3048 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 10 bit. Scanner type: Sheet-fed scanner, Product colour: Black, White. Sensor type: CIS, Daily duty cycle (max): 3000 pages, Scan file formats: BMP, JPG, PDF, PNG, TIFF. Standard input capacity: 50 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Post Card(JPN), ISO A-series sizes (A0...A9): A4, A5, A6

Scanning		Ports & interfaces	
Maximum scan size *	215.9 x 3048 mm	USB version	2.0
Optical scanning resolution *	600 x 600 DPI	Standard interfaces	USB 2.0
Colour scanning	✓	Power	
Duplex scanning *	✓	Power supply type *	AC
Input colour depth	10 bit	Power consumption (off)	0.2 W
Output colour depth	8 bit	AC input frequency	50 - 60 Hz
ADF scan speed (b/w, A4)	26 ppm	Input voltage	100 - 120 V
ADF scan speed (colour, A4)	26 ppm	Power supply	15 W
Design		Weight & dimensions	
Scanner type *	Sheet-fed scanner	Width	297 mm
Product colour *	Black, White	Depth	152 mm
Built-in display *	✗	Height	154 mm
Performance		Weight	2.5 kg
Sensor type *	CIS	Packaging content	
Scan file formats	BMP, JPG, PDF, PNG, TIFF	Cables included	AC, USB
Daily duty cycle (max) *	3000 pages	Bundled software	Document Capture Pro 2.0, Epson Scan 2
Scan drivers	ISIS, TWAIN, WIA	Sustainability	
Input capacity		Sustainability certificates	ENERGY STAR
Standard input capacity	50 sheets	System requirements	
Paper handling		Windows operating systems supported	✓
Scanning media types supported	Business Card, Post Card(JPN)	Mac operating systems supported	✓
Maximum ISO A-series paper size *	A4	Server operating systems supported	Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2
ISO A-series sizes (A0...A9)	A4, A5, A6	Operational conditions	
ISO B-series sizes (B0...B9)	B5, B6	Operating temperature (T-T)	5 - 35 °C
Letter	✓	Operating relative humidity (H-H)	15 - 80%
Legal	✓	Storage relative humidity (H-H)	15 - 85%
Auto Document Feeder (ADF) media weight	50 - 209 g/m²	Logistics data	
Ports & interfaces		Harmonized System (HS) code	84716070
USB port *	✓		



8715946638713

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date