



ATEN OL1500HV uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1500 W 8 AC outlet(s)

Brand : ATEN

Product code: OL1500HV

Product name : OL1500HV



Professional Online UPS

ATEN OL1500HV. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. AC outlet types: C14 coupler, IEC 320, Power plug: C13 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Width: 880 mm, Depth: 438 mm, Height: 410 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	10.3 min
Output power capacity *	1.5 kVA	Charging current	12 A
Output power *	1500 W	Hot-swap battery	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	110 V	Replacement battery cartridge	1
Input operation voltage (max) *	300 V	Design	
Input frequency *	40/70 Hz	Form factor *	Rackmount/Tower
Output frequency	50/60 Hz	Rack capacity	2U
Output voltage regulation	1%	Cable length	1.8 m
Maximum current	7.2 A	Cooling type	Active
Response time	0 ms	Built-in fan	✓
Efficiency	97%	Product colour *	Black
Input power factor	0.99	Display type	LCD
Output power factor	1	LED indicators	✓
Crest factor	3:1	Certification	CE
ECO mode	✓	Operational conditions	
Emergency Power Off (EPO)	✓	Operating temperature (T-T)	0 - 40 °C
Noise level	50 dB	Storage temperature (T-T)	-20 - 50 °C
Ports & interfaces		Operating relative humidity (H-H)	20 - 90%
AC outlet types	C14 coupler, IEC 320	Storage relative humidity (H-H)	10 - 95%
Power plug	C13 coupler	Technical details	
AC outlets quantity	8 AC outlet(s)	Compliance certificates	RoHS
USB port	✓	Weight & dimensions	
Serial interface	✓	Width	880 mm
Serial interface type	RS-232	Depth	438 mm
Emergency Power Off (EPO) connector	✓	Height	410 mm
		Weight	14.3 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit	✓
Battery capacity	9 Ah	Cables included	Power load cable, RS-232, USB cable
Battery voltage	12 V	Manual	✓
Number of batteries supported	3		
Typical backup time at full load	2.96 min		

Logistics data

Harmonized System (HS) code	85078000
-----------------------------	----------

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-DEC-2024. Prints or copies of Information are only valid on the printed Publication date