Brother TJ4005DN label printer Direct thermal 203 x 203 DPI 152 mm/sec Wired Ethernet LAN

Brand : Brother

Product code: TJ4005DNZU1

Product name : TJ4005DN

Direct thermal, 128 MB, USB, LAN, RS-232, 9.2 kg

Brother TJ4005DN label printer Direct thermal 203 x 203 DPI 152 mm/sec Wired Ethernet LAN:

The Brother TJ-4005DN industrial label printer offers performance you can rely on when keeping up with increasing demand.

The high-volume direct thermal label printer has been designed to ensure minimal downtime and maximum productivity through fast print speeds, large roll capacity and in-built durability.

With ZPL2 emulation compatibility and multiple connectivity options, the TJ-4005DN has been built with you in mind.

Brother TJ4005DN. Print technology: Direct thermal, Maximum resolution: 203 x 203 DPI, Print speed: 152 mm/sec. Connectivity technology: Wired. Product colour: Black





Print technology * Colour *Direct thermal XBuilt-in display Display *XMaximum resolution * Print speed * Maximum printing width *203 x 203 DPI 152 mm/sec 152 mm/sec 152 mm/secControl typeButtonsPaper handlingVindows 10.7 cmWindows operating systems supportedWindows 10. Windows 8.1 Statem requirementsMaximum label width Maximum media length 25.4 m12 cm 25.4 mMac OS X 10.13 High Sierra, Mac O X 10.14 Mojave, Mac OS X 10.2 Jaguar, Ma OS X 10.2 Jaguar, Mac OS X 10.5 Calalina, Mac OS X 10.2 Jaguar, Mac OS X 10.5 Calalina, Mac OS X 10.5 Leopard, Mac OS X 10.5 Leopard, Mac OS X 10.5 Sichera Connectivity technology *WiredEthernet LAN * Wi-Fi * USB port *ViredMac operating systems supportedWindows Server 2012 R2, Windows Server operating systems supportedPerformance Ilash memory Ilash memory128 MB 128 MB 25.1 LOMARAR (NW-7), Code 11, Code 128 (AB/C), Code 49, Code 93, Deutsche Post Lietcode, EAN128, EAN13, EAN14, EAN8, IT-14, Interleaved 25.1, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMacib 4 dimensionsWainbt 6 dimensionsUsing systems supported viet set distribution of 1.2. Android 5.1. Android 5.1. Android 5.1. Android 5.1. Android 5.1. Android 5.1. Android 5.1. Android 5.2. Android 5.2. Jobanars, MSI, POSTNET, TELEPEN, UPC-A, UPC-ELinux operating systems supported viet set distribution of 1.2. Stat, Sis, POS 1.2. Sis 3.3. Sis 3.3. Sis 2.3. Sis 3.3. S				
Colour *XDisplay *XMaximum resolution *203 x 203 DPIControl typeButtonsPrint speed *152 mm/secSystem requirementsSystem requirementsMaximum printing width *10.7 cmSystem requirementsWindows operating systemsWindows 10, Windows 8.1Paper handling25.4 mMaximum media length25.4 mMac OS X 10.13 High Sierra, Mac OS X 10.10, Patton S 10.5 Sierra, Mac OS X 10.10, Patton S 10.5 Sierra, Mac OS X 10.10, Patton S 10.5 Sierra, Mac OS X 10.10, Patton Mac OS X	Printing		Design	
Maximum resolution *203 x 203 DPlControl typeButtonsMaximum printing width *152 mm/secSystem requirementsSystem requirementsMaximum printing width *10.7 cmWindows operating systems supportedWindows 10, Windows 8.1Paper handling22 cmSupportedMac OS X 10.13 High Sierra, Mac OMaximum label width12 cmAmaco S X 10.2 Jaguar, Mac OS X 10.13 Migh Sierra, Mac OMaximum media length25.4 mMac operating systems supportedMac OS X 10.13 High Sierra, Mac OPorts & interfacesVinedMac operating systems supportedControl typeMac OS X 10.13 High Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.13 Migh Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.13 Migh Sierra, Mac OS X 10.10 Marci Mac OS X 10.10 Mac OS X 10.13 Migh Sierra, Mac OS	Print technology *	Direct thermal	Built-in display	×
Print speed*152 mm/secSystem requirementsMaximum printing width *10.7 cmWindows operating systemsWindows 10, Windows 8.1Paper handling25.4 mSupportedMax OS X 10.13 High Sierra, Mac O X 10.14 High sierra, Mac OS X 10.2 Jaguar, Mac OS X 10.2 Jaguar, Mac OS X 10.2 Marcor S X 10.2 Jaguar, Mac OS X 10.2 Marcor S X 10.2 Marc	Colour *	×	Display *	×
Maximum printing width*10.7 cmSystem requirementsPaper handlingWindows operating systems supportedWindows 10, Windows 8.1Maximum label width12 cmMac OS X 10.13 High Sierra, Mac O X 10.14 Mojave, Mac OS X 10.23 Catalina, Mac OS X 10.2 Jaguar, Ma OS X 10.2 Panter, Mac OS X 10.2 Siguar, Ma OS X 10.2 Panter, Mac OS X 10.2 Siguar, Ma OS X 10.3 Panther, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.9 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.9 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.9 Nowericks, Mac OS X 10.0 Snow Leopard, Mac OS X 10.0 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.9 Nowericks, Mac OS X 10.0 Snow Leopard, Mac OS X 10.0 Now OS X 10.9 Nowericks, Mac OS X 10.0 Snow Leopard, Mac OS X 10.0 Now OS X 10.9 Nowericks, Mac OS X 10.0 Snow Leopard, Mac OS X 10.0 Now OS X 10.9 Nowericks, Mac OS X 10.0 Now OS X 10.9 Nowericks, Mac OS X 10.0 Now OS X 10.9 Nowericks, Mac OS X 10.0 Now OS X 10.	Maximum resolution *	203 x 203 DPI	Control type	Buttons
Paper handlingsupportedwindows 10, Windows 8.1Maximum label width12 cmMac OS X 10.13 High Sierra, Mac OS X 10.15 AMaximum media length25.4 mMac OS X 10.13 High Sierra, Mac OS X 10.15 APorts & interfacesWiredMac operating systems supportedSo S X 10.3 Panther, Mac OS X 10.5 Now Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Now Leopard, Mac OS X 10.5 Now Server 2012 Row Server 2016PerformanceVNow 128 MB CODABAR (NW-7), Code 11, Code 128 (AB/C), Code 49, Code 93, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, ITT-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, ELEEPEN, UPC-A, UPC-ENobile operating systems supported Android 5.1, Android 5.0, Android 5.1, Android 5.0, Android 5.0, S 14.5, IOS 9.0, IOS 9.1,	1		System requirements	
Maximum media length25.4 mX 10.14 Mojave, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Ma OS X 10.3 Panther, Mac OS X 10.5 Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Now Leopard, Mac OS X 10.5 Now Leopard, Mac OS X 10.5 Now Leopard, Mac OS X 10.5 Panther, Mac OS X 10.5 Now Leopard, Mac OS X 10.5 Now Now Server 2012 R2, Windows Server 2016Performance128 MB Nobile operating systems supported 128 (A/B/C), Code 49, Code 93, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved 125, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMobile operating systems supported Android 5.1, Android 5.1, Android 5.9, Android 5.9, Android 5.9, Android 5.	Paper handling			Windows 10, Windows 8.1
Connectivity technology *WiredLeopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 10.0 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 VenturaWi-Fi *××Image Surver operating systems supportedLeopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 VenturaVB port *××Image Surver operating systems supportedLeopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 VenturaPerformanceImage Internal memoryI28 MB 128 MB (CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 49, Code 93, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN14, FAN8, ITF-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMobile operating systems supported (OS 12, iOS 13, iOS 13.4, iOS 14, iOS 12, iOS 13, iOS 13.4, iOS 14, iOS 12, iOS 9.0, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3DesignProduct colour *BlackWeight & dimensions				Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac
Connectivity technology*WiredMac operating systems supportedLeopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Movericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Mountain Lion, Mac OS X 10.9 Movericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Mountain Lion, Mac OS X 10.9 Movericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Mountain Lion, Mac OS X 13.0 VenturaWiFeir××WifedWindows Server 2012 R2, Windows Server 2012 R2, Windows Server 2016Performance128 MBServer operating systems supportedMindorid 10.0, Android 1.0, Android 1.0, Android 1.0, Android 5.1, Android 1.1, Android 7.1, Android 7.	Ports & interfaces			
Lince DataImage: Construct Data10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 VenturaWi-Fi*×Server Operating systems supportedWindows Server 2012 R2, Windows Server 2016Performance128 MBAndroid 12.0, Android 10.0, Android 11.0, Android 12.0, Android 5.0, Android 5.1, Android 5.0, Android 5.0, Android 5.1, Android 6.0, Android 5.0, Android 5.1, Android 6.0, Android 5.0, Android 5.1, Android 7.1, 2, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 49, Code 93, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN114, EAN8, ITF-14, Inteleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMobile operating systems supported systems supportedAndroid 8.0, Android 8.1, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 14.5, iOS 9.3, iOS 13.4, iOS 14.4, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 14.5, iOS 9.3, iOS 9.3, iOS 9.3, iOS 9.1, iOS 9.2, iOS 14.5, iOS 9.3, iOS 9.4, iOS 14.5, iOS 9.4, iOS 14.5, iOS 9.4, iOS 14.5, iOS 9.4, iOS 9.4, iOS 14.5, iOS 9.3, iOS 9.4, iOS 9.	Connectivity technology *	Wired		
Wi-Fi *XSur, Mac OS X 12.0 Monterey, Mac OS X 13.0 VenturaUSB port *RS-232 ports1PerformanceInternal memory128 MBFlash memory128 MBCODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 49, Code 93, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMobile operating systems supported Android 8.0, Android 8.1, Android 9.0, iOS 12.0, iOS 9.1, iOS 9.2, iOS 9.3, iOS 9.3, iOS 9.3, iOS 9.3, iOS 9.4,	Ethernet LAN *	1		OS X 10.8 Mountain Lion, Mac OS X
NoteVWindows Server 2012 R2, Windows Server 2012 R2, Windows Server 2016RS-232 ports1Server operating systems supportedWindows Server 2012 R2, Windows Server 2016Performance128 MBAndroid 10, Android 10, Android 10, Android 10, Android 10, Android 5.0, Android 5.1, Android 5.0, Android 5.1, Android 5.0, Android 5.1, Android 7.1, Android 7.0, Android 7.1, Android 7.1, Android 7.0, Android 8.1, Android 9.0, iOS 12.0, iOS 13.0, iOS 11.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 13.4, iOS 14, iOS 14, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3Built-in barcodesPost Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-ELinux operating systems supportedPostuct colour *BlackWidth248 mmProduct colour *BlackWidth248 mmDepth436 mm36 mm	Wi-Fi *	×		
PerformanceServer operating systems supportedServer 2016Internal memory128 MBAndroid 10, Android 10, Android 5.0, Android 5.1, Android 5.0, Android 5.1, Android 5.0, Android 5.1, Android 7.1, Android 7.2, Android 8.0, Android 8.1, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.1, iOS 9.3, iOS	USB port *	1		
PerformanceAndroid 10, Android 10.0, Android 10	RS-232 ports	1	Server operating systems supported	
Internal memory126 MbAndroid 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android 7.1, Android 7.1.2, Android 8.0, Android 8.1, Android 9.0, IOS 10.0, IOS 11.0, IOS 11.4, IOS 12, IOS 13, IOS 13.4, IOS 14, IOS 14.5, IOS 9.0, IOS 9.1, IOS 9.2, IOS 9.3Built-in barcodesPost Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMobile operating systems supported ICS 14.5, IOS 9.0, IOS 9.1, IOS 9.2, IOS 9.3Android 5.1, Android 6.0, Android 9.0, IOS 10.0, IOS 11.4, IOS 12, IOS 13, IOS 13.4, IOS 14, IOS 14.5, IOS 9.0, IOS 9.1, IOS 9.2, IOS 9.3DesignWeight & dimensionsProduct colour *BlackWidth Depth248 mm 436 mm	Performance			Android 10, Android 10.0, Android
Flash memory128 MB7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 8.1, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 13.4, iOS 14, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3Built-in barcodesPost Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-EMobile operating systems supported iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3Android 8.0, Android 7.1.2, Android 8.1, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3DesignWeight & dimensionsProduct colour *BlackWidth Depth248 mm 436 mm	Internal memory	128 MB		
128 (A/B/C), Code 49, Code 93, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved 2/5, LOGMARS, MSI, POSTNET, TELEPEN, UPC-A, UPC-E9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 13.4, iOS 14, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3DesignWeight & dimensionsProduct colour *BlackBlackWidth Depth248 mm 248 mmContent of the sector of the	Flash memory	128 MB		7.0, Android 7.1, Android 7.1.2,
Design Weight & dimensions Product colour * Black	Built-in barcodes	128 (A/B/C), Code 49, Code 93, Deutsche Post Identcode, Deutsche Post Leitcode, EAN128, EAN13, EAN14, EAN8, ITF-14, Interleaved	Mobile operating systems supported	9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 13.4, iOS 14, iOS 14.5, iOS 9.0, iOS 9.1, iOS 9.2,
Design Width 248 mm Product colour * Black Depth 436 mm			Linux operating systems supported	✓
Product colour * Black Width 248 mm Depth 436 mm	Design		Weight & dimensions	
Depth 436 mm	•	Black	Width	248 mm
Height 274 mm			•	
			Height	274 mm

Weight & dimensions	
Weight	9.2 kg
Packaging content	
Cables included	AC, USB



5023821215373

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.