




## ATEN 10G Single-Mode/10KM Fiber SFP+ Module

**Brand :** ATEN

**Product code:** 2A-142G

**Product name :** 10G Single-Mode/10KM Fiber SFP+ Module



- Extend your network connectivity up to 10 kilometers
  - Compliant with IEEE 802.3ae standards
  - Compliant with SFF-8431 MSA Digital Diagnostic Monitor (DDM)
  - Hot pluggable
  - Low power consumption
  - Operation Temperature from 0° C to 70° C
  - RoHS compliant
- 10G Single-Mode/10KM Fiber SFP Module

### ATEN 10G Single-Mode/10KM Fiber SFP+ Module:

The 2A-142G 10G Single-Mode/10KM Fiber SFP+ Module is designed for use in 10GbE Ethernet environment that allows you to connect a single-mode Gigabit Ethernet network cable to a network switch's SFP+ port. The 2A-142G provides 10GbE connectivity at distances up to 10 kilometers. As a hotpluggable module with a standard duplex connector for fiber communications, the 2A-142G works with single-mode-fiber (SMF) connections and operates at a nominal wavelength of 1310 nm. This makes the module a cost-effective and highperformance transceiver to significantly increase the span of a compatible network switch.

Performance		Weight & dimensions	
SFP transceiver type *	Fiber optic	Height	13 mm
Maximum data transfer rate *	10000 Mbit/s	Weight	44 g
Interface type *	SFP+	Packaging content	
Single-mode fiber (SMF) supported	✓	Quantity per pack	2 pc(s)
Networking standards	IEEE 802.3ae	Packaging data	
Digital Diagnostics Monitoring (DDM)	✓	Package width	42 mm
Features		Package depth	124 mm
Product colour	Stainless steel	Package height	129 mm
Hot-Plug support	✓	Package weight	80 g
Certificates		Logistics data	
Compliance certificates	RoHS	Master (outer) case net weight	440 g
Certification	RoHS	Master (outer) case width	237 mm
Operational conditions		Master (outer) case length	288 mm
Operating temperature (T-T)	0 - 70 °C	Harmonized System (HS) code	85369010
Storage temperature (T-T)	-40 - 85 °C	Master (outer) case height	157 mm
Weight & dimensions		Master (outer) case gross weight	1.27 kg
Width	14.6 mm	Products per master (outer) case	10 pc(s)
Depth	55.9 mm		



4719264649714



0672792011467



672792011467

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.