EPSON

Epson EB-1485Fi data projector Ultra short throw projector 5000 ANSI lumens 3LCD 1080p (1920x1080) White

Brand : Epson

Product name : EB-1485Fi

Product code: V11H919041

- Flexible display options and sizes: Cater for user needs in any working environment
- All-in-one interactive meeting display: Combines multiple resources in one interactive collaboration device
- Increase productivity & agile working: Share and display content from a range of devices simultaneously
- Sliding split screen: Up to four displays in one image - project images from different sources
- Easy installation: Quick set-up with auto-adjusting calibration function

EB-1485Fi, 3LCD, 5000 lum, 1920x1080, 16:9, 10 Bits, USB 2.0, RS-232C, RJ-45, Wi-Fi, VGA, HDMI, HDBaseT, AC 220-240 V, 458x375x210 mm

Projector

Screen size compatibility *	1651 - 3048 mm (65 - 120")
Projection distance	0.4 - 0.4 m
Projection distance (wide)	0.6 - 0.6 m
Projector brightness *	5000 ANSI lumens
Projection technology *	3LCD
Projector native resolution *	1080p (1920x1080)
Contrast ratio (typical) *	2500000:1
Native aspect ratio *	16:9
Number of colours	1.073 billion colours
Projector brightness (economic mode)	3500 ANSI lumens
Keystone correction, horizontal	-3 - 3°
Keystone correction, vertical	-3 - 3°
Heat dissipation	1244 BTU/h

Light source

Light source type *	Laser
Service life of light source *	20000 h
Service life of light source (economic mode)	30000 h

Lens system

Focus *	Manual
Fixed focal length	39 mm
Aperture range (F-F)	1.5 - 1.5
Zoom capability	✔
Zoom type	Auto
Zoom ratio	1.35:1

Video

Full HD *	✔
3D *	✘
Supported graphics resolutions	1920 x 1080 (HD 1080)
Supported video modes	1080p
Video colour modes	Blackboard, Cinema, Dynamic, Presentation, sRGB
Adjustable colour temperature	✔

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✔
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Miracast	✔

Storage

Card reader integrated *	✘

Features

Noise level (economic mode)	28 dB
On Screen Display (OSD)	✔
Screen mirroring	✔
Noise level *	37 dB
Air filter	✔
Composite sync	✔
Country of origin	China
Password protection	✔
Compatible operating systems	Linux, Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Ubuntu 14.10, Ubuntu 15.04

Multimedia

Built-in speaker(s) *	✔
RMS rated power	16 W

Design

Market positioning *	Presentation
Product type *	Ultra short throw projector
Product colour *	White
Placement	Wall
Cable lock slot	✔
Cable lock slot type	Kensington

Display

Built-in display *	✘

Ports & interfaces

HDMI connector type	Full-size
HDBaseT port	✔
USB 2.0 ports quantity	2
USB 2.0 Type-B ports quantity	2
Microphone in	✔
Serial interface type *	RS-232C
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	2
HDMI ports quantity *	3
Component video (YPbPr/YCbCr) in *	1
DVI port *	✘
DC-in jack	✔

Network

Smart TV *	✘

Power

Power source *	AC
Power consumption (typical) *	366 W
Power consumption (standby) *	0.5 W
Power consumption (economy mode)	262 W
AC input voltage	220 - 240 V
AC input frequency	50 - 60 Hz

Operational conditions

Storage temperature (T-T)	-10 - 60 °C

Weight & dimensions

Width	458 mm
Depth	210 mm
Height	375 mm
Weight *	9.3 kg
Package width	472 mm
Package depth	590 mm
Package height	640 mm
Package weight	27.7 kg

Packaging content

Remote control included *	✔
Manual	✔

Logistics data

Quantity per pack	1 pc(s)

8715946673752