



APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

Brand : APC

Product code: SRT1000RMXLI

Product name : Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit



Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit

APC Smart-UPS On-Line, 1000VA/1000W, Rackmount 2U, 230V, 6x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1000VA on-line 2U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14, BS1363A British and Schuko CEE 7/EU1-16P inputs, and 6x IEC 320 C13 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty.



| Features | | Design | |
|---------------------------------|----------------------------|------------------------------------|-----------------|
| UPS topology * | Double-conversion (Online) | Form factor * | Rackmount/Tower |
| Output power capacity * | 1 kVA | Cable length | 1.5 m |
| Output power * | 1000 W | Product colour * | Black |
| Waveform * | Sine | LED indicators | Status |
| Input operation voltage (min) * | 50 V | International Protection (IP) code | IP20 |
| Input operation voltage (max) * | 150 V | Certification | CE, EAC |
| Input frequency * | 40/70 Hz | Operational conditions | |
| Output operation voltage (min) | 220 V | Operating temperature (T-T) | 0 - 40 °C |
| Output operation voltage (max) | 240 V | Storage temperature (T-T) | -20 - 50 °C |
| Output frequency | 50/60 Hz | Operating relative humidity (H-H) | 0 - 95% |
| Surge energy rating | 432 J | Storage relative humidity (H-H) | 0 - 95% |
| Crest factor | 3:1 | Technical details | |
| Emergency Power Off (EPO) | ✓ | Sustainability certificates | Green Premium |
| Noise level | 50 dB | Compliance certificates | RoHS |
| Audible alarm(s) | ✓ | Weight & dimensions | |
| Ports & interfaces | | Width | 432 mm |
| USB port | ✓ | Depth | 505 mm |
| USB 2.0 ports quantity | 1 | Height | 85 mm |
| Serial interface | ✓ | Weight | 21 kg |
| Serial interface type | RJ-45 | Package width | 594 mm |
| SmartSlot | ✓ | Package depth | 749 mm |
| Battery | | Package height | 246 mm |
| Battery technology | Sealed Lead Acid (VRLA) | Package weight | 29.6 kg |
| Battery life (max) | 5 year(s) | Logistics data | |
| Battery recharge time | 3 h | Products per pallet | 12 pc(s) |
| Hot-swap battery | ✓ | Harmonized System (HS) code | 85078000 |



0731304340256



731304340256

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.