

## ASUS Dual -RTX4060TI-O16G-EVO NVIDIA GeForce RTX 4060 Ti 16 GB GDDR6

**Brand :** ASUS

**Product family:** Dual

**Product code:** 90YV0JH8-M0NA00

**Product name :** DUAL-RTX4060TI-O16G-EVO

- Powered by NVIDIA DLSS3, ultra-efficient Ada Lovelace arch, and full ray tracing
  - 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
  - 3rd Generation RT Cores: Up to 2x ray tracing performance
  - OC edition: Boost Clock 2595 MHz (OC Mode)/ 2565 MHz (Default Mode)
  - Axial-tech fan design features a smaller fan hub that facilitates longer blades and a barrier ring that increases downward air pressure
  - A 2.5-slot design maximizes compatibility and cooling efficiency for superior performance in small chassis
  - 0dB technology lets you enjoy light gaming in relative silence
  - Dual ball fan bearings can last up to twice as long as sleeve bearing designs
  - A protective backplate secures components during transportation and installation
  - Auto-Extreme technology uses automation to enhance reliability
- Dual GeForce RTX 4060 Ti EVO OC Edition 16GB GDDR6 with two powerful Axial-tech fans and a 2.5-slot design for broad compatibility



| Processor                                |                     | Performance                    |                 |
|--|---------------------|--------------------------------|-----------------|
| CUDA *                                   | ✓                   | OpenGL version *               | 4.6             |
| CUDA cores                               | 4352                | HDCP                           | ✓               |
| Graphics processor family *              | NVIDIA              | HDCP version                   | 2.3             |
| Graphics processor *                     | GeForce RTX 4060 Ti | Design                         |                 |
| Processor boost clock speed              | 2595 MHz            | Cooling type *                 | Active          |
| Processor frequency (OC mode)            | 2625 MHz            | Cooling technology             | ASUS Axial-tech |
| Maximum resolution *                     | 7680 x 4320 pixels  | Number of fans                 | 2 fan(s)        |
| Parallel processing technology support * | Not supported       | Number of slots                | 2.5             |
| Maximum displays per videocard           | 4                   | Product colour                 | Black           |
| Memory                                   |                     | Power                          |                 |
| Discrete graphics card memory *          | 16 GB               | Minimum system power supply *  | 650 W           |
| Graphics card memory type *              | GDDR6               | Supplementary power connectors | 1x 8-pin        |
| Memory bus *                             | 128 bit             | Weight & dimensions            |                 |
| Data transfer rate                       | 18 Gbit/s           | Weight                         | 669 g           |
| Ports & interfaces                       |                     | Length                         | 227.2 mm        |
| Interface type *                         | PCI Express 4.0     | Depth                          | 49.6 mm         |
| HDMI ports quantity *                    | 1                   | Height                         | 123.2 mm        |
| HDMI version                             | 2.1a                | Packaging data                 |                 |
| DisplayPorts quantity *                  | 3                   | Package width                  | 368 mm          |
| DisplayPort version                      | 1.4a                | Package depth                  | 220.5 mm        |
|  |                     | Package height                 | 68 mm           |
|  |                     | Package weight                 | 1.12 kg         |
|  |                     | Package type                   | Box             |
|  |                     | Packaging content              |                 |
|  |                     | Manual                         | ✓               |



4711387602812



0197105285767



197105285767



0197105602830



197105602830

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-DEC-2024. Prints or copies of Information are only valid on the printed Publication date