Sony SRG-A40 8.5 MP White 3840 x 2160 pixels 60 fps CMOS 25.4 / 2.5 mm (1 / 2.5")

Brand: Sony Product code: SRG-A40WC

Product name: SRG-A40

- High speed pan/tilt
- Wide angle zoom lens
- Powerful Zoom, wide angle
- PTZ Auto Framing
- Preset camera positions Picture Freeze Preset
- AF, AE and AWB
- PTZ Motion Sync
- Simple, flexible setup
- Single network cable
- HDMI/SDI outputs

SRG-A40 PTZ camera with PTZ Auto Framing

Sony SRG-A40. Megapixel (approx.): 8.5 MP, Sensor type: CMOS. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels, Maximum frame rate: 60 fps. Optical zoom: 30x. Product colour: White





HD type * 4K Ultra HD Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported H.264, H.265 3840 x 2160, 1920 x 1080 (HD Supported graphics resolutions Number of TV lines H.364 Wildows 10 Education x64, Windows 11 x64, Windows 10 Enterprise x64, Windows 10 Indicate the provided by t				
Megapixel (approx.)* 8.5 MP Ports & interfaces Sensor type CMOS HDMI ports quantity 1 Optical sensor size 25.4 / 2.5 mm (1 / 2.5") Ethernet LAN (RJ-45) ports 1 Zoom capability Y DC-in jack Y Optical zoom 30x 3G-SDI output Y Focal length range 4.4 - 88 mm Microphone in Y Horizontal field of view (wide) 70° Microphone in Y Minimum illumination 1.6 lx VISCA output ports 1 Flip & mirror Y VISCA input ports 1 Auto exposure Y Power AC, DC White balance Indoor, One push, Outdoor, Auto, Manual, Daylight DC input voltage 19.5 V Auto exposure Y Power consumption (typical) 80 W Light exposure modes Manual, Auto, Shutter priority AE Auto Manual Operational conditions Focus adjustment AutoManual Operational conditions V PTZ protocols Mort Power consumption (typical) 80 W Minimum working distance (wide) 8 cm Power supply included Y Maximum working distance (wide) 80 cm Cables included AC, HDMI Maximum vi	Camera		Design	
Sensor type CMOS HDMI ports quantity 1 Optical sensor size 25.4 / 2.5 mm (1 / 2.5") Ethernet LAN (RJ-45) ports 1 Coom capability	Camera type	Single camera	Pan speed (max)	300 °/sec
Optical sensor size 25.4 / 2.5 mm (1 / 2.5") Ethernet LAN (R]-45) ports 1 Domaphility 7 Optical zoom 30 x Optical zoom 4 - 88 mm Microphone in 70 wisch output ports 1 Indianami illumination 1.6 lx VISCA output ports 1 VISCA output ports 1 Indianami prome source type Act, DC Domaphi voltage 19.5 V Power source type Act, DC Domapt voltage 19.5 V Power consumption (typical) 80 W Uptotage 19.5 V Power consumption (typical) 80 W Operational conditions Operation	Megapixel (approx.) *	8.5 MP	Ports & interfaces	
Zoom capability Zoom c	· ·		HDMI ports quantity	1
Optical zoom 30x 5C-In jack 7 Focal length range 4.4 - 88 mm 4.4 - 88 mm Microphone in 70° Microphone	•	·	Ethernet LAN (RJ-45) ports	1
Focal length range	• •		DC-in jack	✓
Horizontal field of view (wide) Minimum illumination 1.6 lx VISCA output ports 1 VISCA input ports 1 1 Note in prover of the province of the p	•		3G-SDI output	✓
Minimum illumination 1.6 lx VISCA output ports 1 Flip & mirror	5 5		•	/
Filip & mirror Aperture range (F-F) Aperture range (F-F) Auto exposure Light exposure modes Manual, Auto, Shutter priority AE Focus adjustment Auto/Manual			·	1
Aperture range (F-F) Aperture range (F-F) White balance Indoor, One push, Outdoor, Auto, Manual, Daylight Auto exposure V Auto exposure Auto/Manual Gain control type Auto/Manual Gain control type Auto/Manual Gain control type TZ control VISCA Maximum working distance (wide) Slowest camera shutter speed Is Warranty card Fastest camera shutter speed I 1s Warranty card Fastest camera shutter speed I 4K Ultra HD Maximum video resolution* Maximum frame rate* Video formats supported H.264, H.265 Number of TV lines Number of TV lines Product colour* White Power source type AC, DC Power consumption (typical) 90 W 4C, DC 19.5 V AC, DC 90 W Power consumption (typical) 90 W Werr consumption (typical) 90 W Werranty card AC, HDMI Werranty card Werranty card Werranty card Werranty card Werranty card Werranty			' '	
White balance Indoor, One push, Outdoor, Auto, Manual, Daylight Development of the properties of the	'			
Manual, Daylight DC input voltage 19.5 V Auto exposure	Aperture range (F-F)			10.00
Auto exposure	White balance		· ·	
Light exposure modes Focus adjustment Auto/Manual Auto/Manual Operating temperature (T-T) Operating temperature (Auto exposure	✓	, ,	
Focus adjustment Gain control type Auto/Manual Operating temperature (T-T) Storage temperature (T-T) -20 - 60 °C PTZ control VISCA Packaging content Minimum working distance (wide) Minimum working distance (tele) 80 cm Slowest camera shutter speed 1 s Fastest camera shutter speed 1/10000 s Video Video Video Video Video Video AUto/Manual Operating temperature (T-T) -20 - 60 °C -20 - 60	Light exposure modes	Manual, Auto, Shutter priority AE		80 W
Storage temperature (T-T) -20 - 60 °C PTZ control VISCA Packaging content Windows 11 Enterprise x64, Windows 10 Enterprise, Windows 10 Ior Enterprise, Windows 10 Pro, Windows 10 Pro, Windows 11 Windows 10 Ked, Windows 11, Windows 11, Windows 11 Mindows 10 For Ced, Windows 11, W	Focus adjustment	Auto/Manual	Operational conditions	
PTZ protocols Minimum working distance (wide) Maximum working distance (tele) Mounting brackets included Mindows 11 Enterprise x64, Windows 10 Education, Windows 11 Pro, Windows 10 Education, Windows 11 Pro, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 Enterprise, X64, Windows 10 Home, Windows 10 Home x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro x64, Windows 10 Mindows 10 Pro x64, Windows 10 Notes and the properties of the	Gain control type	Auto/Manual		• .• •
Minimum working distance (wide) 8 cm Maximum working distance (tele) 80 cm Slowest camera shutter speed 1 s Fastest camera shutter speed 1/10000 s Video HD type * 4K Ultra HD Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported H.264, H.265 Supported graphics resolutions Number of TV lines Number of TV lines Minimum working distance (wide) 8 cm Power supply included AC, HDMI Warranty card ✓ Screws included ✓ Mounting brackets included ✓ System requirements Windows 11 Enterprise x64, Windows 10, Windows 11 Home, Windows 10 Education, Windows 11 Pro, Windows 10 Education, Windows 11 Pro, Windows 10 Education, Windows 10 Home, Windows 10 Pro, Windows 10 Pro, Windows 10 Pro, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 Pro x64, Windows 11 Enterprise Product colour * White Maximum working distance (tele) 80 cm Warranty card ✓ Worranty card ✓ Worranty card ✓ Screws included ✓ Mounting brackets included ✓ Windows 11 Enterprise x64, Windows 10, Windows 11 Enterprise, Windows 10 Education, X64, Windows 10 Home, Windows 10 Pro, X64, Windows 11 Enterprise	PTZ control	✓	Storage temperature (T-T)	-20 - 60 °C
Maximum working distance (tele) 80 cm Slowest camera shutter speed 1 s Fastest camera shutter speed 1/10000 s Video Warranty card ✓ Screws included ✓ Mounting brackets included ✓ Mounting brackets included ✓ Windows 11 Enterprise x64, Windows 10 Education, Windows 10 For Enterprise, Windows 10 Pro, Windows 11 Enterprise White Product colour * White Warranty card ✓ Windows included ✓ Windows 11 Enterprise x64, Windows 10 Education, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 Included ✓ Windows 10 For, Windows 11 Enterprise Windows 10 For, Windows 11, Windows 11 Enterprise Enterprise Windows 11, Windows 11 Enterprise X64, Windows 11 Enterprise X6	PTZ protocols	VISCA	Packaging content	
Slowest camera shutter speed 1 s Warranty card ✓ Fastest camera shutter speed 1/10000 s Screws included ✓ Video Mounting brackets included ✓ HD type * 4K Ultra HD Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported H.264, H.265 3840 x 2160, 1920 x 1080 (HD Supported graphics resolutions 1080), 640 x 360, 1280 x 720 (HD 720) Windows operating systems Supported TV lines 1700 Design Product colour * White Image stabilizer ✓ Warranty card ✓ Warranty card ✓ Warranty card ✓ Screws included ✓ Warranty card ✓ Screws included ✓ Windows 10uded ✓ Windows 11 Enterprise x64, Windows 10, Windows 10 Education, Windows 11 Enterprise, Windows 10 Enterprise x64, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 Foro, Windows 10 Foro, Windows 10 Foro, Windows 10 Pro x64, Windows 11 Enterprise Windows 10 Pro x64, Windows 11 Enterprise Windows 10 Pro x64, Windows 10 Pro x64, Windows 11 Enterprise Windows	Minimum working distance (wide)	8 cm	Power supply included	✓
Fastest camera shutter speed Video Video HD type * 4K Ultra HD Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported H.264, H.265 3840 x 2160, 1920 x 1080 (HD Supported graphics resolutions Number of TV lines 1700 Product colour * Inage stabilizer Video Video Varianty Card Screws included Varianty Card Varianty Cath Varianty Ca	Maximum working distance (tele)	80 cm	Cables included	AC, HDMI
Video HD type * 4K Ultra HD Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported H. 264, H. 265 Supported graphics resolutions Number of TV lines Product colour * White Image stabilizer Mounting brackets included ✓ Mounting brackets included ✓ Mounting brackets included ✓ System requirements System requirements Windows 11 Enterprise x64, Windows 10, Windows 11 Home, Windows 10 Education, Windows 10 Education, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 Included ✓ Windows 10 Education x64, Windows 10 Home, X64, Windows 10 Home, Windows	·		Warranty card	✓
HD type * 4K Ultra HD Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported H.264, H.265 3840 x 2160, 1920 x 1080 (HD Supported graphics resolutions Number of TV lines Product colour * Product colour * Windows 11 Enterprise x 64, Windows 10, Windows 11 Home, Windows 10 Education, Windows 11 Pro, Windows 10 Education x 64, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 Home,	Fastest camera shutter speed	1/10000 s	Screws included	✓
Maximum video resolution * 3840 x 2160 pixels Maximum frame rate * 60 fps Video formats supported Video formats supported H.264, H.265 3840 x 2160, 1920 x 1080 (HD Supported graphics resolutions Number of TV lines Number of TV lines Product colour * Windows 11 Enterprise x 64, Windows 10, Windows 11 Home, Windows 10 Education, Windows 11 Windows 10 Education x 64, Windows 10 Enterprise Supported Windows operating systems Supported Windows 10 Enterprise, Windows 10 Enterprise X64, Windows 10 Home, Windows 10 Home x 64, Windows 10 Home, Windows 10 Home x 64, Windows 10 Pro, Windows 10 Pro x 64, Windows 10 Pro x 64, Windows 11 Enterprise Windows 11 Enterprise Windows 11 Enterprise Windows 11 Enterprise	Video		Mounting brackets included	✓
Maximum rate * 60 fps Video formats supported H.264, H.265 Supported graphics resolutions 1080), 640 x 360, 1280 x 720 (HD 720) Number of TV lines 1700 Product colour * White Mindows 11 Enterprise x64, Windows 10, Windows 11 Home, Windows 10 Education, Windows 11 Fro, Windows 10 Enterprise x64, Windows 11 x64, Windows 10 Enterprise x64, Windows 11 x64, Windows 10 Enterprise x64, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 In Home x64, Windows 10 In Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 11 Enterprise Windows 11 Enterprise x64, Windows 11 Enterprise x64, Windows 10 Enterprise, Windows 10 In Home x64, Windows 10 In X64, Windows 10 In X64, Windows 11, Windows 11 Enterprise	,,		System requirements	
Video formats supported H.264, H.265 Supported graphics resolutions Number of TV lines Product colour * Windows 10, Windows 11 Home, Windows 10 Education, Windows 10 Enterprise windows 10 Enterprise (Windows 10 Enterprise) Windows 10 Education x64, Windows 10 Enterprise (Windows 10 Enterprise) Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 IoT (Windows 10 IoT) Enterprise, Windows 10 IoT (Windows 10 IoT) Enterprise, Windows 10 Pro, Windows 10 Pro, Windows 10 Pro x64, Windows 11 Enterprise Windows 10, Windows 11 Home, Windows 10 Enterprise, Windows 10 Enterprise, Windows 10 IoT (Windows 10 IoT) Enterprise Windows 10, Windows 11 Enterprise		'		Windows 11 Enterprise x64.
3840 x 2160, 1920 x 1080 (HD Supported graphics resolutions 1080), 640 x 360, 1280 x 720 (HD 720) Number of TV lines 1700 Product colour * White Windows operating systems supported Windows operating systems supported Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Home, Windows 10 Home, Windows 10 Home x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Home x6		•		Windows 10, Windows 11 Home,
Supported graphics resolutions 1080), 640 x 360, 1280 x 720 (HD 720) Number of TV lines 1700 Product colour * Image stabilizer 1080), 640 x 360, 1280 x 720 (HD 720) Windows operating systems supported Windows operating systems supported x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro, Windows 10 Pro x64, Windows 10 Pro x64, Windows 11 Enterprise	video formats supported			
Number of TV lines 1700 supported x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 Pro x64, Windows 11 Enterprise	Supported graphics resolutions	1080), 640 x 360, 1280 x 720 (HD		Windows 11 x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows
DesignEnterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 EnterpriseImage stabilizer✓Enterprise	Number of TV lines			
Product colour * White x64, Windows 11, Windows 11 Image stabilizer ✓ Enterprise	Design			Enterprise, Windows 10 Pro,
Image stabilizer ✓ Enterprise	Product colour *	White	·	
	Image stabilizer	✓		
	•	-20 - 90°		

Design		System requirements	
Pan range Tally light ✓ Tilt speed (min) 0.5 °/sec Tilt speed (max) 126 °/sec Pan speed (min) 0.5 °/sec	Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey	
	126 °/sec	Performance	
		Auto framing	✓
		Audio	
		Audio channels	2
		Audio codecs	AAC LC 256kbps/ST (IP), AAC LC 128kbps/ST(IP)
		Network	
		Multi-stream capability	3
		Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
		Bit rate range	512 - 50000 Kbit/s
		Supported network protocols	IPv4, IPv6, TCP, UDP, ARP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP/RTCP, RTSP, VISCA over IP, SRT
		Weight & dimensions	
		Width	156.7 mm
		Depth	200 mm
		Height	184 mm
		Weight	2 kg





5013493458635

4548736143371

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.