## StarTech.com Gigabit Ethernet Fiber Media Converter with Open SFP Slot

Brand : StarTech.com

Product code: ET91000SFP2

**Product name :** Gigabit Ethernet Fiber Media Converter with Open SFP Slot


StarTech.com Gigabit Ethernet Fiber Media Converter with Open SFP Slot - Fiber to Ethernet Converter - Gigabit Ethernet Media Converter

StarTech.com Gigabit Ethernet Fiber Media Converter with Open SFP Slot. Maximum data transfer rate: 1250 Mbit/s, Converter input interface: 1000Base-T, Converter output interface: 1000Base-LX, 1000Base-SX. Mean time between failures (MTBF): 65000 h. Product colour: Black, Housing material: Steel. Fiber optic connector: SFP, Connectivity technology: Wired. Input voltage: 100 - 240 V, Input current: 0.36 A, Output voltage: 12 V





Network		Power	
Maximum data transfer rate * Converter input interface	1250 Mbit/s 1000Base-T	Output current Power consumption (typical)	1 A 8 W
Converter output interface	1000Base-LX, 1000Base-SX	Power over Ethernet (PoE)	×
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z	External power adapter	✓
Ethernet interface type	Gigabit Ethernet	Weight & dimensions	
Ethernet LAN data rates	1000 Mbit/s	Width	95 mm
Auto MDI/MDI-X	<ul> <li>Image: A second s</li></ul>	Depth	160 mm
Duplex system	Full, Half	Height	20 mm
Performance		Weight	400 g
Mean time between failures (MTBF)	65000 h	Operational conditions	
Features		Operating temperature (T-T) Storage temperature (T-T)	0 - 60 °C -10 - 70 °C
Internal *	×	Operating relative humidity (H-H)	10 - 90%
LED indicators		Packaging content	
Product colour	Black	Manual	1
Housing material	Steel	Deckewing data	
Ports & interfaces		Packaging data	
Connectivity technology Ethernet LAN (RJ-45) ports Fiber ports quantity Fiber optic connector *	Wired 1 1 SFP	Package width Package depth Package height Package weight	137 mm 208 mm 92 mm 786 g
Power		Certificates	
Input voltage Input current	100 - 240 V 0.36 A	Compliance certificates Certification	RoHS FCC
Output voltage	12 V	Logistics data	
		Harmonized System (HS) code	85176990





065030852517

0065030852517



5054533529434

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.