

StarTech.com 4PORT-8K-HDMI-SWITCH video switch

Brand : StarTech.com

Product code: 4PORT-8K-HDMI-SWITCH

Product name : 4PORT-8K-HDMI-SWITCH

StarTech.com 4-Port 8K HDMI Switch, HDMI 2.1 Switcher 4K 120Hz HDR10+, 8K 60Hz UHD, HDMI Switch 4 In 1 Out, Auto/Manual Source Switching, Power Adapter and Remote Included
StarTech.com 4PORT-8K-HDMI-SWITCH. Video port type: HDMI, USB port type: Micro-USB. Material: Metal, Product colour: Black, Maximum operating distance: 5 m. AC input voltage: 100 - 240 V, AC adapter input current: 0.3 A, AC adapter output voltage: 5 V. Width: 61 mm, Depth: 136 mm, Height: 14 mm. Package width: 123 mm, Package depth: 179 mm, Package height: 50 mm



Ports & interfaces		Weight & dimensions	
Video port type *	HDMI	Width	61 mm
HDMI ports quantity	5	Depth	136 mm
HDMI version	2.1	Height	14 mm
HDMI in	4	Weight	150 g
Number of HDMI outputs	1	Packaging data	
USB port type	Micro-USB	Package width	123 mm
Features		Package depth	179 mm
Material	Metal	Package height	50 mm
Product colour	Black	Package weight	420 g
High Dynamic Range (HDR) supported	✓	Packaging content	
Plug and Play	✓	Mounting kit	✓
HDCP	✓	Quick start guide	✓
Maximum operating distance	5 m	Remote control included	✓
Supported graphics resolutions	1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1080, 2560 x 1440, 3440 x 1440, 4096 x 2160, 5120 x 1440, 7860 x 4320	Cables included	USB Type-A to Micro-USB Type-B
		AC adapter included	✓
Bandwidth	48 Gbit/s	Operational conditions	
LED indicators	✓	Operating temperature (T-T)	0 - 70 °C
External power adapter	✓	Storage temperature (T-T)	-10 - 80 °C
Audio output channels	7.1 channels	Operating relative humidity (H-H)	5 - 90%
Dolby technologies	DTS-HD Master Audio, DTS:X, Dolby Atmos, Dolby TrueHD	Sustainability	
HDCP version	2.3	Sustainability compliance	✓
Power		Technical details	
AC input voltage	100 - 240 V	Compliance certificates	CE, RoHS
AC adapter input current	0.3 A	Logistics data	
AC adapter output voltage	5 V	Master (outer) case width	400 mm

Power		Logistics data	
AC adapter output current	1 A	Master (outer) case length	550 mm
Power consumption (typical)	5 W	Master (outer) case height	280 mm
		Products per master (outer) case	40 pc(s)



0065030899420



065030899420

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-DEC-2024. Prints or copies of Information are only valid on the printed Publication date