



APC Smart-UPS On-Line, 1000VA, Rackmount 3U, 230V, 8x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

Brand : APC

Product code: SRTL1000RMXLI

Product name : Smart-UPS On-Line, 1000VA, Rackmount 3U, 230V, 8x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit, W/ Lithium-ion external battery



Smart-UPS On-Line, 1000VA, Rackmount 3U, 230V, 8x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

[APC Smart-UPS On-Line, 1000VA, Rackmount 3U, 230V, 8x C13 IEC outlets, SmartSlot, Extended runtime, W/ rail kit, W/ Lithium-ion external battery:](#)

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1000VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with IEC 320 C14 input and 8x IEC 320 C13 outlets. It has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features		Battery	
UPS topology *	Double-conversion (Online)	Automatic battery test	✓
Output power capacity *	1 kVA	Cold start	✓
Output power *	900 W	Design	
Waveform *	Sine	Form factor *	Rackmount
Input operation voltage (min) *	220 V	Rack capacity	3U
Input operation voltage (max) *	240 V	Product colour *	Black, Grey
Input frequency *	40/70 Hz	Display type	LCD
Output operation voltage (min)	220 V	LED indicators	Status
Output operation voltage (max)	240 V	International Protection (IP) code	IP20
Output frequency	50/60 Hz	Certification	CE, EAC, RCM, VDE
Surge energy rating	340 J	Operational conditions	
Crest factor	3:1	Operating temperature (T-T)	0 - 40 °C
Emergency Power Off (EPO)	✓	Storage temperature (T-T)	-20 - 50 °C
Noise level	50 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Auto-restart	✓	Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler	Sustainability certificates	Green Premium
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	8 AC outlet(s)	Width	432 mm
USB port	✓	Depth	590 mm
Serial interface	✓	Height	128 mm
Serial interface type	RJ-45	Weight	26.7 kg
Serial ports quantity	1	Package width	600 mm
SmartSlot	✓	Package depth	850 mm
Battery		Package height	445 mm
Battery technology	Lithium-Ion (Li-Ion)	Package weight	37.4 kg
Battery life (max)	10 year(s)	Logistics data	
Battery recharge time	6 h	Products per pallet	6 pc(s)
Hot-swap battery	✓	Harmonized System (HS) code	85078000

Other features

Output voltage	230 V
----------------	-------



0731304346388



731304346388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.