Philips B Line 245B1/00 LED display 60.5 cm (23.8") 2560 x 1440 pixels Quad HD Black

Brand : Philips

Product family: B Line

Product code: 245B1/00

Product name : 245B1/00

- 24" Quad HD IPS 2560 x 1440

- 75 Hz, 4 ms

- Anti-Glare

Business Monitor 245B1 LCD monitor with PowerSensor

Philips B Line 245B1/00 LED display 60.5 cm (23.8") 2560 x 1440 pixels Quad HD Black:

Get your best work done with this Philips monitor. Crystal-clear QHD gives the space and clarity for your work. Loaded with features to improve productivity and sustainability. Eye comfort features with TUV certified to reduce eye fatigue.

Philips B Line 245B1/00. Display diagonal: 60.5 cm (23.8"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Height adjustment	15 cm
Display resolution *	2560 x 1440 pixels	Pivot	1
HD type *	Quad HD	Pivot angle	-90 - 90°
Native aspect ratio *	16:9	Swivelling	 Image: A set of the set of the
Display technology *	LED	Swivel angle range	-180 - 180°
Panel type *	IPS	Tilt adjustment	1
Backlight type	W-LED	Tilt angle range	-5 - 35°
Touchscreen *	×	On Screen Display (OSD)	1
Display brightness (typical) Response time * Display surface Anti-glare screen Screen shape *	250 cd/m ² 4 ms Matt ✓ Flat	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Supported graphics resolutions	2560 x 1440	Number of OSD languages	21
Aspect ratio	16:9	Plug and Play	1
Contrast ratio (typical) *	1000:1	LED indicators	Operation, Stand-by
Contrast ratio (dynamic)	5000000:1	Power	
Dynamic contrast ratio marketing name	SmartContrast	Energy efficiency class (SDR) *	E
Maximum refresh rate * Viewing angle, horizontal	75 Hz 178°	Energy consumption (SDR) per 1000 hours *	17 kWh
Viewing angle, vertical	178°	Power consumption (typical) *	16.3 W
Display number of colours *	16.7 million colours	Power consumption (standby) *	0.3 W
Pixel pitch	0.2058 x 0.2058 mm	Power consumption (PowerSave)	13 W
Pixel density	123 ppi	AC input voltage	100 - 240 V
Horizontal scan range	30 - 114 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	48 - 75 Hz	Power supply type	Internal
Viewable size, horizontal	52.7 cm	Energy efficiency scale	A to G
Viewable size, vertical	29.6 cm	European Product Registry for Energy Labelling (EPREL) code	388603

DisplayOperationsOperationsDigital horizonts0 - 40 °CDigital voicants48 - 75 H2Storage maperature (T-7)-20 - 60 °CDigital voicants65 - 55 H2Storage maperature (T-7)-20 - 60 °CDOCIStorage material horizonts20 - 60 °CStorate hardness3HNon-operating altitudie0 - 213 StorageStorate hardness3HNon-operating altitudie0 - 213 StorageStorate hardness3HDept (with stand)20 FmStorate storage (kpical)116 %Dept (with stand)20 FmDisplay storageYWith (with cand)3.2 kgWIDLA GSYNC *XHardne (without stand)3.3 ronVSA Adaptice synce synceAckage width horizontand3.0 ronWIDLA GSYNC *XAckage width horizontand1.0 ronVSA Adaptice synce synceAckage width horizontand1.0 ronWIDLA GSYNC *XAckage width horizontand1.0 ronMulti Consol *XAckage width horizontand1.0 ronMulti Consol * <t< th=""><th></th><th></th><th>a</th><th></th></t<>			a	
Diplay diagonal (metric)40 - 58 / 40Sinage remeature (T-T)-0 - 60 ''Delphay diagonal (metric)60 - 60 ''20 - 80 ''20 - 80 ''DC/ClStarage nelative humiday (H-H)20 - 80 ''Bate rate25 ''Operating altisture humiday (H-H)20 - 80 ''Sufface hardness3HOperating altisture humiday (H-H)20 - 80 ''Color ganut standardSRGWeight C dimensions-Color ganut standardSRGWeight C dimensions50 mmSRG coverage (typice)150 ''Deph (with standard)50 mmSRG coverage (typice)9% ''Deph (with standard)51 mmStorewrage (typice)9% ''Deph (with standard)32 mmNDIA C-SYNC (Secorage typice)''Performate-''WOLDA C-SYNC (Secorage typice)Secorage typic (typice)32 mmMDIA C-SYNC (secorage typice)Secorage typic (typice)32 mmMODA C-SYNC (secorage typic (typice)Secorage typic (typice)32 mmMolto festigative sync (secorage typic (typice)Secorage typic (typice)32 mmMODA C-SYNC (secorage typic (typice)Secorage typic (typice)32 mmMODA C-SYNC (secorage typic (typice)Secorage typic (typice)32 mmMolto festigative sync (secorage typic (typice)Secorage	Display		Operational conditions	
Display diagonal (metric)0.6.3 cmOperating altitude0.6.0.8%DGCI25%Operating altitude0.8.0%Surface Hardnesso3HNon-operating altitude0.12182 rmColour ganut StandardSGBSGBSGBColour ganut StandardSGBSGBSGBColour ganut Standard9%With (with stand)505 nmSGB coverage (typica)9%Height K dimension505 nmSGB coverage (typica)9%Height K dimension307 nmPartomacoYaki (kith stand)3.1 nmSGBSGB coverage (typica)SSGBSGBSGB coverage (typica)SSGBSGBSGB coverage (typica)SSGBSGBSGB coverage (typica)SGBSGBSGBSGB coverage (typica)SGBSGB				
DCQC Issue and Issue and Issu			5 1 1	
Name29% Operation should0 - 3632 0 - 12122 0 - 121222 0 - 12122 0 - 121222 0 - 121222 0 - 121222 0 - 121222 0 - 1		60.5 cm		
Name of a part of a part of a part of a part of a dimension of a part	DDC/CI	1		
Colour ganut Golour ganut Singlik conseque (typical)Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singlik Singl	Haze rate	25%		
Calar gamt99%Wath (with stad)540 nmsRGB coverage (typical)16%Depth (with stad)205 nmNSC coverage (typical)99%Height (with stad)3.01 nmDisplay sRGBAWeight (with stad)3.78 ngPerformanceVield (without stad)5.1 nmSet on manual stateNDIDA CSTNC*XNeght (without stad)3.23 ngAMD FreeSync*XWeight (without stad)3.23 ngComponent video syncSeparate syncPeckage dight (without stad)3.23 ngFilcke-free technologyPeckage dight (without stad)3.23 ngWith video syncSeparate syncPeckage dight6.65 NgMultinedioPeckage dight (without stad)3.28 NgNumber of speakers2.9 NgOunanity per pack to a Set on S	Surface hardness	3H	Non-operating altitude	0 - 12192 m
968 coverage (typical)115%Mind (with stand)205 mmNTSC coverage (typical)99%Height (with stand)205 mmNTSC coverage (typical)99%Height (with stand)4.78 kgPerformanceWeight (with stand)4.78 kgNVDA CSYNC*XWeight (with stand)323 mmADD FreeSync*XWeight (with stand)323 mmADD FreeSync*XWeight (with stand)323 mmVESA Adaptive Sync supportSeparate syncPackage with (with stand)323 mm(Ekcer free technologyYPackage deight465 mm(Ekcer free technologyPackage height85 kgNumber of speares2Package weight635 kgNumber of speares2Package height85 kgBuilt-in cames2Package height85 kgBuilt-in cames2Package height85 kgBuilt-in cames2Package height85 kgBuilt-in cames2Package height85 kgProtocolout**Stand included4AProtocolout***BiackManualManualProtocolout***BiackManualManualProtocolout***BiackManualManualProtocolout****BiackManualManualProtocolout***********************************	Colour gamut standard	sRGB	Weight & dimensions	
NTSC coverage (typical)99%Depuis valueDepuis value	-	99%	Width (with stand)	540 mm
NTSC coverage (typical)99%High (with stand)51.mmDisplay SKGWeight (with stand)14.7m (aPerformanceWith (without stand)32.mmNUDA G-SYNC*XHeight (without stand)32.mmAMD FreeSync*XWeight (without stand)32.mmVESA Adaptice Sync supportPackage with stand)32.kmComponent video syncSeparate syncPackage with stand)600 mmFlicker-free technologyPackage with stand)600 mmWithin with stand)Separate syncPackage with stand)68.sk (aNumber of spackers2Package with yer pack68.sk (aNumber of spackers2Quantity per packbackage typeRVS rated poor2Quantity per packpackage with yer packRVS rated poor2Quantity per packpackage with yer packRVS rated poor8ackSand includedfrom totalProduct colourBlackBandle dottwaresmartControlProduct colourBlackBandle dottwarefrom totalProduct colourBlackBandle dottwarefrom totalStandbilty certificateVSTAR (TCOPackage with totalfrom totalStandbilty certificateSmartControlfrom totalfrom totalStandbilty certificateNorder totalfrom totalfrom totalStandbilty certificateSmartControlfrom totalfrom totalStandbilty certificateSmartControlfrom totalfrom t	5	116%	Depth (with stand)	205 mm
PerformanceWidd (without stand)540 nmNUDIA G.SYNC *XPeth (without stand)531 nmAMD FreeSync *XPeth (without stand)323 nmAMD SerSync *XHeight (without stand)32 logVESA Adaptive Sync supportYPackage with600 nmComponent video syncSeparate syncPackage with600 nmFilcer-free technologyYPackage with655 kgNuthier technologyYPackage weight635 kgNuther of speakers2Package weight635 kgNuther of speakers2Package weight1 pc(s)Builtin speaker(s)*YPackage weight635 kgNuther of speakers2Quantity per pack1 pc(s)Builtin speaker(s)*YStand included*Poduct colour*BlackStand included*Product colour*BlackBundle softwareSmartControlPotace locurBlackStaniability certificatesPecKoge ManZentrolBuiltin tiss hubXDestricatesPackage daging materialPotace softwareUS Type-8DestricatesSmartControlBuiltin USB hubXDestricatesPackage daging materialSubstanbility certificates16KertSmartmageBuiltin USB hubXCompleancementSmartmageSubstanbility certificatesSmartmageSmartmageBuiltin USB hubXCompleancementSmartmageSubstanbility certificatesS	NTSC coverage (typical)	99%		501 mm
PerformanceWitch without stand)54 mainNVDA 65YNC*XPeckpel (without stand)3.2 m mAMD FreeSync*XHeight (without stand)3.2 k gVESA Adaptite Sync supportVeckpel (without stand)3.2 k gComponent video syncSparate syncPeckage width600 mmLow Blue Light technologyPackage depth600 mmLow Blue Light technologyPackage height485 mmMuttinediaYPackage height485 mmNumber of speakers2 M Quantity perack1 pc(s)Builtin speaker(s)*2 MQuantity perack1 pc(s)Builtin speaker(s)*Sackage depth400, highlyPort, Audio (3.5 mm)Porduct colour*BlackManual*Product colour*BlackManual*Product colour*BlackManual*Product colour*BlackManual*Potabelic klusthareSatishability certificatesPKC/PFR, MercuryBuil:in USB hub**Satishability certificatesPKC/PFR, MercuryBuil:in USB hub**Satishability certificatesSmartlongoSubstraber of upstraam ports1 CSmartlongoSubstraam port typeUSB Type-ASmartlongoSubstraam port typeSatishability certificatesSmartlongoSubstraam port typeSatishability certificatesSmartlongoSubstraam port typeSatishability certificatesSmartlongoSubstraam port typeSatishability certificatesSmartlongoSu	Display sRGB	1	Weight (with stand)	4.78 kg
NULL SYNC-*KHeight (without stand)3.2 kmAND FreesyncKYeight (without stand)3.2 kgVESA Adaptive Sync supportSeparate syncPackage digth600 mmComponent Video syncSeparate syncPackage digth600 mmIcker-free technologyPackage digth455 mmPackage height455 mmIcker-free technologyPackage height455 kmPackage height6.85 kgNumber of speakersZQuantity per pack1 pc(s)Package height80xNumber of speakers)2Quantity per pack1 pc(s)Package heightMmBuilt-in camera **ZQuantity per pack1 pc(s)MmSingerBuilt-in speaker(s)*4Package heightMmSingerSingerPorduct colour *BlackManual<	Performance		Width (without stand)	540 mm
AND FreeSync×Height (without stand)3.2 kgmVESA Adaptive Sync syncSeparate syncPackage wildth3.2 kgmDirkber, free technologyPackage wildth60 mmLow Blue Light technologyPackage wildth198 mmDirkber, free technologyPackage wildth63 fsmMutheur Sync sub Sync Sync Sync Sync Sync Sync Sync Sync		v	Depth (without stand)	51 mm
VEAA day inverseWeight (without stand)3.2 kgComponent video syncSeparate syncPackage dayth600 mmPicker-free technologyPackage deyth199 mmLow Blue Light technologyPackage deyth6.85 kgNumber of speakers2Package type80xRMS rated power2Quantity per pack10 (s)Built-in speaker(s)*Package type80xRMS rated power2Quantity per pack10 (s)Built-in speaker(s)**Stand included10 (s)Product colorBlackStand included*Product colorBlackManual*Product colorBlackSustainability*Product colorBlackSustainability*Prot sk interfaces*Sustainability certificatesFNRCY STAR, TCOProt sk interfacesSustainability certificatesFNRCY STAR, TCONumber of upstream ports1Pacterior finish typeTexturedUSB upterem ports ype A downstream ports1Recyclable packaging materialSing FARCY Class B, ICES-003; CEDVI ports quantity1Recyclable packaging materialGB; EPA; FCC Class B, ICES-003; CECL_1 VV Ergo; TUV/GS; SENCO; CL_2 CL, VV Ergo; TUV/GS; SEN			Height (without stand)	323 mm
Component video syncSeparate syncPackage neightGolo maFlick-free technology<	,	×	Weight (without stand)	3.2 kg
Component voteo syncSeparate syncComponent voteo syncPackage width600 mmFicker-res textonologyPackage depth198 mmLow Blue Light technologyPackage depth198 mmMufferdiaPackage weight6.85 kgNumber of speakers2Quantity per pack1pc(s)Built-in speaker(s)*Package typeBoxBuilt-in speaker(s)*YPackaging content1pc(s)Built-in speaker(s)*YCables includedProduct colour*BlackManualYProduct colour*BlackMundel softwareSmartControlProduct colour*BlackManualYProduct colour*BlackSustainability certificatesPK/BFR, MarcuryBuilt-in USB hub*XSustainability certificatesPK/BFR, MarcuryBuilt-in USB hub*XSustainability certificatesPK/BFR, MarcuryBuilt-in USB hub*XSustainability certificatesSmartControlUSB type-A downstream ports1Exterior finish typeTexturedUSB Type-A downstream ports1Recyclable packaging material100%UVI portYRecyclable packaging material100%USB Type-A downstream ports1Exterior finish typeYUSB Type-A downstream ports1Exterior finish typeMarcuryUSB Type-A downstream ports1Exterior finish typeYUSB Type-A downstream port		4	Packaging data	
Increase technology*Package height198 mm Package height465 mmLow Blue Light Echnology*Package weight465 mmNumber of speakers2Package weight80xNumber of speakers2Vactage weightBoxBuilt-in speakers2Vactage meightBoxBuilt-in speakers*Vactage meightHoldBuilt-in speakers*Stand included*Built-in speakers*Stand included*Product colourBlackManual*Product colourBlackManual*Protact colourBlackBundled softwareSmartControlBuilt-in usbane*Sustainability certificatesENERGY STAR, TCOBuilt-in USB hub**Sustainability certificatesENERGY STAR, TCOBuilt-in USB hub**Sustainability certificatesENERGY STAR, TCOBuilt-in USB hub**Sustainability certificatesENERGY STAR, TCOSustainability certificates*Sustainability certificatesENERGY STAR, TCOSustainability certificates*Sustainability*Sustainability certificates*Sustainability*Sustainability certificates*Sustainability*Sustainability certificates*Sustainability*Sustainability certificates*Sustainability*Sustainability certificates*Sustainability*Sustainability certificates*		Separate sync		600 mm
Low Bie Light technologyPackage weight465 mmMuttimediaPackage weight6.85 kgNumber of speakers2 WQuantity per pack1 pc(s)RKS rated power2 WQuantity per pack1 pc(s)Built-in speaker(s)*Package weightMoM. DisplayPort, Audio (3.5mm)Built-in speaker(s)*Stadin includedProduct colour*BlackMunualProduct colour*BlackManualSmartControlProduct colour*BlackStatianbilityPetchable standYDesent containPVCJRFR, MercuryBuilt-in USB hub*XDesent containPVCJRFR, MercuryBuilt-in USB hub*XDesent containTexturedUSB type-BStatianbility certificatesTexturedTexturedUSB type-BStatianbilityTexturedSmartImageUV port/Segulatory ApprovalsCisi: FAP, FCC class B; ICES-003; CDVI port/Segulatory ApprovalsCisi: FAP, FCC class B; ICES-003; CDVI ports quantity1EasyRead modeIDMI ports quantity1EasyRead modeIDMI polyalyPort squantity1EasyRead modeAmountIDMI polyalyPort squantity1EasyRead modeIDMI ports quantity1EasyRead modeIDMI ports quantity1EasyRead modeIDMI ports quantity1EasyRead modeIDMI ports quantity <td>Flicker-free technology</td> <td>1</td> <td>5</td> <td></td>	Flicker-free technology	1	5	
<table-container>MumberPackage vight6.85 kgNumber of speakers2Package typeBoxNumber of speakers2Package typeBoxBMS rated power4Package typeBoxBuilsin speaker(s)*-Package typePackage typeBuilsin speaker(s)*XPackage typePackage typeBuilsin speaker(s)*XPackage typePackage typePowerBackManualCProduct colour *BackManualSecondardPort bezic colourBackBustability certificatesPackage typePort Sci functioneSustabilityPackage typePackage typePort Sci functioneSustabilityPackage typePackage typeBuilsin US hub*XPackage typePackage typeUS upstram port typeSi Type-BPackage typePackage typeSubinabilitySi Type-BPackage typePackage typeUS type-A downstream ports16Package typePackage typeUS type-A downstream portsSi Type-BPackage typePackage typeUS type-A downstream ports16Package typePackage typeUS type16Package typePackage type<td< td=""><td>Low Blue Light technology</td><td>✓</td><td>5</td><td></td></td<></table-container>	Low Blue Light technology	✓	5	
Number of speakers2Package typeBoxRMS rated power2 WQuantity per pack1 pc(s)Built-in speaker(s)**Package typeBoxBuilt-in speaker(s)*XStand included*DesignCables included*MDN, DisplayPort, Audio (3.5mm), ACProduct colour*BlackManual*Product colour*BlackManual*Product colour*BlackManual*Petachable stand*SustainabilitySmartControlPetachable stand*Sustainability certificatesNERGY STAR, TCO Posent containBuilt-in USB hub*XDesn't containPrefixedUSB upstream port typeUSB Type-BPicture enhancement Recyclable packaging materialSmartImage Recyclable packaging materialUV port**SmartImageQuantity1Heavy metals freeHg (mercury)HDMI version1.4Kegulatory Approvals*DisplayPort squantity1EasyRead mode*HDMI version1.4Compliance certificatesRoHsHDMI version1.4Compliance certificatesRoHsHDMI port squantity1LeasyRead mode*HDMI version1.4Compliance certificatesRoHsHDMI version1.4Compliance certificatesRoHsHDMI version1.4Compliance certificatesRoHsHDCP version1.4Compliance certificatesRoHsHDC	Multimedia			
RNS rated power2 WQuantity per pack1 pc(s)Built-in speaker(s)*Built-in speaker(s)*XStand includedBuilt-in speaker(s)*XCables includedMDM, DislayPort, Audio 3.5mm, ACPoduct colour *BlackManualProt to ezi colourBlackManualPetcolourBlackSustainability CertificatesENERGY STAR, TCOBuilt-in USB hub *Sustainability CertificatesENERGY STAR, TCOBuilt-in USB hub *XSustainability CertificatesENERGY STAR, TCOUSB upstream port typeUSB Type-BCertificatesSustainability CertificatesENERGY STAR, TCOUSB upstream port typeUSB Type-BCertificatesSmarttmageSmarttmageUSB type-A downstream ports1Exterior finish typeTexturedSmarttmageDVI-D ports quantityIRegulatory ApprovalsCertifiedSmarttmageUSB Type-A downstream portsIRegulatory ApprovalsCertifiedSmarttmageDVI-D ports quantityIHeavy metals freeHg (mercury) TW/GS; SEMKORDisplayPort versionI.2Compliance certificatesRHSHuddio inputXCompliance certificatesRHSHours point versionI.4Compliance certificatesRHSHours point versionI.4Compliance certificatesRHSHours point versionI.4CertificationCompliance certificatesDisplayPort versionI.4Certification<		2		5
Builtin speaker(s)*<Builtin camera *XStad includedBuiltin camera *XStad includedProduc colourBlackManualProduc colourBlackBandled softwareSmartControlProtub cel colourBlackBundled softwareSmartControlPetcolourBlackSustainability certificatesNerge SystemProtub cel colourBlackSustainability certificatesNerge SystemPorter factorSustainability certificatesNerge SystemBuiltin USB hub *XDecent containNerge SystemStatistip System AportsSta SystemSmartimageNumber of upstream portsSta SystemSmartimageVSB upstream portsStatistipSmartimageVI portSignerRecyclable packaging materialSmartimageVI portSignerStatistipStatistipVI ports quantity1Heavy metals freeHeavy metals freeHDM ports quantity1.4Lowella certificatesRHSNudo inputSignerCompliance certificatesRHSHDCPICompliance certificatesRHSHDCPICompliance certificatesRHSHDCPISignerSignerHDCPISignerSignerHDCPISignerSignerHDCPISignerSignerHDCPISignerSignerHDCPISignerSigner <td>•</td> <td></td> <td>5 71</td> <td></td>	•		5 71	
Built-in carea* X Stand included Image: Construction of the second o				1 pc(s)
DesignCables includedPDM, DisplayPort, Audio (3.5mm), ACProduct colour*BlackManualFront bezel colourBlackManualDetachable standSustainabilitySmartControlDetachable standSustainabilityPorts & interfacesSustainability certificatesENERGY STAR, TCO PVC/BFR, MercuryBuilt-in USB hub*XDoesn't containPVC/BFR, MercuryUSB upstream port typeUSB Type-BCther featuresSmartImage Recyclable packaging material100%USB upstream port typeUSB Type-A downstream ports5Recyclable packaging material100%DVI portRecyclable packaging material100%DVI portCB; EPA; FCC Class B; ICES-003; CE CLE; TUV Ergo; TUV/GS; SEMKO; CLE-AC; URRAINAN, CC; CECP; CEL; TUV Ergo; TUV/GS; SEMKO; CLE-AC; URRAINAN, CC; CECP; CLE; TUV Ergo; CURRAINCA; CLE; TUV Ergo; CURRAINCA; CLE; TUV Ergo; TUV/GS; SEMKO; CLE-AC; C	• • • •		Packaging content	
Product colour*BlackCables includedACFront bezel colourBlackManual/Detachable stand/Suntal Bundled softwareSmartControlPeter colourBlackSustainabilityPorts & interfacesSustainability certificatesENERGY STAR, TCOBuilt-in USB hub*XDesen't containPVC/BFR, MercuryUSB upstream port typeUSB Type-BCther featuresSmartImageNumber of upstream ports1Exterior finish typeTexturedUSB Type-A downstream ports5Recyclable packaging material100%DVI port//Cther enhancementSmartImageDVI port//Cther enhancementSmartImageDVI ports quantity1Heavy metals freeH (g mercury)HDMI version1.4Light sensor/DisplayPort version1.2LowBlue mode/Audio input1.4Compliance certificatesRoHSHDCP//CertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4Light sensor/HDCP version1.4Compliance certificatesRoHSHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4Compliance certificatesRoHSHoCP version1.4Compliance certificatesRoHSHoCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4C	Built-in camera *	×	Stand included	1
Product colourBlack Buck BuckManualImage ImageFront bezel colourBlackBundled softwareSmartControlDetachable standImageSustainabilityImageFeet colourBlackSustainability certificatesENERGY STAR, TCO Doesn't containBuilt-in USB hub *XOuesn't containPVC/BFR, MercuryBuilt-in USB hub *XSustainability certificatesENERGY STAR, TCOUSB upstream port typeUSB Type-BOther featuresTexturedUSB type-A downstream ports1Certification typeSmarttmageUSB type-A downstream portsSRecyclable packaging material Recyclable packaging material100%DVI-p ortImageRegulatory ApprovalsCB: EPA: FCC Class B: ICES-003; CE CU-EAC: UKRAINIAN; CCC: ECCP; CU-EAC: UV/SS: SENKO; CU-EAC: UKRAINIAN; CCC: ECCP; CEL: TUV Ego confort certifiedHDMI version14Light sensorImageHDMI version1.4Light sensorRevIsHDDPImageCompliance certificatesRoHSHDDPImageCompliance certificatesRoHSHDDPImageCompliance certificatesRoHSHDDP version1.4CertificationCompliance certificatesHDDP version1.4CertificationCompliance certificatesHDDP version1.4CertificationCompliance certificationHDDP version	Design		Cables included	
Front bezil colourBlackBundled softwareSmartControlDetachable standFeet colourBlackSustainability certificatesENERGY STAR, TCOPorts & interfacesDoesn't containPVC/BFR, MercuryBulit-in USB hub*XDoesn't containPVC/BFR, MercuryUSB upstream port typeUSB Type-BCheffe faturesTexturedUSB upstream ports1Exterior finish typeTexturedViportSmartlinageSmartlinageDVI portSmartlinageDVI ports quantity1Recyclable packaging material100%DVI ports quantity1Heavy metals freeHg (mercury)HDMI version1.4Light sensorLobalphort stragentity1.4Compliance certificatesRelationageHDMI version1.4Compliance certificatesRelationageHDDPCompliance certificatesRelationageHDCP version1.4Compliance certificatesRelationageHDCP version1.4CertificationCale Lock, UKRANIAN, CCC, CECP, CEL, TUV Eye Confort certifiedHDCP version1.4CertificationRelationageHDCP version1.4Compliance certificatesRelationageHDCP version1.4CertificationCole, CL, UKRANIAN, CCC, CECP, CEL, TUV Eye Confort certifiedHDCP version1.4CertificationCole, CL, UKRANIAN, CCC, CECP, CEL, TUV Eye Confort certifiedFerenceMeantime b			Manual	
Detachable stand V Feet colour Black Sustainability certificates ENERGY STAR, TCO Ports & interfaces X Doesn't contain PVC/BFR, Mercury Built-in USB hub* X Deson't contain PVC/BFR, Mercury Sustainability certificates ENERGY STAR, TCO PVC/BFR, Mercury Number of upstream ports 1 Exterior finish type Textured Number of upstream ports 1 Exterior finish type Textured DVI port S Satainability certificates SmartImage DVI ports quantity 1 Regulatory Approvals CB: EPA: FCC Class B; ICES-003; CE DVI-D ports quantity 1 Regulatory Approvals CB: EPA: FCC Class B; ICES-003; CE DVI-D ports quantity 1 Regulatory Approvals CB: EPA: FCC Class B; ICES-003; CE DisplayFort quantity 1 Light sensor CB: EPA: FCC Class B; ICES-003; CE DisplayFort version 1.4 Light sensor CE: TUV Eye Comfort certificates DisplayFort version 1.2 LowBlue mode HDCP version <t< td=""><td></td><td>Black</td><td></td><td></td></t<>		Black		
Ports & interfaces Sustainability certificates Dean't contain ENERGY STAR, TCO POC/BFR, Mercury Built-in USB hub* X Dean't contain PVC/BFR, Mercury USB typeram port type USB Type-B Cther features Textured Number of upstream ports 1 Exterior finish type Textured USB Type-A downstream ports 5 Picture enhancement Recyclable packaging material SmartImage DVI-port ~ CB; EPA; FCC Class B; ICES-003; CE CH: FA; TUV Ergo; TUV/GS; SEMKO; CU-EA;; UKRAINIAN; CCC; CECP; CEL; TUV Ege Confort certified HDMI ~ Regulatory Approvals CB; EPA; FCC Class B; ICES-003; CE HDMI ports quantity 1 Heavy metals free Hg (mercury) HDMI version 1.4 Light sensor DisplayPort version 1.2 LowBlue mode Audio input X Compliance certificates ReHS Headphone out * Y Mark; TUV Ergo; TUV/GS; SEMKO; CU-EA; UKRAINIAN, CCC, CECP; CEL; TUV Eye Comfort certified HDCP Compliance certificates ReHS Headphone out * Compliance certificates RHS HDCP version 1.4 Certification CB; EPA, FCC Class B, ICES-003, CE Efformatics Post-co		4		Sharcontor
Built-in USB hub* × Doesn't contain PVC/BFR, Mercury Built-in USB hub* × Obesn't contain PVC/BFR, Mercury USB upstream port type USB Type-B Other features Textured USB upstream ports 1 Exterior finish type Textured USB Type-A downstream ports 5 Picture enhancement SmartImage Quantity - Recyclable packaging material 100% DVI-D ports quantity 1 Regulatory Approvals Mark: TUV Ergo; TUV/GS; SEMKO; CEL; TUV Eye Comfort certified HDMI ports quantity 1 Heavy metals free Hg (mercury) HDMI version 1.4 Light sensor DisplayPorts quantity 1.2 LowBlue mode Audio input × Compliance certificates RoHS Headphone out * Compliance certificates ROHS HDCP Certification Mark: TUV Ergo; TUV/GS; SEMKO, CU-EAC; UKRAINIAN, CCC, CECP, CEL; TUV Eye Comfort certified HDCP version 1.4 Compliance certificates ROHS HDCP v	Feet colour	Black		
Built-in USB hub* X USB upstream port type USB Type-B Other features Number of upstream ports 1 Exterior finish type Textured USB Type-A downstream ports 5 Recyclable packaging material SmartImage Quantity - CB; EPA; FCC Class B; ICES-003; CE DVI-D ports quantity 1 Recyclable packaging material CB; EPA; FCC Class B; ICES-003; CE HDMI* - CB; EPA; FCC Class B; ICES-003; CE CU-CLAC; UKRANIAN, CCC, CECP, CEL; UTV/CS; SEMKO; CU-EAC; UKRANIAN, CCC, CECP, CEL; UTV Eye Comfort certified DVI-D ports quantity 1 Heavy metals free Hg (mercury) HDMI version 1.4 Light sensor - DisplayPorts quantity 1.2 LowBlue mode - Audio input X Compliance certificates RoHS Headphone out * - Certification CB, EPA, FCC Class B, ICES-003, CE HDCP - - Compliance certificates RoHS HDCP version 1.4 Certification CB, EPA, FCC Class B, ICES-003, CE HDCP version 1.4 Certification CB, EPA, FCC Class B, ICES-003, CE HDCP version 1.4 Certification CB, EPA, FCC Class B, ICES-003, CE VESA mounting * -				
Use bysteam ports1Exterior finish typeTexturedNumber of upstream ports1Exterior finish typeTexturedQuantity5Picture enhancementSmartImageQuantity-Recyclable packaging material100%DVI portMark; TUV Ergo; TUV/GS; SEMKO; CEL; TUV Ergo; TUV/GS; SEMKO; CEL; TUV Ergo; TUV/GS; SEMKO; CEL; TUV Ergo Creating and the second and the			Other features	-, , ,
Name Displayment of the second				
quantity5Recyclable packaging material100%DVI portCB; EPA; FCC Class B; ICES-003; CEDVI-D ports quantity1Regulatory ApprovalsCB; EPA; FCC Class B; ICES-003; CEHDMI *HDMI *HDMI ports quantity1Heavy metals freeHg (mercury)HDMI version1.4Light sensorDisplayPorts quantity1EasyRead modeDisplayPort version1.2LowBlue modeAudio input×Compliance certificatesRoHS-HDCPCB; EPA; FCC Class B; ICES-003; CECB; EPA; FCC Class B; ICES-003; CEHDCPHDCPHDCP version1.4Compliance certificatesRoHS-HDCP version1.4CertificationCB; EPA; FCC Class B; ICES-003; CE-HDCP version1.4CertificationCB; EPA; FCC Class B; ICES-003; CE-Kark, TUV Ergo, TUV/GS; SEMKO, CU-EAC, UKRAINIAN, CCC, CECP; CEL; TUV Eye Comfort certified-FroometicsVESA mounting *Panel mounting interface100 x 100 mmCable lock slot *Cable lock slot typeKensington		1		
DVI portImage: Constraint of the pectaging interactionCBS: PAS; FCC Class B; ICES-003; CEDVI-D ports quantity1Regulatory ApprovalsCB: FPA; FCC Class B; ICES-003; CEHDMI *IHeavy metals freeHg (mercury)HDMI version1.4Light sensorCE: TUV Eye Comfort certifiedDisplayPorts quantity1EasyRead modeIDisplayPort version1.2LowBlue modeIAudio inputXCompliance certificatesRoHSHeadphone out *ICompliance certificatesRoHSHDCPICompliance certificationTO000 hHDCP version1.4CertificationCure Exp, FCC Class B; ICES-003; CEHDCP versionI.4Compliance certificatesRoHSHDCP versionI.4CertificationCompliance certificatesHDCP versionI.4CertificationCure Exp, FCC Class B, ICES-003; CEMark, TUV Ergo, TUV/GS, SEMKO, CL, CECP, CEL, TUV Ergo, TUV/GS, SEMKO,		5		-
DV-D ports quantity HDMI*1Regulatory ApprovalsMark: TUV Ergo; TUV/GS; SEMKO; CU-EAC; UKRAINIAN; CCC; CECP; CEL; TUV Eye Comfort certifiedHDMI ports quantity1Heavy metals freeHg (mercury)HDMI version1.4Light sensor✓DisplayPorts quantity1EasyRead mode✓DisplayPort version1.2LowBlue mode✓Audio inputXCompliance certificatesRoHSHeadphone out *✓Mark: TUV Ergo; TUV/GS; SEMKO; CEL; TUV Eye Comfort certifiedHDCP✓Compliance certificatesRoHSHDCP version1.4Compliance certificatesRoHSHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CE Mark, TUV Ergo, TUV/GS; SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CEL, TUV Eye Comfort certifiedHDCP version1.4CertificationSB, EPA, FCC Class B, ICES-003, CE Mark, TUV Ergo, TUV/GS; SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CEL, TUV Eye Comfort certifiedFregonmicsISecuritySemKo, CU-EAC, UKRAINIAN, CCC, CECP, CEL, TUV Eye Comfort certifiedVESA mounting *IPost-consumer recycled plasticS5%Panel mounting interface100 x 100 mmLogistics dataCable lock slot *✓ForsitonS282510Cable lock slot typeKensingtonI			Recyclable packaging material	
HOM ports quantityIRegulatory ApprovalsCU-EAC; UKRAINIAN; CCC; CECP; CEL; TUV Eye Comfort certifiedHDMI *·IHeavy metals freeHg (mercury)HDMI version1.4Light sensor·DisplayPorts quantity1EasyRead mode·DisplayPort version1.2LowBlue mode·Audio inputXCompliance certificatesRoHSHeadphone out *··CB, EPA, FCC Class B, ICES-003, CEHDCP··CertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version··CertificationCB, EPA, UV/CS, SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CELHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEMark, TUV Ergo, TUV/GS, SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CELCertificationCB, EPA, FCC Class B, ICES-003, CEMDCP version1.4CertificationCB, EPA, CC Class B, ICES-003, CEMark, TUV Ergo, TUV/GS, SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CL-EAC, UKRAINIAN, CCC, CECP, CL-EAC, UKRAINIAN, CCC, CECP, CLVESA mounting *·Post-consumer recycled plastic85%Panel mounting interface··Consumer recycled plastic85285210Cable lock slot *··Harmonized System (HS) code85285210	•	-		
HDMI ports quantity1Heavy metals freeHeavy metals freeHeavy metals freeHDMI version1.4Light sensorDisplayPorts quantity1EasyRead modeDisplayPort version1.2LowBlue modeAudio inputXCompliance certificatesRoHSHeadphone out *Mean time between failures (MTBF)70000 hHDCPCertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEAC (power) inCertificationCB, EPA, CC Class B, ICES-003, CEFeronmicsCertificationSB, EPA, CC Class B, ICES-003, CEVESA mounting * </td <td></td> <td></td> <td>Regulatory Approvals</td> <td></td>			Regulatory Approvals	
HDM/ version1.4Light sensorreg (metal),DisplayPorts quantity1Light sensorDisplayPorts quantity1.2LowBlue modeAudio inputXCompliance certificatesRoHSHeadphone out *<				•
DisplayPorts quantity1Eagn BachageCompliance of the service of the s			Heavy metals free	Hg (mercury)
DisplayPort version1.2LowBlue modeAudio inputXCowBlue modeHeadphone out *Compliance certificatesRoHSHeadphone out *Mean time between failures (MTBF)70000 hHDCPCertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEAC (power) inCertificationCB, EPA, FCC Class B, ICES-003, CEFrgonomicsRecycling dataVESA mounting *Post-consumer recycled plastic85%Panel mounting interface100 x 100 mmLogistics dataEogistics dataCable lock slot *Harmonized System (HS) code85285210			Light sensor	1
Audio inputXLowBlue mode✓Audio inputXCompliance certificatesRoHSHeadphone out *✓Mean time between failures (MTBF)70000 hHDCP✓✓CertificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4CertificationCertificationCB, EPA, FCC Class B, ICES-003, CEAC (power) in✓Poteconsumer recycled plasticSoftwark, TUV Ergo, TUV/GS, SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CEL, TUV Eye Comfort certifiedVESA mounting *✓Post-consumer recycled plastic85%Panel mounting interface100 x 100 mmLogistics dataSoftwareCable lock slot *✓✓Harmonized System (HS) code85285210			EasyRead mode	1
Headphone out *·Compliance certificatesRoHSHeadphone out *·Mean time between failures (MTBF)70000 hHDCP··ErtificationCB, EPA, FCC Class B, ICES-003, CEHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEAC (power) in··Parel mounting interfaceInterfaceVESA mounting *·Post-consumer recycled plastic85%Panel mounting interface·Post-consumer recycled plastic85%Cable lock slot *··Harmonized System (HS) code85285210			LowBlue mode	1
Headphone out *·Mean time between failures (MTBF)70000 hHDCP··CB, EPA, FCC Class B, ICES-003, CEHDCP version1.4CertificationCB, EPA, FCC Class B, ICES-003, CEAC (power) in··CertificationCU-EAC, UKRAINIAN, CCC, CECP, CEL, TUV Eye Comfort certified Ergonomics VESA mounting *·Post-consumer recycled plastic85%Panel mounting interface100 x 100 mm Loistics data Loistics dataCable lock slot *··Harmonized System (HS) code85285210	•	×	Compliance certificates	RoHS
HDCP version1.4CertificationCertificationCertificationCertificationCertificationCertificationCertificationMark, TUV Ergo, TUV/GS, SEMKO, CU-EAC, UKRAINIAN, CCC, CECP, CEL, TUV Eye Comfort certifiedAC (power) inRecycling dataRecycling dataVESA mounting *Post-consumer recycled plastic85%Panel mounting interface100 x 100 mmConstitue dataConstitue dataCable lock slot * </td <td>Headphone out *</td> <td>1</td> <td></td> <td>70000 h</td>	Headphone out *	1		70000 h
AC (power) in Image: Constraint of the second of the sec	HDCP	1		
AC (power) in CEL, TUV Eye Comfort certified Ergonomics Recycling data VESA mounting * Panel mounting interface 100 x 100 mm Cable lock slot * Cable lock slot type Kensington	HDCP version	1.4	Certification	5
VESA mounting * Image: Construction of the second	AC (power) in	1		
Panel mounting interface 100 x 100 mm Logistics data Cable lock slot * ✓ Cable lock slot type Kensington	Ergonomics		Recycling data	
Cable lock slot * ✓ Harmonized System (HS) code 85285210 Cable lock slot type Kensington Kensington Kensington	VESA mounting *	1	Post-consumer recycled plastic	85%
Cable lock slot * ✓ Cable lock slot type Kensington	Panel mounting interface	100 x 100 mm	Logistics data	
Cable lock slot type Kensington	Cable lock slot *	J.		85285210
Height adjustment *	Cable lock slot type	Kensington		
	Height adjustment *	1		



8712581764272

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.