

APC APDU9981EU3 power distribution unit (PDU) 24 AC outlet(s) 0U Black

Brand : APC Product code: APDU9981EU3

Product name: APDU9981EU3

- APC Rack PDU 9000 Switched, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19
- With Industry leading reliability, manageability, and security, APC Switched Rack PDU's provide advanced load management plus on/off outlet level power cycling and sequencing control
- Includes: Installation guide, Rack mounting brackets, Safety guide, Serial configuration cable Rack PDU 9000 Switched, ZeroU, 11.0kW, 230V, (21) C13 & (3) C19

APC APDU9981EU3. PDU types: Switched, Rack capacity: 0U, Type: Three-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 1.8 m, Certification: CUL listed, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003,.... Nominal input voltage: 400 V, Maximum current: 16 A, AC input frequency: 50 - 60 Hz. Width: 55 mm, Depth: 46 mm, Height: 1792 mm



Design		Power	
Type Three Rack capacity * 0U	/ertical	Load capacity Maximum input current per phase Maximum total current draw per phase Maximum power	11040 VA 16 A 16 A 11000 W
Display	LCD	Weight & dimensions	
On/off switch	✓	Width	55 mm
Ports & interfaces		Depth	46 mm
AC outlets quantity *	24 AC outlet(s)	Height Weight	1792 mm 7 kg
Power plug	IEC 60309	Packaging data	, kg
AC outlet types *	C13 coupler, C19 coupler		0.05 km
Features		Package weight Package width	8.95 kg 165 mm
Daisy chain	✓	Package depth	114 mm
Reset button	1.8 m CUL listed, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, UL listed, VDE	Package height	2002 mm
Cable length		Operational conditions	
Certification		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-5 - 45 °C -25 - 65 °C 0 - 95%
Power		Storage relative humidity (H-H)	5 - 95%
Nominal input voltage *	400 V	Operating altitude	0 - 3048 m
AC input frequency	50 - 60 Hz	Non-operating altitude	0 - 15240 m
Maximum current *	16 A		
Nominal output voltage	230 V		
Output voltage	230 V		





731304404262

0731304404262

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.