

## **APC BVX700LI uninterruptible power supply (UPS) Line-Interactive** 0.7 kVA 360 W 4 AC outlet(s)

Brand : APC

Product code: BVX700LI

Product name : BVX700LI

## 700VA, 230V, AVR, 4x IEC Sockets, Black

APC BVX700LI. UPS topology: Line-Interactive, Output power capacity: 0.7 kVA, Output power: 360 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 7 Ah, Battery voltage: 12 V. Form factor: Compact, Product colour: Black, International Protection (IP) code: IP20. Width: 31 mm, Depth: 138 mm, Height: 98 mm





Features		Battery	
UPS topology *	Line-Interactive	Battery voltage	12 V
Output power capacity *	0.7 kVA	Battery life (max)	2 year(s)
Output power *	360 W	Battery recharge time	8 h
Waveform *	Sine	Cold start	1
Input operation voltage (min) $st$	170 V	Design	
Input operation voltage (max) *	280 V	Form factor *	Compact
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	230 V	LED indicators	
Output operation voltage (max)	230 V		
Output frequency	50/60 Hz	International Protection (IP) code	
Output frequency regulation	0.5 Hz	Certification	CB, CE, EN/IEC 62040-1, EN/IEC 62040-2
Output voltage regulation	10%		
Automatic Voltage Regulation (AVR)	) 🗸	Operational conditions	
Surge energy rating	273 J	Operating temperature (T-T)	0 - 40 °C
Response time	6 ms	Storage temperature (T-T)	-15 - 40 °C
Input power factor	0.51	Operating relative humidity (H-H)	0 - 95%
Noise level	40 dB	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 3000 m
Audible alarm(s)	<ul> <li>Image: A set of the set of the</li></ul>	Weight & dimensions	
	Alarm when on battery, Battery	Width	31 mm
Audible alarm modes	replacement, Low battery alarm, Overload alarm	Depth	138 mm
		Height	98 mm
Ports & interfaces		Weight	4.5 kg
AC outlet types	C13 coupler	Package width	222 mm
Power plug	C14 coupler	Package depth	346 mm
AC outlets quantity	4 AC outlet(s)	Package height	142 mm
Battery		Package weight	4.5 kg
Battery technology	Sealed Lead Acid (VRLA)		

Battery		Packaging data	
Battery capacity	7 Ah	Cables included Manual	Input power cable
		Logistics data	

Publication date: 21-DEC-2024. Prints or copies of Information are only valid on the printed Publication date

Harmonized System (HS) code

85078000





731304404484

0731304404484

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.