


NETGEAR MSM4310 Managed L3 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) 1U Black

Brand : NETGEAR

Product code: MSM4310-100NES

Product name : MSM4310



- 8 2.5G PoE++ ports with 2 25GBASE-X SFP28 uplinks.
- Comes with one APS254W power adapter providing 119W of base PoE budget.
- Half-width form factor enables one or two switches in a single rack space
- Up to three APS254W power adapters provide up to 551W PoE budget and/or N+1 redundancy
- The PoE budget can reach 551W, when the redundant PoE budget is 119W (1+1) or 322W (2+1).
- Virtual Chassis stacking provides non-stop forwarding (NSF) and hitless failover.
- Layer 3 feature set includes static, policy-based, and dynamic routing.
- NETGEAR IGMP Plus™, NETGEAR AV OS, and Engage Controller speed up AV installations.
- SMPTE ST 2110 Grand Master Clock and Boundary Clock for AES67 and ST2059-2 applications.
- Multi-color LED on each physical port reflecting the profile color in the NETGEAR AV OS™ and Engage Controller.

8x2.5G PoE++ (119W base, up to 551W) and 2x25G SFP28 Managed Switch

Management features		Multicast features	
Switch type *	Managed	Multicast Listener Discovery (MLD) snooping	✓
Switch layer	L3	Protocols	
Quality of Service (QoS) support	✓	Management protocols	SNMP V1, V2, V3
Web-based management	✓	GARP VLAN Registration Protocol (GVRP)	✓
ARP inspection	✓	Routing protocols	OSPF, OSPFv2, OSPFv3, RIP, RIP-1, RIP-2
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	8	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Stackable *	✓
2.5G Ethernet (copper) ports quantity	8	Form factor	1U
10G Ethernet (copper) ports quantity	8	Product colour	Black
SFP28 ports quantity	2	LED indicators	✓
Power connector	AC-in jack	Airflow direction	Front-to-back airflow
Network		Performance	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ak, IEEE 802.3bz, IEEE 802.3u	Built-in processor	✓
10G support *	✗	Processor model	ARM Cortex-A57
Full duplex	✓	Processor frequency	1800 MHz
Flow control support	✓	Memory type	DDR4-SDRAM
Link aggregation	✓	Internal memory	2048 MB
Broadcast storm control	✓	Flash memory	512 MB
Spanning tree protocol	✓	sFlow	✓
6to4 tunnel	✓	Power	
IPv4 routes	512	Power source *	AC
IPv6 routes	256	Power supply included *	✓
VLAN support	✓	Power consumption (typical)	133.5 W
Virtual LAN features	MAC address-based VLAN, Private VLAN, Voice VLAN	Power consumption (max)	351.5 W
Number of VLANs	4093	Power over Ethernet (PoE)	
Data transmission		Power over Ethernet (PoE) *	✓
Switching capacity *	140 Gbit/s	Power over Ethernet 4PPoE (PoE++) ports quantity	48
Throughput	372 Mpps	Power over Ethernet (PoE) power per port	90 W
		Total Power over Ethernet (PoE) budget	3314 W

Data transmission		Other features	
MAC address table *	16000 entries	Power supply	550 W
Store-and-forward	✓	Operational conditions	
Latency (10 Gbps)	2.27 µs	Operating temperature (T-T)	0 - 45 °C
Jumbo frames support	✓	Storage temperature (T-T)	-20 - 70 °C
Jumbo frames	12000	Operating relative humidity (H-H)	0 - 90%
Packet buffer memory	32 MB	Storage relative humidity (H-H)	0 - 95%
Security		Operating altitude	0 - 3000 m
DHCP features	DHCP Option 150, DHCP Option 66, DHCP Option 67, DHCP relay, DHCP server, DHCP snooping	Non-operating altitude	0 - 3000 m
Access Control List (ACL)	✓	Weight & dimensions	
Access Control List (ACL) egress	1023	Width	220 mm
Access Control List (ACL) ingress	511	Depth	300 mm
IGMP snooping	✓	Height	43.2 mm
IGMP proxy	✓	Weight	2.9 kg
MAC address filtering	✓	Packaging content	
Static port security	✓	Cables included	AC, USB Type-C
Loop protection	✓	Quick start guide	✓
BPDU filtering/protection	✓	Rack mount kit	✓
Authentication	Guest VLAN, MAC-based authentication	Packaging data	
Root protection	✓	Included power plug types	EU, UK, NA
Password protection	✓	Sustainability	
DoS attack prevention	✓	Sustainability compliance	✓
Authentication type	RADIUS, TACACS+	Certificates	
Queue scheduling algorithms	Strict Priority Queue (SPQ), Weighted random early detection (WRED)	Compliance certificates	BSMI, CCC, CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD)
Multicast features			
Multicast support	✓		



0606449172911



606449172911

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.