

NETGEAR 28-Port 10G Ethernet Smart Switch (XS728T)

Brand : NETGEAR

Product code: XS728T-100NES

Product name : 28-Port 10G Ethernet Smart Switch (XS728T)



ProSAFE XS728T - 24x 10GBASE-T copper ports, 4x SFP+ 1000/10GBASE-X fiber ports, 173.3W max., 41.6 dB, 5.04 kg
NETGEAR 28-Port 10G Ethernet Smart Switch (XS728T). Switch type: Managed, Switch layer: L2+/L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 24, USB 2.0 ports quantity: 1. Full duplex. MAC address table: 16000 entries, Switching capacity: 560 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack mounting



Management features		Security	
Switch type *	Managed	Security algorithms	802.1x RADIUS
Switch layer	L2+/L3	MAC address filtering	✓
Quality of Service (QoS) support	✓	Multicast features	
Web-based management	✓	Multicast support	✓
Ports & interfaces		Protocols	
Basic switching RJ-45 Ethernet ports quantity *	24	Management protocols	SNMP v1, v2c, v3
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Design	
SFP+ module slots quantity	4	Rack mounting *	✓
USB 2.0 ports quantity	1	Product colour	Black
Network		LED indicators	Activity, Link, Power
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Number of fans	4 fan(s)
	10G support *	Performance	
	Copper ethernet cabling technology	Built-in processor	✓
	Cable types supported	Processor frequency	800 MHz
Port mirroring	✓	Internal memory	512 MB
Full duplex	✓	Flash memory	256 MB
IP routing	✓	Noise level	41.6 dB
Flow control support	✓	Mean time between failures (MTBF)	514977 h
Link aggregation	✓	Power	
Rate limiting	✓	AC input voltage	100 - 240 V
VLAN support	✓	AC input frequency	50 - 60 Hz
Virtual LAN features	Private VLAN, Protocol-based VLAN	Power consumption (max)	173.3 W
Number of VLANs	512	Power over Ethernet (PoE)	
Data transmission		Power over Ethernet (PoE) *	✗
Switching capacity *	560 Gbit/s	Operational conditions	
MAC address table *	16000 entries	Operating temperature (T-T)	0 - 50 °C
Store-and-forward	✓	Operating relative humidity (H-H)	0 - 90%
Latency (10 Gbps)	11.649 µs	Operating altitude	0 - 3000 m
		Weight & dimensions	
		Width	440 mm
		Depth	310 mm
		Height	43 mm

Data transmission		Weight & dimensions	
Number of queues	8	Weight	5.04 kg
Number of static routes	128	Packaging content	
Jumbo frames support	✓	Cables included	AC
Jumbo frames	10000	Quick start guide	✓
Packet buffer memory	3 MB	Rack mount kit	✓
Security		Certificates	
DHCP features	DHCP server, DHCP client		
Access Control List (ACL)	✓	Certification	CE, FCC Cl. A, VCCI Cl. A, Cl. A EN 55022 (CISPR 22), Cl. A C-Tick, EN 55024, CCC
Access Control List (ACL) rules	164		
IGMP snooping	✓	Logistics data	
		Harmonized System (HS) code	85176990



0606449107241



606449107241

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.