

610R/T

DVI Rx/Tx Extender over Ultra-Reach MM Fiber



The 610T and 610R are a detachable optical transmitter and receiver for sending DVI signals with resolutions of up to 1920x1200 at 60Hz over LC optical cable. The 610T attaches to the transmitter side of a fiber optical cable and the 610R connects to the receiver end and both are sold as a set

FEATURES

Max. Data Rate - 4.95Gbps (1.65Gbps per graphic channel) Standards Compliance - Certified for medical applications according to IEC 60601-1-2 (Electromagnetic Compatibility) HDTV Compatible Not HDCP Compliant System Range - Up to 400m (1312ft) EDID Capture - Copies and stores the EDID from a display device (610T) Cable - Multimode fiber optic cable with 4 simplex or 2 duplex LC fiber connectors Power - External power adapter (supplied) or 5V DC from source | DVI



TECHNICAL SPECIFICATIONS

INPUTS:	Single-link DVI-D on a DVI-I connector (610T); 4 LC optical connectors for R, G, B & clock (610R)
OUTPUTS:	4 LC optical connectors for R, G, B & clock (610T); single-link DVI-D on a DVI-I connector (610R)
RESOLUTION:	Up to WUXGA @60Hz (1.65Gbps)
HUMIDITY:	Operating: 5% to 65%; Storage 5% to 95%
POWER CONSUMPTION:	5V DC, 240mA max. (610T); 390mA max. (610R)
INCLUDED ACCESSORIES:	2 power supplies

